

UNCLASSIFIED

AD NUMBER

AD908190

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies only; Test and Evaluation; FEB 1973. Other requests shall be referred to Army Engineering Laboratory, Aberdeen Proving Ground, MD 21005.

AUTHORITY

HEL ltr dtd 8 Aug 1989

THIS PAGE IS UNCLASSIFIED

U. S. ARMY

Technical Memorandum 4-73

HISTORICAL DOCUMENTATION OF THE INFANTRY HELMET RESEARCH AND DEVELOPMENT

USAMC Five-Year Personnel Armor System

Technical Plan

Charles W. Houff
Joseph P. Delaney

February 1973
AMCMS Code 564M.55.L40

HUMAN ENGINEERING LABORATORY



ABERDEEN PROVING GROUND, MARYLAND

Distribution limited to U. S. Government agencies only; test and evaluation; February 1973.
Other requests for this document must be referred to Director, U. S. Army Human Engineering Laboratory, Aberdeen Proving Ground, Md. 21005

Destroy this report when no longer needed.
Do not return it to the originator.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Use of trade names in this report does not constitute an official endorsement or approval of the use of such commercial products.

HISTORICAL DOCUMENTATION OF THE INFANTRY HELMET

RESEARCH AND DEVELOPMENT

USAMC Five-Year Personnel Armor System

Technical Plan

Charles W. Houff¹
Joseph P. Delaney¹

February 1973

APPROVED: 

JOHN D. WEISZ

Director

U. S. Army Human Engineering Laboratory

¹ Human Factors Group, Biomedical Laboratory, Edgewood Arsenal, Md.

U. S. ARMY HUMAN ENGINEERING LABORATORY
Aberdeen Proving Ground, Maryland

Distribution limited to U. S. Government agencies
only; test and evaluation; February 1973.
Other requests for this document must be referred
to Director, U. S. Army Human Engineering Labora-
tory, Aberdeen Proving Ground, Md. 21005

ABSTRACT

This report documents the history of U. S. infantry helmets from 1917 to 1971. Major topics are presented in separate sections: Ballistic Protection, Materials Technology, Suspension and Retention, Acoustic Characteristics, Eye Protection and Visual Field, Anthropometrics and Mathematical Models of the Head, Wound Ballistics, and Funding. Discussion of helmet design includes one-piece versus two-piece (shell and liner), one size versus multiple sizes, pad versus multiple-web suspension, and area coverage. The current evaluation procedure, Casualty Reduction Analysis, is also discussed.

The report concludes that the helmet program contained in the USAMC Five-Year Personnel Armor System Technical Plan adequately addresses the major problem areas established by this documentation. It concludes further that the systems approach is appropriate for problems of incompatibility and for optimizing the total ballistic protection for the combat soldier.

FOREWORD

The work contained in this report was funded by the U. S. Army Natick Laboratories, Natick, Mass., under project number 1J664713DL40. The original objective was to retrieve, review and evaluate all pertinent data concerning the research, development, testing and evaluation of the M1 steel helmet and liner. It soon became apparent that, to place the entire helmet development program in perspective, the scope of the report should be expanded to include the efforts that preceded the M1 helmet and those that have followed the adoption of the M1 as the standard helmet.

The authors are extremely grateful for the assistance of Miss Jois Williams of the Biomedical Library at Edgewood Arsenal, Md. Her technical competence and cheerful enthusiasm were a major factor in the acquisition of the literature to document this report. The timely and unfailing support of Mrs. Mary Starr in the voluminous typing is also gratefully acknowledged.

CONTENTS

FOREWORD	ii
ABSTRACT	iii
INTRODUCTION	1
DEVELOPMENTAL HISTORY	2
World War I	2
1920-1934	2
1935-1940	2
World War II	2
Post-World War II	3
Post-Korea and Vietnam	3
HISTORY	3
BALLISTIC PROTECTION	14
MATERIALS TECHNOLOGY	25
SUSPENSION AND RETENTION	32
ACOUSTIC CHARACTERISTICS	41
EYE PROTECTION AND VISUAL FIELD	44
ANTHROPOMETRICS AND MATHEMATICAL MODELS OF THE HEAD	46
WOUND BALLISTICS	50
FUNDING	52
DISCUSSION	58
CONCLUSIONS	62
REFERENCES	65

TABLES

1. Titanium-Alloy Helmets Developed Between 1965 and 1968	8
2. Helmet, Infantry-Development (Long Range)	11
3. Standard and Experimental Helmet Data	27
4. Materials Program	29
5. Helmet Suspension Materials	33
6. Acoustical Characteristics of Helmets	43
7. Helmet Fields of Vision	45
8. Advantages and Disadvantages of One-Size Versus Multiple-Size Helmets	48
9. Helmet Sizes and Suspensions	49
10. Contract Program — Helmet, Lightweight (LINCLOE) for Ground Troops	52
11. Contract Program — Nylon Helmet Liner	53
12. Contract Program — Titanium Helmet for Ground Troops	54
13. Contract Program — M-1 Steel Helmet	55
14. Contract Program — Siege Helmet	55
15. Personnel Armor Materials and Items — Industry Proposals to Natick Laboratories — FY 69	56
16. Personnel Armor Materials and Items — Industry Proposals to Natick Laboratories — FY 70	57

HISTORICAL DOCUMENTATION OF THE INFANTRY HELMET

RESEARCH AND DEVELOPMENT

INTRODUCTION

The Human Factors Group of the Biomedical Laboratory at Edgewood Arsenal, Md., was requested by the Human Engineering Laboratory to retrieve, review and evaluate all pertinent data concerning research, development, testing and evaluation of the M1 Steel Helmet and Liner. This historical documentation was accomplished as a Work Unit, HLR-5, of the U. S. Army Materiel Command Five-Year Personnel Armor System Technical Plan (1971).

The initial step was to retrieve all documents available on infantry helmets from the Defense Documentation Center (DDC), Natick Laboratories Technical Library, Aberdeen Proving Ground and Edgewood Arsenal Technical Libraries, Medical Literature Analysis Retrieval System (MEDLARS), and Scientific Technical Information Office (STINFO).

A chronological history of the U. S. infantry helmet from 1917 to 1971 was prepared from the documents retrieved. To gain a perspective on the M1 helmet, it was concluded that a history of all U. S. infantry helmet development should be included. Therefore, the history covers the M1917, M1917A1, M1 and all documented experimental models developed as candidate replacements for these standard models up to 1971.

Specific problem areas were identified, general overviews of the problem areas encountered and attempted solutions were traced. These problem areas are not mutually exclusive nor exhaustive and include ballistic protection with the associated problems of material, area coverage, silhouette and weight, and lack of stability on the head (or suspension and retention).

The solution to ballistic-protection problems center on materials technology. The specific goal is to increase protection, consistent with human factors, against the projected threat.

Of equal importance to ballistic protection are human factors elements such as weight, weight distribution, presented target area, off-set from the head, ventilation, comfort, stability, hearing, vision-area coverage and protective capability. These parameters directly influence soldier acceptance and the probability of wear of any headgear under combat conditions.

Utilizing casualty reduction analysis and expressing protection in terms of casualty reduction will enhance the combat soldier's ability to understand and appreciate the capability of any protective system.

The developmental history shows that the problem areas discovered during development of the M1 helmet and liner, as well as subsequent candidate helmets, are those addressed by the USAMC Five-Year Personnel Armor System Technical Plan. This detailed plan will generate the basic data to perform the trade-off analysis necessary to optimize future ballistic headgear as a component of the overall ballistic protective system for the combat soldier.

The value of this report is that it establishes what has been done, what approaches have been tried, and for what reasons they have been accepted or rejected. The documentation should eliminate approaches offering little probability of success or illuminate areas previously rejected for reasons that now appear invalid.

DEVELOPMENTAL HISTORY

The historical documentation that follows shows that infantry helmet research and development activity has increased during periods of hostility. Generally the period 1917-1971 can be divided into eras as follows: World War I; 1920-1934; 1935-1940; World War II; post World War II through Korea; post-Korea and Vietnam. It is also evident that helmet research and development over the years can be identified by category of effort.

World War I

The first U. S. Army protective helmet was the British Mk I, which was adopted during World War I, since the British could furnish helmets while the U. S. was setting up production. The Mk I, with a U. S. modification to the suspension system, was designated as the U. S. Model 1917. Concurrently, research was initiated to develop a "distinctly American" helmet. The most promising model, #5, was rejected as being too similar to the pot-shaped German field helmet.

1920-1934

Further testing of experimental models and retesting of the Model 5 between 1920 and 1934. In 1934, the M1917 was modified by the addition of hair-filled pads to the suspension system and designated the M1917A1.

1935-1940

The M1917A1 remained the standard U. S. helmet until 1940, when the Chief of Infantry requested a new helmet. The TS3, a pot-shaped helmet shell with removable liner incorporating a suspension system, was then developed.

World War II

In 1941, the TS3 was tested and approved and designated the U. S. Steel Helmet, M1. During the war, research and development efforts were initiated to improve that standard helmet.

Post-World War II

After World War II, helmet research and development continued in two main directions: (1) to improve the M1 helmet and (2) to develop a helmet to replace the M1 as standard. Product-improvement efforts have included research in ballistic materials for both the helmet and liner, and research to improve the suspension/retention system.

New helmet-development programs have included ballistic materials and suspension/retention systems and have also considered new shapes, sizes, etc. A specific requirement to lighten the infantry soldier's load (the LINCLOE program) led to ballistic-materials research principally in titanium, polycarbonates, nylon, and composites of different materials.

Post-Korea and Vietnam

In 1968 two specific helmet concepts were introduced. The siege helmet was an effort to provide more protection for the head, at an increased weight, in non-mobile situations. The Hayes-Stewart helmet was proposed to give greater coverage at decreased weight and to provide a variety of sizes for greater comfort and stability.

The helmet-development chronology is completed with the approval of a complete and comprehensive development program, the USAMC Five-Year Personnel Armor System Technical Plan (1972). This plan includes both short-range and long-range development programs to be accomplished within the AMC Laboratories. Partial documentation of helmet efforts during the first year of this plan is included in the report.

HISTORY

Men wore helmets and armor for protection against enemy armaments as early as 1015 B.C. Materials used included hair-filled hides, quilted cloth, wood, and various types of metals. Since the armorers of all eras have the task of providing protection, the quality of armor protection increases with the technology of the times to counter the weapons of the times. Armor was also often stylized to provide prestige, recognition and identification as well as protection. But the sheer weight of armor required to protect the wearer defeated the mobility required on the battlefield, and the advent of firearms in the 15th Century began a decline in use of armor. Although specialized armor continued to be worn through the Napoleonic Wars and was reported in isolated instances in the American Civil War, helmets and armor had disappeared from the dress of the U. S. soldier before World War I. Excellent historical accounts of helmets and body armor are provided by Crowell (72), Dean (76), Studler (274), and Coates and Beyer (53).

The early stages of World War I emphasized mobility, but as the war progressed, it became static and developed into trench warfare. Mobility became secondary to a requirement for protection in the trenches from artillery and mortar fire. All the authorities in the field give Intendant-General Adrian of the French Army credit for re-instigating the use of a metal helmet in World War I.

Observing his troops in 1915 General Adrian learned that one of the poilus had been saved from a serious head wound because he had been wearing his metal food-bowl, whereupon the general had a steel skull-cap calotte made to wear under his kepi. Later convinced of its effectiveness, he had helmets fabricated for the French Army which resembled the helmets of firemen. These "casque Adrian," were credited with providing at least partial head protection against lower-velocity fragments.

The French completely equipped their army with helmets in 1915-1916, the British and Germans in 1915, and the Belgians and Italians in 1916. Of special interest is the Mk 1 helmet issued to the British. When the U. S. entered the war in 1917, it had no helmet in its inventory. The Army General Staff reviewed the helmets of its allies and provisionally selected the Mk 1 for issue to U. S. troops. This helmet was already in production and could be bought from the British. The Mk 1 was not ideal since it protected a smaller area of the head than the French and was heavier than the French, but it was simple to manufacture and gave good ballistic protection. Some 400,000 Mk I helmets were shipped to France between July and November, 1917, to equip arriving U. S. troops.

The Mk I helmet was made of manganese steel .036 of an inch thick, weighed approximately two pounds, and contained an integral suspension system. When the U. S. started its own production of helmets, it changed the metal alloy to improve ballistic performance (10% improvement over Mk I) and modified the lining design to provide a cotton-twine mesh. Additionally, the cowhide chin strap was replaced with a web strap and a new buckle arrangement was added. By February, 1918, 700,000 American-made helmets had been delivered. By 11 November 1918, more than 2,700,000 American M1917 helmets had been produced.

Even while the M1917 was being tooled up and produced, the Army Ordnance Department was engaged in developing experimental helmets to replace it. Design objectives of this development were multiple: patriotic, to design a distinctly American helmet; diplomatic, to avoid a charge of favoritism in selecting a foreign helmet; and functional, to provide a superior helmet for U. S. troops.

Numerous design models were developed in the period 1917-1918 to provide additional protective coverage, improved ballistic properties, more adequate suspension, adaptability for special applications (such as tank or aircraft operations), and a distinctive patriotic design.

Some 15 infantry and special-purpose models were developed. Models 2, 3, 4, 5A, 6, 8 and 10 were infantry helmets; 7 was a sentinel's helmet; 9 was a machine gunner's helmet; 12 was a tanker's helmet; 14, 14A and 15 were aviators' helmets; and the Liberty Bell was a variant of Model 4. All these models are described and illustrated in Dean (76). For a variety of reasons, ranging from difficulty of manufacture to unacceptability of design, none of the experimental helmets were adopted in World War I.

The most promising of these experimental models was Model 5A. It had a pot-shaped design, weighed two pounds 6 ½ ounces, offered maximum protection for its weight, and was claimed easy to produce. The Model 5A was designed by the Metropolitan Museum of Art in conjunction with the Ordnance Department, and it was strongly recommended by the General Staff. The Swiss Model 1918 closely resembled the 5A but was independently developed (Dean, 76).

During the period 1918-1940, Ordnance Department research and development continued to strive for an acceptable helmet that offered increased area coverage and improved ballistic protection when compared with the M1917 - M1917A1, and modified the suspension system to make the helmet more stable and thus facilitate troop acceptance.

Comparative service tests of the 5A and M1917 were conducted in 1926 (274). The M1917 was continued as the standard helmet because it afforded greater ballistic protection, was lighter and interfered less with rifle firing. Further comparative tests of helmet-steel composition again proved the M1917 superior, so in 1932 testing of pot-shaped helmets was stopped. In 1934 the M1917 lining was changed to a hair-filled pad and the helmet standardized as the M1917A1 (274). This helmet weighed two pounds 6 ounces.

Between 1934 and 1940, Coates and Beyer report that a lull in helmet development occurred until 1940, when the first draft call was issued. New overtures were made to American industrial firms and to the Metropolitan Museum of Art in an attempt to improve the protective coverage and ballistic limit of the M1917A1 helmet and to take advantage of recent advances in steel alloy manufacture, liner materials, and mass production methods. In addition, a 2-piece helmet was considered desirable to meet the increasing variety and complexity of tactical and climatic conditions. The first problem to be solved was to determine the desired characteristics and a satisfactory shape for a helmet. This problem was given to the Infantry Board, which stated in a report:

Research indicates that the ideal shaped helmet is one with a dome shaped top and generally following the contour of the head, allowing sufficient uniform headspace for indentations, extending down in the front to cover the forehead without impairing necessary vision, extending down on the sides as far as possible without interfering with the use of the rifle or other weapons, extending down the back of the head as far as possible without permitting the back of the neck to push the helmet forward on the head when the wearer assumes the prone position, to have the frontal plate flanged forward to form a cap style visor, and to have the sides and rear slightly flanged outward to cause rain to clear the collar opening (274).

These characteristics address the problems of providing increased area coverage for the soldier's head, more stability than existed in the M1917A1, compatibility with the soldiers equipment and military tasks, (and therefore soldier acceptability). Interestingly enough, the Infantry Board mentioned neither increased ballistic protection nor weight.

Based on the characteristics enumerated, a helmet was developed which basically was the dome of the M1917 with the rim cut off, extended down on all sides, and flanged to provide a visor and to allow rain run-off.

Materials technology indicated that the best ballistic protection to be attained was provided by the Hadfield manganese steel which had been used in the M1917. The pot-shaped helmet was then modified to improve the visual field and sized to provide a uniform standoff.

The helmet was suspended and retained by a fiber liner which fitted into and could be secured to the steel helmet. This liner incorporated a modified Riddell football-helmet suspension system. The proposed helmet and liner system, designated as the TS3, had a total weight of three pounds, with the steel shell weighing 2.3 pounds and the liner and suspension system weighing 0.7 pounds.

During testing at Ft. Benning and at Aberdeen Proving Ground, the TS3 received favorable reports of more coverage, more comfort, more stability on the head, an acceptable visual field, non-interference with rifle firing and a better-than-expected ballistic performance. Where the M1917 specification required it to resist penetration by a 230-grain, caliber .45 bullet with a velocity of 600 feet per second, the ballistic test of the TS3 required penetration resistance by a similar bullet at 800 feet per second. A report from Aberdeen Proving Ground concluded that "The experimental helmet, TS3, is ballistically superior to the requirements for a military helmet" (274).

The TS3 received a favorable report from the Infantry Board in February 1941 as a successor helmet to the M1917A1 and it was standardized on 30 April 1941 as the Army M1 Helmet. It was approved on 9 June 1941.

When the M1 Helmet was standardized, the Ordnance Department was responsible for an initial procurement of approximately 962,000 helmets, including liners. After the initial procurement, the Ordnance Department retained responsibility for developing and procuring the steel helmet and the Quartermaster Corps was assigned responsibility for developing and procuring the helmet liner and suspension system.

Between 1941 and 1945 the Quartermaster Corps continued efforts to improve the M1 helmet liner and the Ordnance Corps continued efforts to develop an improved helmet shell. During the period August 1941 to August 1945, 22,363,015 M1 helmets were produced (53).

The Quartermaster Corps went to work to improve the "Hawley Type" compressed paper-pulp liner, and by July 1944 had developed and type-classified an improved impregnated cloth liner and improved headband and retaining clips. The neckband was modified so that it was more comfortable, provided more stability, and was both detachable and adjustable. Between 1942 and 1945 more than 3,900,000 liners were procured.

The Office of the Quartermaster General commented that "Even more interesting than the quantities procured is the variety of uses to which the liner was put:

It served as a field hat in temperate zones, as a sun helmet in the tropics, as protective headgear over a woolen cap or toque in cold climates, and of course as a lining for the steel helmet in all combat zones. Furthermore, modifications of the liner were used by jungle troops, parachutists, and armored troops." (207)

Additionally, the Quartermaster Corps initiated work to ascertain the possibility of replacing the liner and steel helmet with a plastic headgear which would be lighter yet offer better ballistic protection. Out of this work came the plastic armor material known as "Doron" (207). The Ordnance Corps made only one significant design change to the steel helmet assembly between 1941 and 1945, modifying the chinstrap fastener to incorporate a ball and clevis device which would automatically release at 15 pounds or more of pull. This redesign was incorporated to offset the possibility of injury to the cervical vertebrae under impact of a nearby detonation blast wave (53). Troop acceptability was fairly high, but a common complaint was lack of stability of the M1 helmet (53).

Although the M1 Helmet was standardized, investigative work to improve the helmet was continued. The Metropolitan Museum of Art, in conjunction with the Ordnance Department and Aero Medical Laboratory, designed three new helmets, the T21, 22 and 23.

The T21 shell had a curvature in all directions at all points in the helmet, established through anthropometric studies of the human head and purported to decrease size with no sacrifice of area coverage, yet increase strength and protection. It weighed two pounds, three ounces and was worn with the standard liner. The T22 was smaller than the T21 and was a one-piece helmet, worn without a liner. The T23 was larger than the T21 and incorporated a thicker liner.

Alternate ballistic materials investigated included Doron, and aluminum and nylon in combination. Helmets and liners using the alternate materials were the T24, T21E1, Doron Type 1 liner for the M1, and the Type II 24-ply nylon helmet.

The T24 helmet had an aluminum shell modeled after the M1, with a laminated nylon liner. The T21E1 utilized the nylon and aluminum but was based on the contour pattern of the T21 (53).

In spite of research and development efforts to field a better helmet than the M1, none of the experimental helmets proved to be sufficiently better than the M1 and none were standardized during the time that the Ordnance Corps had development responsibility for the M1 Helmet, although Army Field Force Board No. 3 commented favorably on the T21E2 and Doron Type II in July 1946 (319).

War Department Memorandum 30-5-2, dated 25 June 1947, assigned responsibility for developing end items of body armor to the Office of the Quartermaster General.

The period 1947-1951 saw research continuing on helmet and liner designs and on new material. The T21 was modified according to test report comments and became the T21E2, having additional coverage at the nape of the neck. However, with the additional coverage, weight increased to that of the M1. In January 1949, a decision was made to suspend development of the T21E2 and the non-ballistic tankers helmet and to concentrate on an all-purpose helmet. The first model was the EX49-3, which became the EX51 after test and modification. The EX51-1 was two-piece, having an aluminum shell and a 9-ply nylon liner. It had two sizes, small, to size 7 1/8, and large, size 7 and larger. The EX51-1 utilized the M1 suspension and weighed under three pounds. It was extensively tested (319, 67, 165, 166, 69, 167, 170).

Tests by Army Field Force Board No. 3 in 1952 concluded that the EX51-1 was unsuitable for the Army Field Force, pointing out that it exposed a larger area of the head to missiles, impaired hearing and interfered with communication equipment. Moreover, the hardware attachments were both fragile and difficult to operate. In this report, Board No. 3 stated that it had commented favorably in 1946 on the T21E2 and the Doron Type II and concluded that they were suitable for further development. The Board questioned the soundness of an "all-purpose helmet" (319).

An Army Helmet Conference at the Office of the Quartermaster General in Washington, D. C., 9-10 December 1952, decided to discontinue the all-purpose helmet and require two helmets -- one infantry and one combat vehicle crewmen -- and developed the military characteristics for these two helmets.

In 1953, the Combat Helmet T53-2 and T54-1 Helmet Liner were engineering-development (ED) tested and engineering service test (EST) quantities of these items were produced for testing in 1955. The T53-2 was a 35-ounce aluminum shell having a 15-ounce nylon liner. It increased the protected area by 10 percent, provided an improved suspension system, offered better ballistic protection and was considered to be more compatible with the armor vest than the M1.

The T54-1 was a four-ply 13 1/2-ounce nylon liner for the M1 steel shell. This ballistic liner had a V50 of 800 feet per second (fps) and increased the V50 of the M1 steel shell and T54-1 to 1300 fps, an increase of 250 fps. It also incorporated an improved suspension system.

Extensive tests were conducted on the T53-2 helmet and the T54-1 liner. These tests included materials, ballistic, wound ballistic, and field testing (144, 247, 248, 170, 171, 173). However, development of the two-piece T53-2 helmet was discontinued and efforts were concentrated on improving the helmet liner. The T55-2 nylon liner evolved with improved ballistic characteristics, and suspension. This liner was further tested and approved by Continental Army Command (CONARC) and recommended for adoption in March 1958 (321).

Purchases were initiated in 1959 and the liner was type classified in 1961. This liner remains the current standard.

In efforts to find an improved ballistic material for the shell, titanium was experimentally cold-formed in 1953, using the dies of the T53-2. Although weight was reduced from 38 ounces for the M1 Hadfield steel to 27 1/2 ounces, the titanium experiment was considered unsuccessful. Later attempts in 1957 attempted cold-forming titanium alloys, but these too were unsuccessful.

Interest continued in titanium-alloy helmets between 1965 and 1968, as the search continued for metals to satisfy the Lightweight Infantry Clothing and Equipment (LINCLOE) requirement for light weight. Four models were developed for test and evaluation:

TABLE 1

Titanium-Alloy Helmets Developed Between 1965 and 1968

Model	Gauge	Shell Wgt	Liner Wgt	Total Wgt
Type I	0.045	23 oz	12 oz	35 oz
Type II	0.052	27 oz	12 oz	39 oz
Type III	0.075	39 oz	12 oz	51 oz
Type IV	0.050	24 oz (w/sus)	None	24 oz

Techniques were studied for mass-production forming and helmets were successfully formed. The Army Materiel Systems Analysis Agency (AMSAA) conducted casualty-reduction studies on the 24, 39 and 51-ounce models and concluded that protection was directly related to area coverage and weight (328, 366, 241, 348).

Design studies were initiated in 1956. A contract was let to Egmont Arens to design, develop and evaluate helmet models. In 1957, a contract was let to Cornell Aeronautical Laboratory (86) to further evaluate the nine concepts submitted by Arens, to develop a one-piece helmet concept, and to develop, fabricate and evaluate suspensions and suspension systems for the T53-2, the standard M1 and the CVC helmet. From their work and from a review of Arens, a determination was made that a one-piece helmet with a movable neck shield showed the most promise (10). Cornell then modified this design, developed the Cornell One-Piece Shell, and recommended that the "visor-type" helmets be submitted for field tests. No data was retrieved from the literature of any tests that were conducted; however, the concept to date had not been accepted.

Material studies had been carried on to evaluate the ballistic qualities of candidate materials for helmets and body armor (180, 99, 315, 261, 100, 101, 102, 103, 104, 105, 106, 50, 51, 150, 151, 184, 185, 94, 95, 88, 135, 136). Attempts continued to form titanium as a helmet, and in 1965 a suitable mass-forming technique was developed to produce a titanium-alloy M1 helmet with increased ballistic protection at no increase in weight.

In 1965 the Quartermaster established a project called "Design Criteria for Combat Infantry Headgear." Also in 1965, a QMR generated a need for a lightweight helmet as a component of the "System of Lightweight Individual Combat, Clothing and Equipment Development (LINCLOE)" (341). This development project had as its goal a 24-ounce helmet for the infantry soldier to provide protection against fragmentation-type weapons. The program was initiated with two objectives:

(1) A lightweight interim helmet (35 oz.)

(2) A lightweight helmet (24 oz.).

Two approaches were followed — a one-piece nylon similar to the nylon liner incorporating a suspension system, and a two-piece polycarbonate helmet, having a polycarbonate shell and a nylon liner. Later, a one-piece titanium was added, similar to the nylon liner.

Simultaneously, contracts were let for suspension development and for casualty-reduction studies. The one-piece nylon work ceased when it was found that it was not equivalent to the M1. The one-piece titanium shell (24 oz.) was eliminated ballistically. The two-piece polycarbonate was eliminated because of poor resistance to hydrocarbons and to ultraviolet radiation.

In an Army Materiel Command (AMC) Helmet Conference held 16 May 1968, Brigadier General Hayes, Office of the Surgeon General, and Mr. George Stewart, Edgewood Arsenal, presented their concept of a new helmet design for use in Vietnam. The design resembled a Roman helmet with protection to the forehead, skull, back of the neck and temples; however, it was cut out over the ears. The one-piece helmet would incorporate a removable cushion-type suspension with a combination chin-nape strap. It would be constructed of nylon and have nine sizes. A test was conducted by the Infantry Board to determine stability, compatibility with equipment, evaluation of human factors engineering, soldier opinion of comfort, and soldier acceptability. Several shortcomings were found: the helmet was incompatible with the M17A1 mask and with body armor; it reduced vision for parachutists; and it was generally not properly human factors engineered. However, it was also found to be more stable and preferred by soldiers (111). In July 1969, AMC directed that a parallel effort be pursued (351). This effort would

include further work on the Hayes-Stewart Helmet and on a helmet that would be completely responsive to the Qualitative Materiel Requirement (QMR), since the Hayes-Stewart will not meet the QMR. The weight is to be approximately 24 ounces, but one or two additional ounces would not be an over-riding constraint if studies indicate such a requirement. Additionally, equal protection level is defined as:

Providing equal ballistic protection to an area of the head equal to that covered by the M1 Hadfield Steel Helmet against all 4 fragment simulators (1.35, 5.185, 17 and 44 grains) fired at 0 and 45 degrees obliquity (351).

Natick Laboratories (NLABS) requested the Army Materiel and Mechanics Research Center (AMMRC) on 27 August 1969 to recommend materials for both an interim and an optimum item. AMMRC replied on 13 November 1969 that an M1-configuration titanium helmet with standard nylon liner would meet the ballistic requirements and weigh 39 to 41 ounces. AMMRC also provided details on an experimental composite material for the optimum helmet.

An October 1969 engineering design test (EDT) to determine the compatibility of the modified Hayes-Stewart Helmet with standard fatigue uniform, body armor and mask with hood was reported from the USA General Equipment Test Activity, December 1969. This report generally concluded that the helmet was compatible with the clothing and mask, but incompatible with the 12-ply body armor; and that the foam-pad suspension system was not satisfactory, although it was more comfortable and equal to the M1 with respect to stability, preference and effect on performance. This report recommended redesign to overcome these aspects and further testing (157).

While development and testing was continuing on the LINCLOE program, efforts continued from 1966 through 1968 on the M1 Steel Helmet Product Improvement Program. These efforts resulted in a correlation of helmet thickness-V50 ballistic limit which allowed a thickness-inspection plan (259) of helmets fabricated from dual hardness steels. These steels were superior to Hadfield steel but ballistically inferior to titanium alloy.

In 1968 AMC directed NLABS to pursue development of a Siege Helmet (349, 341). Work was contracted for a suspension system and AMMRC was requested to recommend armor material. In the LINCLOE in-process review (IPR) in December 1969, a decision was made to hold this program in abeyance.

In December 1969, AMC directed that a program be initiated to provide information required for the development of LINCLOE and other new helmets. There was an acknowledged information gap in data required to provide a helmet for the 99th percentile population. Consequently, in January 1970, representatives of AMC, the Ballistic Research Laboratory (BRL), the Human Engineering Laboratory (HEL), Edgewood Arsenal, AMSAA and AMMRC met with NLABS to establish plans for an in-depth program. By March 1970 a draft helmet-development plan was prepared and submitted to AMC in July for incorporation into the overall Five-Year Personnel Armor System Technical Plan published in March 1971 (351, 330). The helmet program is divided into two phases, a short-range program and a long-range program. Table 2 lists the work units of the long-range program (330). The short-range program has not been included in tables.

TABLE 2

Helmet, Infantry - Development
(Long Range)

TECHNICAL AREA	WORK UNIT (1498)		LABORATORY	FUNDING 10 ³					
	No.	Description		71	72	73	74	75	76
Anatomical Analysis	1	Helmet, Infantry - Mathematical Model of the Head	ARDC-BRL						
	2	Helmet, Infantry - Verification of Math. Model of Head	NLABS						
	3	Helmet, Infantry - Configuration and Production of Research Prototypes	NLABS						
Human Factors Analysis	4	Helmet, Infantry - Sizing Evaluation of Prototype Helmets	NLABS						
	5	Helmet, Infantry - Documentation of M-1 Helmet & Liner	ARDC-HEL						
	6	Helmet, Infantry - Effect of Helmet Form on Hearing	ARDC-HEL						
	7	Helmet, Infantry - Human Factors Engineering Support	ARDC-HEL						
	8	Helmet, Infantry - Physiological Evaluation	ARIEM						
Casualty Criteria Analysis	9	Helmet, Infantry - Casualty Reduction Studies	ARDC-AMSAA NLABS						
	10	Helmet, Infantry - Casualty Criteria	ARDC-BRL						
Materials Development & Evaluation	11	Helmet, Infantry - Ballistic Testing	ARDC-BRL						
	12	See Table IV for Materials Program	AMMRC, NLABS						
Threat, Tactical Doctrine	13	Helmet, Infantry - Tactical Doctrine Interface	NLABS						
	14	Helmet, Infantry - Threat Analysis	ARDC-AMSAA						
Systems Development Plan	15	Helmet, Infantry - Systems Development Plan	NLABS ARDC-AMSAA ARDC-HEL ARDC-BRL						

Funding levels are not included. This information is available from USANLABS on a need-to-know basis.

TABLE 2 (Continued)

TECHNICAL AREA	WORK UNIT (1498)		LABORATORY	FUNDING 10 ³					
	No.	Description		71	72	73	74	75	76
Systems Development Plan	15	Helmet, Infantry - Systems Development Plan (cont.)	AMMRC CDC CONARC						
Reliability & Maintainability	16	Helmet, Infantry - Reliability and Maintainability Criteria	NLABS						
Design & Producibility Technology	17	Helmet, Infantry - Suspension Studies	NLABS						
	18	Helmet, Infantry - Retrieval and Analysis of Design Data	NLABS						
	19	Helmet - Infantry - Fabricate Experimental Helmets	NLABS						
	20	Helmet, Infantry - Fabricate ET/ST Helmets	NLABS						
Coordinated Testing & Evaluation	21	Helmet, Infantry - Coordinated Test Plan	NLABS						
Utilization Doctrine	22	Helmet, Infantry - Establishment of Utilization Doctrine	NLABS						
Production Engineering	23	Helmet, Infantry - Production Engineering Effort	NLABS						
Specifications & Quality Assurance	24	Helmet, Infantry - Establish Systems Specifications	NLABS						
	25	Helmet, Infantry - Establish a Type B2 MIL-STD-490 Critical Item Developmental Spec.	NLABS						
	26	Helmet, Infantry - Establish a Type C2b MIL-STD-490 Critical Item Product Fabrication Spec.	NLABS						
	27	Helmet, Infantry - Establish System Technical Data Pkg.	NLABS						

TABLE 2 (Continued)

TECHNICAL AREA	WORK UNIT (1498)		LABORATORY	FUNDING 10 ³					
	No.	Description		71	72	73	74	75	76
Final Evaluations	28	Helmet, Infantry - Engineering and Service Testing	NLABS-TECOM						
Personnel & Training Requirements	29	Helmet, Infantry - Personnel and Training	CONARC						
Management Review	30	Helmet, Infantry - Annual Technical Review of Plan	NLABS						
		Total Funding/FY							
		Program Total							
		Funding by Laboratories	AMMRC ARIEM ARDC-AMSA ARDC-BRL ARDC-HEL Edgewood NLABS Contract TECOM/GETA USABAAR						
		*Funded Outside the Program							

On 13 September 1971 a presentation was made to the Military Personnel Supplies Committee on Helmets of the National Academy of Science's National Research Council Advisory Board in Washington wherein the Five-Year Armor Program was introduced by NLABS. Work accomplished within that program was presented by NLABS, Edgewood Arsenal, BRL, AMMRC and AMSAA in the areas of Ballistic Materials Studies, Casualty Reduction Studies, The M1 Helmet Documentation, Studies to Improve the M1 Suspension, Algorithm for Sizing Helmets, and Human Engineering.

At the Working Committee Meeting No. 3 at HEL, APG, Md. on 15-16 December 1971, William C. Wright, program manager of the Five-Year Personnel Armor System Technical Plan, presented "Recommendations to Establish Standardized Casualty-Reduction Analyses Reporting" (324).

These recommendations were adopted by the committee with the addition of the M-43A1 Grenade as a threat. No documentation on these recommendations has been provided beyond this date.

BALLISTIC PROTECTION

Protection to the head involves a combination of many factors including environmental protection, eye protection, hearing protection, protection from concussive shock, compatibility with equipment such as the gas mask and communication equipment, comfort, and protection against the multiples of combat threats such as the threat posed by ballistic missiles.

The ballistic threat must be defined and analyzed; then protective headgear must be designed to afford the optimum protection consistent with the other factors involved. The true protection requirement, then, results from trading off many parameters, with the major constraints being primarily materials capability and human factors considerations. This systematic approach to protective headgear is currently being pursued under the USAMC Five-Year Personnel Armor System Technical Plan. The ballistic threat for the development of the new generation of personnel armor has been established by the Foreign Science Technology Center and further refined by AMSAA for inclusion in the AMC Armor Plan as Classified Appendix IV.

The ballistic threat from a casualty-producing standpoint has been shown to be primarily from fragmenting-type munitions, as reported by Dean (76), Coates and Beyer (53), Wound Data and Munitions Effectiveness Team (WDMET) and others.

Although the threat has been established as that of fragmenting munitions, the replication or simulation of this threat for evaluating armor materials and end items has been a major problem.

The section on "The Evolution of Ballistic Test Methods and Test Projectiles for Evaluating Armor Materials" which follows is a direct copy of Appendix A of reference 18 and is included in its entirety.

The Evolution of Ballistic Test Methods and Test Projectiles For Evaluating Armor Materials

Ballistic evaluation of lightweight fragment-resisting armor by simulation of service conditions of attack has been a continuously changing problem because of new specialized weapons and materials which are continually being introduced.

During World War I, fragment-resisting armor (the first U. S. modern helmet¹), was tested with caliber .45 ball ammunition only because it was a standard service round which could be defeated by the helmet. Consequently this ammunition was adopted for evaluating the ballistic performance of fragment-resisting armor. As the years passed on, this test was questioned by many research laboratories and testing stations. The mechanism of penetration by the very deformable mushrooming pistol ball projectile is markedly different from that of steel or cast iron shell fragments which were the major cause of battlefield casualties. Armor materials that offer superior resistance to caliber .45 ball ammunition may provide reduced resistance to HE shell fragments. It has also been found, to the great confusion of testing facilities, that the caliber .45 ball, M1811, ammunition was far from being sufficiently uniform in production and in ballistic performance to be satisfactory for use in ballistic testing and evaluation. (The lack of uniformity did not affect its suitability for combat use). This test was replaced by one using a fragment-simulating projectile.

Another early empirical approach was the array test (or arena test, "Yankee Stadium" test). A test was conducted by placing test samples in a circular arrangement² (varying the radius from the point of detonation) and detonating a HE shell placed at the center of the circle. These tests were evaluated on a statistical basis in an effort to obtain reliable and reproducible results. The ballistic characteristics of the armor were expressed in a number of ways, such as (a) the number of perforations per unit area of armor surfaces; (b) the percent of impacting fragments which perforate the armor; and (c) the residual energies of perforating fragments which may be evaluated by means of a series of witness plates placed behind the armor. The number of witness plates one behind the other, which could be perforated provided an index of the residual energy possessed by the fragments. A large area was needed to conduct these tests, which were very costly since many samples were placed around the shell in order to obtain statistical data. This type of test is still employed occasionally. This test suffers from the limited sampling by the armor of the non-uniform distribution of fragment sizes, shapes and weights. The results are dependent upon the selected height of burst; the detonation is static instead of dynamic; no information is obtained that associates fragment weight and velocity with penetration.

A similar test, which was employed to evaluate personnel armor, was set up by the Army Ordnance Corps³ during World War II. Armor materials were tested by a controlled fragmentation side-spray test. A 20MM shell, HEI MK-I, was statistically detonated inside a rectangular or triangular box test set-up. Three or four recovery boxes 12"x12" were used to recover the fragments that perforated the armor samples being tested. (See Figure 1 for a triangular test arrangement). A total of twenty 2024-T3 aluminum alloy sheets, 0.020" thick, were spaced at one-inch intervals behind the armor samples. The 20MM shell was suspended nose-up in the center of the square or triangle, and the shell was statically detonated. The HE fragments which perforated the test panels were recovered and identified as to the box and zone number in which the fragments came to rest. The firing process was repeated until the desired number of samples had been tested. The recovered fragments were weighed and the weighted totals computed accordingly to set standards. Some of the disadvantages of these tests were: (1) they were cumbersome; (2) they required a large quantity of test panels; (3) they were expensive to perform; (4) they yielded data difficult to reduce to simple expressions of ballistic merit such as a merit factor or a ballistic limit. Other disadvantages cited for the array test also apply here.

A controlled forward spray type of test was employed by the Naval Proving Ground, Dahlgren, Virginia⁴, for rating lightweight armor materials. In this test a 20MM HEI shell is fired with a striking velocity of 2700 ± 50 feet per second at a 0.125" cold-rolled mild steel plate (hardness of $RB50 \pm 10$), which is called a triggering plate since it detonates the HE shell. The armor sample which is being tested is mounted normal to the line of fire and three feet beyond the triggering plate. The triggering plate is positioned so that the projected line of fire passes through the center area of the triggering plate and through the center area of the test sample. The result of any round whose center of impact on the mild steel triggering plate is greater than 5" from the center of the detonating plate is discarded. The firing process is repeated for a number of samples. A statistical analysis is made on the number of complete penetrations obtained for given areal densities of armor. The material which has the least number of penetrations for a given areal density is rated as the best from a protection viewpoint. This test has the characteristics cited for the array test except it is a dynamic test. However, the triggering plate provides additional fragments that impact the armor.

Multiple cube testing was investigated after World War II. In this test approximately 31 cubes of uniform weight were fired in a phenolic plastic sabot. The 3/16", 1/4", 5/16", 3/8" and 1/2" cubes employed weighed 13, 31, 61, 104 and 245 grains respectively, and were hardened to a hardness of Rockwell "C" 23 to 28. The plastic sabot which contained the number of cubes of uniform size was fired from a rifled 57MM M1 gun, and the velocity of the forward cube was measured and taken to be representative of the velocities of all cubes. The mean velocity and percentage of complete penetrations were determined for each round fired. A V_{50} limit velocity* and a limit penetration coefficient** were computed and used as a basis for comparing material. Other criteria used in obtaining ballistic limits are given on Inclosure 1 of this Appendix. Criticism of this test include; (a) there were variations in results since the measured velocity employed was that of the fastest cube, whereas a velocity distribution actually existed, (b) the velocity spread between the highest measured velocity and the mean velocity varied considerably, especially for the smaller size cubes, and (c) the non-uniform dispersion of cubes from round-to-round added to the confusion and caused difficulty in interpretation of results.

*A V_{50} limit velocity is an estimate of the mean velocity at which, on the average, 50% of the cubes striking the target will defeat it. A defeat is considered to have occurred when there is a through hole in the target which will allow the cube or major portion thereof to pass through.

**A limit penetration coefficient F is defined as follows:

Where: M = Cube Mass (grains)
 e = Equivalent plate thickness (inches)
 A = Cube face cross section (inches)
 V_{50} = Limit velocity (feet per second)

$$F = \frac{M}{e} \times \frac{V_{50}}{A}$$

The multiple cube test was abandoned in favor of the single cube test. Steel cubes of known sizes were sheared from cold rolled square bar stock having a hardness of approximately 28 Rockwell "C". The cubes were individually mounted in plastic carriers (See Figure 2) and fired from rifled guns. The plastic carrier provided for rotation and gas seal for the missile. The cube broke out of the carrier upon emerging from the muzzle of the gun and traveled downrange to the target. The cube may impact the target with various orientations including those for which an edge, corner, or side is presented. These variations increase the scatter in the ballistic evaluation because the shape factor of the cube varies from impact to impact depending upon how the cube strikes the target. Its average shape factor is within the range of values for fragments. Cubes have been used for several decades and are still being used for wound ballistic studies and for input data into casualty reduction assessments. Obtaining either a random or a specified set of orientations has proven difficult.

Single and multiple sphere types of ballistic tests have been conducted by some research establishments in evaluating fragment-resistant armor. In the single sphere test the sphere is launched from a smooth-bored gun (or the sphere can be placed in a plastic cup and launched from a rifled gun). In a multiple sphere test a plastic sabot is employed to launch spheres. These tests are similar to the cube tests that were described in the preceding paragraphs. A major disadvantage of this test is that spheres do not have jagged or sharp edges. As a result they do not exhibit the same mechanism of penetration as HE shell fragments. Also, the sphere geometry is limited to one value of shape factor.

Another method of assessing the performance of armor for protection against shell fragments, which was developed by Watertown Arsenal Laboratories, consists of detonating a standard HE shell, recovering the fragments, screening them into weight classes, and then selecting and firing individual shell fragments from a given weight class at the armor sample to determine a V_{50} ballistic limit in the conventional fashion; i.e., firing enough fragments of a selected weight group. The shell fragments are individually mounted in plastic cups (Figure 2) in which they are held in place by sealing wax and fired from standard rifled guns. The fragment breaks out of the cup upon emergence from the gun tube and proceeds down-range to impact the armor.

Although this method represented an improvement over previous tests it still has several limitations. First, it is necessary to secure and detonate HE shells, recover, screen, and weigh fragments — a not inconsiderable task. Furthermore, variations in mass, shape factor and geometry of shell fragments falling within one weight class introduce sufficiently wide scatter in test results (wide zone of mixed results), to necessitate firing a moderately large number of fragments to obtain a reproducible (V_{50}) ballistic limit. Finally, variations in the mechanical properties of shell steel are so wide that shell fragments display a broad range of deformation and fracture characteristics, thus influencing their ability to penetrate hard metallic armor materials and affecting the ballistic limit. However, against fabric or plastic armors which are relatively soft the projectile's hardness does not affect the ballistic performance significantly.

During World War II, Watertown Arsenal Laboratories experimented with design of fragment simulating projectiles for evaluating personnel armor¹⁵. A homologous series (1.35 to 830 grains) of fragment simulating projectiles (Figure 2) were developed, which consists essentially of cylinders having blunt, chisel-shaped noses and raised flanges at their bases to act as gas-seals and rotating bands^{16&17}. These missiles are hardened to Rockwell "C" 28-32. This hardness level was selected after determining that this represents the average hardness range of recovered fragments of detonated 20MM, 37MM and 105MM HE shell of domestic manufacture. Ballistic tests of these fragments simulating projectiles demonstrated that they were stable in flight and rated personnel and lightweight armor on a basis compatible with experience.

Firing a fragment simulating projectile is fairly simple compared to testing with HE shell or individually-fired shell fragments. In addition, the scatter of the resulting data is quite small thereby providing greater accuracy and reproducibility with a minimum number of rounds.

These projectiles are currently used for material studies, for the evaluation of armor end items and for acceptance testing of personnel armor production. The test projectiles are procured through the use of Military Specification MIL-P-46593, Projectile, caliber .22, .30, .50 and 20MM Fragment-Simulating. A test procedure is given by Military Standard MIL-STD-662, Ballistic Acceptance Test Method for Personal Armor Material.

At the time of its development it was recognized that it did not match ballistic limits obtained with actual fragments fired individually in some cases¹⁷.

A yawed dart projectile was developed by the Naval Research Laboratory for testing and screening experimental lightweight armor materials. The dart, Figure 2, is a cylindrical missile with 90° cones ground on each end and heat treated to a very high hardness (approximately Rockwell C 60-63) so that the projectile is essentially nondeforming during impact. The technique used for making controlled yaw impacts involves firing into a ballistic plate testing pendulum at close range through a blast deflector. A light upsetting or tipping plate is fastened to the rear of the blast deflector in such a position that the dart missile will graze the edge of the upsetting plate. Projectile yaw develops depends upon the dart velocity. Precise velocity control is desirable both for the purpose of closely bracketing limit velocity points and for the purpose of maintaining accurate control of yaw. Generally, the dart missile is deflected such that it will impact the armor broadside. A sufficient number of complete and partial velocities are fired so that the limit velocity may be calculated. The yaw dart missiles provide less kinetic energy per unit presented area than do most shell fragments. Its shape factor is at the high end of the range for munition fragments, but is lower than shape factors for most fragment simulators.

Parallelepipeds, (Figure 2) flat-end right circular cylinders and hemispherical nose-type missiles and others have also been investigated and employed in the ballistic testing of armor. Tests have shown that each of these missiles differ somewhat in its mechanism of penetration into an armor material. When metallic armor is perforated by HE shell fragments, there are two principal ways or mechanisms by which the perforation is effected. These may be called the "pushing-aside" or "ductile" mechanism and the "plugging" or "shearing" mechanism. In the first, the missile forces its way through the armor by displacing the material sideways, building up a bulge on the front surface and depressing the back surface and laterally compressing the material in the interior of the plate. The harder the material the more resistant it is to lateral displacement. Thus, when the pushing-aside mechanism of penetration is the one that occurs, the resistance to penetration increases with increasing hardness of the armor. The plugging mechanism involves the shearing out from the metallic armor of a cylindrical disc, which is ejected ahead of the missile. There is relatively little deformation and no lateral compression of armor when this type of penetration occurs. Harder materials tend to plug more readily and completely than softer materials, and thus above a certain hardness, the plugging mechanism of penetration is involved, and the resistance to penetration decreases. Armor much harder than the projectile may deform or shatter it. Other factors besides hardness of the armor which determine the mechanism of penetration include the following:

1. Ratio of plate thickness to size of the HE fragment; the larger the presented area of the missile at impact, the greater the tendency toward penetration by the plugging mechanism.

2. Blunt-nosed missiles tend to plug the metallic armor while sharp-nosed missiles tend to pierce and laterally displace the plate material. When plugging occurs, less energy is absorbed than when penetration is affected by the pushing-aside mechanism. Since shell fragments are blunt missiles, the penetration of armor by HE fragments generally involves plugging. Perforation of some materials such as aluminum and magnesium alloys, which are soft and overmatch (armor thickness greater than the projectile diameter) the projectile, is effected by a combination of the two mechanisms of penetration. The material is displaced sideways during the first stage of penetration and then finally plugs when the fragment approaches the rear surface of the plate.

Residual velocity measurements can be obtained for most of the tests that have been discussed by instrumenting the test set-up with added electronic measuring equipment or by photography. Measurement of the energy absorption of a material from a penetrating missile can be readily calculated from the difference in kinetic energy of the missile before and after penetration. Three measurements are required for each round fired: the mass of the projectile; its striking velocity as it contacts the target; and its residual velocity as it just leaves the target.

Ballistic Research Laboratories at Aberdeen Proving Ground have conducted extensive tests^{10, 11, 12}, on residual velocity investigations. The velocity-reducing characteristics of materials when impacted by various missiles are useful in developing lethality and vulnerability data for use in the design of experimental armored vehicles and in making estimates of casualty reduction offered by various personnel armors. The behavior of most armor materials is similar. As the striking velocity is increased from a very low velocity to the ballistic limit of the material, theoretically no complete penetration occurs. When the striking velocities are in excess of the ballistic limit, the fragment will pass through the material with a residual velocity, the amount of which depends upon the excess of the striking velocity over the ballistic limit. As the striking velocity tends to approach the striking velocity. When the striking velocity of the missile is considerably in excess of the ballistic limit, damage to the plate generally becomes less severe and more localized, and less energy is absorbed during penetration. Glass and ceramic faced composites show more of a straight line relationship between residual and striking velocities.

The difficulty of measuring the velocity of a given fragment in the presence of a shower of other fragments of metallic armor thrown from the back of the plate also affects the test results on some residual velocity measurements. For nonmetallic armor there may be no secondary missiles thrown off the back of the armor. In rigid plastic armor, (Doron and bonded nylon), when striking velocities approach the ballistic limit the material is damaged by splitting and bending. Deformation of these plastic materials is greater when there is no perforation since all of the missile's energy is absorbed by the material.

The measurement of transient and permanent deformation in a material may be necessary in testing fragment-resistant armor materials. This information is useful to designers of helmets and helmet liners so as to enable the headpiece to have the required offset (distance between the head and the inside of the headpiece). A helmet¹³ can have extensive transient and permanent deformation when impacted by the missile at velocities approaching the ballistic limit. The full force of the impact may well be transmitted to the head behind the helmet, and serious and extensive wounds may result even though the helmet has not been perforated. When deformation tests are conducted, a ballistic limit is first obtained on the end item and then velocities are selected, which are slightly less than the ballistic limit velocity, since maximum deformation and damage occurs at this velocity level. Elaborate instrumentation is required to obtain transient deformation ballistic data¹³.

BALLISTIC LIMITS

All ballistic penetration tests may be termed as a resistance-to-penetration type of evaluations. The resistance of a material against penetrating forces of missiles which are classified as penetrators is measured. These penetrators may be of any regular or irregular shape and may be applied to materials at either slow or rapid rates of loading. An illustration of a commonly used static type of penetration (indentation) test with a spherical indenter is the Brinell test for hardness measurements. The Brinell hardness of a metallic material is nothing more than the resistance-to-penetration of that material by a spherical penetrator applied at slow rates of loading under definite conditions of test. The ballistic test for resistance-to-penetration is an illustration of rapid rates of loading with various shaped objects known as projectiles, missiles or fragments. The material under this condition is the armor. At the high rates of application of load, the resistance that the material offers is a result of a complex combination of factors (physical, mechanical and metallurgical) which are affected by high rates of strain. To date there is no one simple measure of the resistance-to-penetration of armor. Instead, there are in use several measures of the resistance-to-penetration of armor. Each of these is based more or less on practical considerations and is expressed as the striking velocity of a given projectile or fragment causing a preselected amount of damage. Therefore, the amount of preselected damage serves as the criterion for these different measures of penetration. Three such criteria, the Army, Protection and Navy Ballistic Limits, which are employed in rating armor materials are defined as follows:

Army Ballistic Limit — The critical or limit velocity at which the specified projectile will be borderline in penetrating the armor being impacted according to the "Army" criterion. (Although historically it was first employed in Army studies, it should only be considered at present as a term which defines a specific type of ballistic limit). In this ballistic test a complete penetration occurs whenever a projectile or fragment has penetrated the armor sufficiently to permit at least a pinhole of light to pass through a hole or crack developed in the armor, or the front of the fragment or nose of the projectile can be seen from the rear of the armor. A partial penetration occurs when lesser damage to the armor occurs.

Protection Ballistic Limit — The critical or limit velocity at which the specific projectile will be borderline in penetrating the armor being impacted according to the "Protection" criterion. In this case a complete penetration occurs whenever a fragment or fragments from either the impacting projectile or the armor are caused to be thrown from the back of the armor with sufficient remaining energy to pierce a sheet of 0.020" thick 2024-T3 aluminum alloy placed parallel to and 6" behind the target. Any fair impact which rebounds from the armor plate, remains embedded in the target, but with insufficient energy to pierce the 0.20" thick aluminum alloy witness plate, is termed a partial penetration.

Navy Ballistic Limit — The critical or limit velocity at which the specified projectile will be borderline in penetrating the armor being impacted according to the "Navy" criterion. Although historically it was first employed in Naval activities, it should only be considered at present as a term which defines a specific type of ballistic limit. In these ballistic tests a complete penetration occurs whenever the entire projectile or essentially the entire projectile passes completely through the armor. All other penetrations are classified as partial. No witness plates are employed in these tests.

Employing the above criteria, in assessing partial and complete penetrations, a ballistic limit can be defined as a striking velocity (feet per second) of a kinetic energy fragment or projectile above which complete penetrations (as defined above) of the armor will predominate and below which partial penetrations of the armor will generally predominate. This is generally expressed as a Army, Protection or Navy (V_{50}) ballistic limit and is a critical velocity of a fragment or a projectile at which 50% complete penetrations and 50% partial penetrations of the armor target can be expected on a limited statistical test. A protection (V_{50}) ballistic limit is now generally employed by all of DOD is assessing the ballistic efficiency of armor materials.

The inherent variables within a material and the variables in any ballistic test such as slight difference in weights of projectiles, orientation of projectiles at time of impact, etc., introduce into the test a probable "zone of mixed results". As the name implies, this zone of mixed results may contain one or more impacts which completely penetrate the material under test at velocities below those of other impacts which fail to effect complete penetration. This zone of mixed results can vary up to several hundred feet per second depending upon projectile reaction and the mechanism of penetration. However, in tests of lightweight armor against fragment simulating projectiles, the zone of mixed results is generally less than 100 feet per second.

A protection (V_{50}) ballistic limit of fragment resistant materials is generally computed by averaging ten fair impact velocities comprising the five lowest velocities resulting in complete penetration and the five highest velocities resulting in partial penetration. A maximum spread of 125 feet per second is permitted between the lowest and highest velocities employed in the determination of the ballistic limit. In cases where the spread between the lowest complete and highest partial velocities is greater than 125 feet per second the ballistic limit shall be based upon 14 velocities, 7 of which result in the lowest complete penetrations and 7 which result in the highest partial penetrations. All velocities employed in the determination of the ballistic limit are corrected to striking velocities.

The Program on the Development of Improved Test Methodology for Evaluating Armor Materials Versus Fragmenting Munitions is contained in the USAMC Armor Plan (330) as Materials Work Unit No. 18, with the objective stated as "The development of an integrated ballistic testing system for personnel armor materials and end items;

1. Yields results that can be correlated by the use of appropriate factors or procedures to results derived from actual munition fragments. Direct simulation while acceptable is not considered essential.

2. Can be applied by the selection of appropriate options if necessary to, primarily: (a) the evaluation of materials being considered for armor applications, (b) the evaluation of flaws in materials or end items; and secondarily to: (c) provide the input data for casualty reduction assessments (d) the evaluation of production material and (e) the evaluation of newly developed armor items as part of the required engineering testing. For purposes of correlating the test methods and projectiles that will be developed with actual fragments, laboratory tests and analysis will be used to obtain ballistic data and comparisons of test projectiles with selected fragments covering a wide range of fragment shapes and sizes."

The work unit gives an excellent digest on munition fragments, characteristics of armor materials, and ballistic-test methods and projectiles.

In a report on the status of the methodology program (18), AMMRC reported the following:

a. There was some difficulty involving experimental methods for controlled shell-fragment launch and flight to obtain ballistic data on personnel armor materials. The problem was successfully resolved, and an experimental basis was developed for future experimental work in shell-fragment ballistic-data acquisition.

b. An improved model, which represents an improved method of data representation, was developed for residual velocity versus strike velocity. The model provides a technique for quantitatively comparing simulator residual-velocity data population and provides an objective method for dealing quantitatively with the question of shell-fragment residual-velocity data simulation.

c. Data indicate that the slope of the residual-velocity curve versus strike-velocity curve is very steep at the critical or cut-off velocity and changes abruptly to a constant value in a relatively short velocity range. That range has been identified as the velocity range over which data generation is most critical for defining the armor response to an attacking projectile and for distinguishing the relative performance of armor materials.

Pending completion of the above described effort, the AMC family has agreed to utilize the fragment simulators as a screening technique for armor materials and to employ "cube" projectiles with related residual velocity/striking velocity relationships as material input data into casualty-reduction methodology.

Under the USAMC Five-Year Personnel Armor System Technical Plan, the Army has agreed to employ casualty reduction to express the effectiveness of armor materials and end items. The Joint Service Materiel Need (JSMN) for a Personnel Armor System for Ground Troops (PASGT), which has been agreed upon by the Navy and Marine Corps and which is being prepared for world-wide coordination by the Combat Developments Command, reflects the statement and application of protective characteristics in casualty-reduction terminology.

The casualty-reduction methodology is reflected in models developed by AMSAA to predict reductions in casualties provided by helmets and body armors for ground troops. Detailed descriptions of these models are given in AMSAA Report No. 1, ARDC Report No. 2 and AMSAA Technical Memorandum No. 126.

The following extract from Appendix III of the USAMC Armor Plan prepared by AMSAA briefly describes casualty-reduction methodology:

...the models attempt to predict the number of casualties produced by a given fragmenting munition in a simulated battlefield environment. Two types of personnel targets are generally considered. These are armored and unarmored personnel. In one battlefield, no personnel wear the protective gear of interest (unarmored). In the other, all personnel wear the protective gear of interest (armored). The difference between the number of casualties predicted for the two battlefields (targets) is the number of casualties saved because personnel wore the protective gear of interest. Generally, reduction in casualties is expressed as a percentage of the number of casualties produced when the protective gear of interest is not worn. Several types of fragmenting munitions are usually considered in a casualty reduction analysis to cover a wide range of battlefield threats.

These casualty reduction models can be used to obtain answers to a number of important questions relating to personnel armor systems. Listed below are some limited studies that could be conducted with the models:

- The level of protection provided by end items.
- The alternative(s) of a given type of personnel armor system that maximizes protection.
- The candidate materials that appear most promising for the design of personnel armor systems.
- The effect of armor configuration and body area covered on protection.
- The effect of the weight of the personnel armor system on protection.

In broader systems analysis studies, the models can be used to assist in the estimation of the number of casualties saved in a hostile environment such as SEA or Europe. A casualty reduction model is a powerful tool that can be used in a number of different ways.

One of the most important aspects of casualty-reduction methodology is that the protective capabilities of materials and end items will now be expressed in a terminology that is meaningful from the standpoint of personnel survival, related to the real world and not in terms of V_{50} , etc., which did not, and does not, relate directly to protection. In other words, casualty-reduction analysis bridges a communication gap between the developer and user and should improve the probability of wear under combat conditions because the user in the future will be able to relate the protective capabilities of his equipment to the combat environment.

At Working Committee Meeting No. 3 on the AMC Five-Year Personnel Armor System Technical Plan, 15-16 December 1971, the AMC Program Manager, Mr. William C. Wright, included as an agenda item a Review of Casualty-Reduction Methodology and presented a prepared paper entitled "Recommendations to Establish Standardized Casualty Reduction Analyses Report" (377). This paper had as its objective "to achieve standardization and repeatability of casualty reduction analysis, to issue dissemination and reporting of non-conflicting and consistent results, and to insure that the AMC family is addressing the program and methodology inputs to meet agreed upon needs." Within the parameter of the term casualty reduction, characterizing personnel protective armor, the Army Materiel Systems Analysis Agency (AMSAA) has the responsibility for establishing the methodology and any changes to it. Performing activities, primarily the Army Materials and Mechanics Research Center (AMMRC) and Natick Laboratories (NLABS), are responsible for performing analyses properly.

Wright recommended two tables of criteria as a standard base for characterization. In both of the tables, Casualty Criteria are defined and quantified in ARDC Technical Report No. 2, September 1969, A Parametric Analysis of Body Armor for Ground Troops (367).

Table A would be used in material evaluations as would be prepared by AMMRC and NLABS. It considers ballistic data, coverage, casualty criteria and threats. Table B would be used for proposed system or component evaluations as would be performed by NLABS and verified by AMSAA. Table B considers the criteria in Table A, and in addition, data to support systems analysis, cost effectiveness and/or trade-off studies. These include, but are not limited to:

- a. Estimated cost of the item based on a lot size of 50,000 units.

- b. Projected Army user, i.e., mission profile.
- c. Weight of total system and each system component.
- d. Number of sizes.
- e. Estimated service life (years-min).
- f. Estimated storage life (years-min).
- g. Maintainability, scheduled hours per year.
- h. Personnel training requirements.
- i. Special maintenance equipment, if applicable.
- j. Production feasibility.
- k. Adequacy of available manufacturing techniques.
- l. Physiological assessment.
- m. Human factors parameters including compatibility, mission effectiveness, mobility, attitudes, sizing assessments.
- n. Projected environmental usage conditions.
- o. Assessment against all military-need (MN) characteristics.

As has been shown above, substantial progress has been made in the methodology of ballistic material evaluation, and the scope has been expanded to include the application of casualty-reduction methodology.

As reported by Coe (58), by Coates and Beyer (53), and by the R&D Liaison Office, Fort Benning, Ga., in interviews with returning Vietnam veterans, lack of stability of the M1 helmet has been and continues to be a complaint. Related to this complaint and to ballistic protection has been the requirement that the helmet must be off-set from the head a specified distance as a result of transient deformation of the helmet material when subjected to a hit.

Coates and Beyers (53) state that "A suitable offset will always be necessary to counteract the denting of a metallic helmet or the transient deformation of a non-metallic helmet, but the prime objective of any military protective headgear is to prevent the entrance of missiles into the cranial cavity. This entrance might be prevented over a wider range of missile weights and velocities by modification of the present effort concept in helmet design. The missile defeat might result in skull fractures in a number of casualties, but the skull fracture type of injury is amenable to successful treatment by the neurosurgeon."

Different materials react differently in resisting penetration and in defeating impinging missiles. One of the results of these differences is reflected in varying degrees of transient deformation which is critical to helmet design. Until recently, there was no standardized procedure for determining transient deformation. However, Prather and Hawkins of the Biomedical Laboratories of Edgewood Arsenal have reported, in the 1st Year Summary of Progress and Up-dated Milestone Schedule USAMC Five-Year Personnel Armor System Technical Plan, their successful effort to establish a standardized methodology for determining transient deformation of lightweight armor materials. Work is now progressing to develop from the procedure casualty criteria assessments for input into casualty-reduction models.

Conclusions

The USAMC Five-Year Personnel Armor System Technical Plan aggressively addresses the problem areas of determining adequate ballistic test methodology, and refinement of casualty reduction methodology.

MATERIALS TECHNOLOGY

As long as man has desired to protect himself with "armor," he has concerned himself with a search for better materials from which to fashion armor. Dean (76) gives a comprehensive survey of armor materials up through the end of World War I. Of particular interest to this documentation is a rank-ordering of factors involved in evaluating armor materials:

"Ballistic value	45%
Weight	15%
Comfort in wearing	10%
Security in support	10%
Ease of recognition and the opposite (non-visibility)	10%
Noiselessness	3%
Cleanliness	3%
Durability	2%
Adaptation	2%

Egmont Arens (10), in a contract for "Analysis of Design," considered materials to provide ballistic protection including transient deformation in a helmet. He stated that there were three variables in helmet design:

- (1) weight and material
- (2) size

(3) suspension

With respect to weight, Arens said that the maximum protection was desired for the smallest weight per inch and that thinking should be directed toward reinforced plastics.

An additional interesting reference in Dean (76) is that the "two layered condition... is but a reappearance of an ancient principle...that the best armor should have an outer skin of extreme hardness, which prevents the entrance of a missile, while the inner substance of the plate should be tenacious and prevent the armor from shattering." This principle resurfaced when the U.S. experimented with the ballistic liner and various hard shells.

Another aspect to be considered in armor development must always be the practicality and efficiency, including the cost per item, of mass producing helmets from a candidate armor. Sir Robert Hadfield's manganese steel was the choice for the U.S. M1917 Helmet, and after all the research and testing, was again the choice for the U.S. M1 helmet in 1941. During World War II, research in armor for helmets continued and as early as 1942 a glass laminate, DORON, was fabricated and tested (207) and found not acceptable as a replacement for the Hadfield steel. Still later tests by the U.S. Marine Corps found that it would not be practicable to replace the M1 steel helmet with the new plastic (DORON) helmet (159).

When the U.S. M1 steel helmet was standardized in 1941, the Quartermaster Corps initiated research on alternate materials for the helmet liner, feeling that a plastic liner would be superior to the resinated duck material (207). In 1947, the Quartermaster assumed entire responsibility for helmet development and production. In 1949, a project was initiated to develop an "all-purpose" helmet with an aluminum shell and a nylon liner. The helmets developed during the period 1949-1954 did not meet all the requirements of the Army Field Forces (AFF), and effort then was initiated to provide improved ballistic protection to the M1 through the use of a ballistic liner. The cotton duck liner, weighing 10 ounces, contributed little or no ballistic protection. A four-ply nylon liner, weighing approximately the same as the duck liner, provided 250 feet per second more ballistic protection, thus providing increased protection at no increase in weight (341). This liner was type classified and is the standard liner.

The search continued, however, for improved ballistic materials for helmets. Candidate materials included aluminum, polycarbonates, nylon, various steel alloys and titanium. Combination materials occurred when shells of aluminum, polycarbonate, other steels, and titanium were placed over a nylon liner. It may be generally said that of all the materials and combinations tested, none was found to be sufficiently promising to warrant adoption as the new helmet armor material. Although increased ballistic protection could be gained for a given weight of material, or equal protection for a smaller weight of material, testing indicated that none of these materials were satisfactory. In some of the promising materials, the production methods were unsatisfactory, and in essentially all candidate materials, the relative gains afforded by a new material or combination thereof were not considered to be cost-effective (Table 3) (92).

In 1968, Natick Laboratories received a report from AMSAA on casualty-reduction studies which essentially concluded that casualty reduction was directly related to area coverage and weight (350). In 1969, in direct response to an inquiry from NLABS, AMMRC replied that an M1-configuration titanium helmet with a nylon liner would meet the ballistic requirement and weigh 39-41 ounces. This appeared to satisfy the material requirement for an interim helmet, and AMMRC also provided classified details of a new composite material as a candidate for the optimum helmet of 24 ounces (351).

TABLE 3
Standard and Experimental Helmet Data^a

	Weight	Shell	Liner	Shell Area in ²	Liner Area in ²	Shell Areal Density (oz/ft ²)	Liner Areal Density	Composite Areal Density	Shell Material	Liner Material	Sizes
M1 Steel + Nylon Liner	50.0	40.0	10.0	190	170	30.3	8.5	37.8	Hadfield Steel	Ballistic Nylon Fab.	1
T21E2 Nylon + Alum	41.0	34	7						Aluminum	Nylon	4
E49-3 Alum + Nylon	38 41			154 195					Aluminum	7-Ply Nylon	2
E51-1 Aluminum	43 47	21 23	22 24						Aluminum	9-Ply Nylon	2
E53-2 Aluminum	51.0	35.5	15.6	204					Aluminum 24 ST	Nylon	1
T55-2 Nylon	14.5	N/A	13.5	N/A	170				N/A	4-Ply Nylon	1
Type III Titanium + Aluminum	50.0	40.0	10.0	190	170	30.3	8.5	37.8	Titanium Alloy	Ballistic Nylon Fab.	1
Polycarbonate Nylon Liner	22.0	12.0	10.0	187	170	9.2	8.5	16.9	Polycarbonate	Ballistic Nylon Fab.	1
One Piece Titanium	20.0	20.0	N/A	165	N/A	17.5	N/A		Titanium Alloy	N/A	1
One Piece Nylon	19.0	19.0	N/A	180	N/A	15.2	N/A		Ballistic Nylon Fab.	N/A	1

^a NLABS Ltr, 3 Sep 1970 (341).

Under the AMC Five-Year Personnel Armor System Technical Plan a search is continuing for materials for helmets and work is continuing on material evaluation in methodology.

As recommended by Wright (377) at Working Committee Meeting No. 3, 15-16 December 1971, a standardized evaluation and reporting procedure for materials has been adopted. In this procedure, Table A includes ballistic data, coverage, casualty criteria and threats. The procedure is to be used by AMMRC and NLABS in performing casualty-reduction analyses.

Under the USAMC Five-Year Personnel Armor System Technical Plan, a broad, aggressive materials research and development program directed toward materials of high casualty-reduction potential is being pursued.

The following is extracted from the Summary contained in the plan dated March 1971 (331):

The Materials Research and Development Program is concentrated on composite materials containing ceramics, textiles, polymers, and/or metals. It encompasses the following areas:

- (1) Establishment of the fundamental mechanism by which fragments are defeated.
- (2) Synthesis of new materials having required properties.
- (3) Development and optimization of composite compositions.
- (4) Experimental fabrication and processing of mock-up models.
- (5) The ballistic evaluation and medical assessment of the research product, and
- (6) Formulation of specific recommendations for hardware development.

The Armor Plan First-Year Summary of Progress and Up-dated Milestone Schedule dated March 1972 gave a further report:

A standardized high speed photographic methodology for determining transient deformation of armor materials has been achieved which will allow the evaluation of all potential armor materials. Effort is continuing to develop criteria for injury assessment from transient deformation.

An economic substitute (glass ceramic) for boron carbide (B_4C) for protection against fragments and ball projectiles has been established and development of material processing to employ this material in curved shapes for body armor applications is progressing. In this latter regard AMMRC has reported that "Pyrex glass helmet shapes can be made by press molding to cover the range of wall thicknesses of interest." (Materials for Personnel Armor, First Status Report to the Senior Steering Committee, 16 September 1971).

Flexible structures in ceramic composite armor have been demonstrated, and an extensive design effort is being applied to utilize these rigid and semi-rigid materials in helmet and torso armor applications.

TABLE 4

Materials Program

TECHNICAL AREA	WORK UNIT (1498)		LABORATORY	FUNDING 10 ³					
	No.	Description		71	72	73	74	75	76
Materials Development and Evaluation Research, Development Testing and Evaluation (RDT&E)	1	Development of Transparent Polymers for Armor	AMMRC						
	2	Effectiveness Analysis for the Development of Personnel Armor Materials	AMMRC						
	3	Synthesis of Boron Compounds	AMMRC						
	4	Ballistic Behavior of Composite Armor	AMMRC						
	5	Transparent Ceramics for Armor	AMMRC						
	6	Master Ballistic Penetration Curves and Tables	AMMRC						
	7	Nature of Fiber Deformation and Rupture Under Missile Impact	AMMRC						
	8	Research on Ceramic Gradient Armor	AMMRC						
	9	Spark Sintering of Metal - Ceramic Armor Materials	AMMRC						
	10	Transparent Armor Development	AMMRC						
		Total RDT&E Funded	AMMRC						
	11	Mechanical Processing of Polymer Into Sheet and Thin Film Armor	AMMRC						
	12	Metal/Metal Composites for Armor	AMMRC						
	13	Development of Advanced Ceramic and Ceramic/Metal Gradient Armor	AMMRC						

Funding levels are not included. This information is available from USANLABS on a need-to-know basis.

TABLE 4 (Continued)

TECHNICAL AREA	WORK UNIT (1498)		LABORATORY	FUNDING 10 ³					
	No.	Description		71	72	73	74	75	76
Materials Development and Evaluation Research, Development Testing and Evaluation (RDT&E)	14	Reactive Processing and Fabrication of Boron Ceramics into Helmet and Body Armor Components	AMMRC						
	15	Materials Processing Research of Composite Configurations	AMMRC						
	16	Energy Dissipation and Absorption Mechanisms in Personnel Armor	AMMRC						
	17	Evaluation and Application of Novel Improved Material Forms, Compositions and Arrays in Helmet and Body Armor Configurations	AMMRC						
		Total 1971 Unfunded							
		Total RDT&E	AMMRC						
Supporting Ballistic Test Methodology (R&D) and Armor Production (MM&TE), (O&MA)	18	Improved Test Methodology for Evaluation Armor Materials vs. Fragmenting Munitions	AMMRC BRL, EALabs NRL(Navy)						
	19	Engineering Support Data for Specifications	AMMRC, BRL NLABS						
	20	Processing MM&TE 1706073 of XP Proprietary Plastic Material for Lightweight Armor Applications	AMMRC						
		Total MM&TE, O&MA	AMMRC						
		Total AMMRC							
Research, Development, Test and Evaluation (RDT&E)	21	Toxicity Screening of Implantable Body Armor Material	EA Labs						
		Total EA Labs	\$1,100,000						

TABLE 4 (Continued)

TECHNICAL AREA	WORK UNIT (1498)		LABORATORY	FUNDING 10 ³					
	No.	Description		71	72	73	74	75	76
Materials Development and Evaluation (cont.) Research, Development, Test and Evaluation (RDT&E)	22	Textile Fiber Evaluation and Chemical Modification to Maximize Ballistic Performance	NLABS						
	23	Engineering of Textile Materials to Obtain Optimum Form Factors for Translation of Fiber Properties Into Fabrics	NLABS						
	24	Correlation of Fiber and Fabric Properties with Ballistic Performance	NLABS						
	25	Utilization of High Tenacity Textile Fibers in Laminate Form in Helmets and Body Armor	NLABS						
		Total NLABS							
		GRAND TOTAL MATERIALS							

Significant progress has been made in the toxicity study of candidate armor materials. To date preliminary measurement of acute toxicity in vitro for the following items has been completed: Boron Carbide, Silicon Hexaboride, Calcium Hexaboride, Al_2O_3 , ZrO_2 , TiO_2 , Y_2O_3 , woven roving and titanium.

To retain the unclassified status of this report, the classified contents of various materials reports are not being included but the reports may be obtained by qualified persons.

SUSPENSION AND RETENTION

Lewis, in his Military Helmet Design (154), indicates the great importance of the suspension system: "The suspension may be the deciding factor regarding level of protection, compatibility under various environmental conditions, and acceptance of a helmet design by the individual wearer and his unit." However, in spite of the importance of the suspension system, helmets seem to be designed with the suspension as an after thought to the ballistic shell. The requirements of suspension systems are presented by Lewis as are the general suspension designs that have evolved over the past 50 years. There are five general practical systems:

1. Several (multiple pads and a crown restrainer)
2. Multiple-web arrangements (triangulation system)
3. Continuous padding over the cranial area
4. Combination of flat springs and cap
5. Combination of the above

He further breaks the suspension system down into seven main subsystems:

1. Shell-to-suspension attachment
2. Offset
3. Headband or pad backing
4. Sweatband or pad backing
5. Weight-bearing crown
6. Shock absorbers
7. Chin and nape strap

Lewis also indicates the variety of possible materials that could be or have been used in the helmet suspension subsystems (Table 5).

TABLE 5

Helmet Suspension Materials^a

- | | | |
|--|--|--|
| <p>1. Shell-to-suspension attachment</p> <p>a. Rivets</p> <p>(1) Metal</p> <p>(2) Plastic</p> <p>b. Liner (Friction-held)</p> <p>(1) Textile laminates</p> <p>(2) Glass fiber laminates</p> <p>(3) Metal</p> <p>(4) Plastic</p> <p>c. Welded metal lugs or screws</p> <p>d. Web, cord, or bolts (through holes)</p> <p>e. Snaps</p> <p>f. Cement</p> <p>g. Slots or keyways</p> <p>(1) Metal</p> <p>(2) Plastic</p> <p>2. Spacing</p> <p>a. Metal</p> <p>(1) Spring</p> <p>(2) Rigid</p> <p>b. Webbing--natural or synthetic fibers</p> <p>c. Leather</p> <p>d. Cords or laces</p> <p>e. Plastic</p> | <p>f. Pads</p> <p>(1) Ununited fibers, natural and synthetic</p> <p>(2) Felts and bats, natural and synthetic</p> <p>(3) Plastic foam</p> <p>(4) Sponge rubber</p> <p>3. Headband or pad backing</p> <p>a. Textile webbing or cloth, natural or synthetic</p> <p>b. Leather</p> <p>c. Metal</p> <p>d. Plastic</p> <p>e. Textile or glass fiber laminates</p> <p>4. Sweatband or pad covers</p> <p>a. Leather</p> <p>b. Textiles, natural or synthetic</p> <p>c. Plastics</p> <p>d. Foam "skin"</p> <p>e. Latex film</p> <p>5. Weight-bearing crown</p> <p>a. Leather</p> <p>b. Textile, natural or synthetic</p> <p>c. Plastic</p> <p>d. Plastic foam</p> <p>e. Fiber pads</p> | <p>e. Buckles, D-rings, snaps, etc.</p> <p>f. Springs</p> <p>6. Shock absorbers</p> <p>a. Plastic foam</p> <p>b. Ununited fiber pads</p> <p>c. Felt or bat</p> <p>d. Crushable metal structures</p> <p>7. Chin and nape straps</p> <p>a. Leather</p> <p>b. Webbing, natural or synthetic</p> <p>c. Cords, natural or synthetic</p> <p>d. Pads (nape)</p> |
|--|--|--|

^a Lewis, 1968

Lewis lists 12 general requirements for an ideal suspension system:

(1) Maintain sufficient offset of the helmet to provide impact protection and ventilation.

(2) Allow minimum relative motion between helmet and head while the wearer is in motion or when the head is moved suddenly or violently.

(3) Be capable of balancing uniformly and distributing uniformly the static and dynamic focus caused by helmet weight, motions of the head, and the impact of missiles and larger objects upon the helmets: application of excessive forces to the relatively weak temporal region of the skull should be avoided.

(4) Protect the upper spinal cord and neck from injury due to the impact on the helmet of missiles or shock waves.

(5) Be non-toxic to skin surface and open wounds.

(6) Provide ventilation or insulation, as required by the climate in which the helmet is worn.

(7) Be compatible with other clothing and equipment (communications, protective, optical, etc.).

(8) Provide adjustments for fit which are simply and easily made, few in number, and self-maintaining.

(9) If removable from helmet shell, be capable of replacement simply and securely without tools.

(10) Be simple and cheap to manufacture.

(11) Withstand field conditions and storage for extended periods (resist fungus attack, rot, mildew, abrasion, perspiration, corrosion, and metallurgical failure).

(12) Maintain design properties for reasonable periods of actual use in any climate where combat is possible.

Dean (76) states that there are two principal lines in which armor may be studied objectively: Utility (including ballistic value, weight and comfort in wearing), and beauty. In this discussion, beauty will receive essentially no consideration, although form, surface and color are considerations in helmet design from a utilitarian point of view. Additionally, soldier acceptability does hinge to some degree on appearance.

With the entrance of the U.S. in World War I, it was decided that the U.S. would adopt the standard British Mk I, although this helmet was recognized to possess some notable defects. Among these was that the center of gravity was not placed so as to reduce wobbling on the head, and that the lining was uncomfortable and disregarded the anatomy of the head. Consequently, the U.S. redesigned the helmet lining. The U.S. lining was woven of cotton twine in meshes 3/8 of an inch square. This web, fitting closely upon the wearer's head, evenly distributed the weight of the two-pound helmet and in the same way distributed the force of any blow upon the helmet. The netting, together with small pieces of rubber around the edge of the lining, kept the helmet away from the head so that even a relatively large dent could not reach the wearer's skull (72).

Additionally, the chin strap was modified by replacing the cowhide strap with an olive drab web strap incorporating a buckle-hook. This chin strap rested upon the point of the wearer's chin instead of near the angle of the jawbone.

As experimental efforts continued during World War I to develop a distinctly American helmet, the helmet linings incorporated were a variant of the German model, which is described by Dean (76):

"The helmet lining is borne on a sweat band of cowhide, which is fastened to the helmet at three points. To this band are attached three pads which fold upward within the dome of the helmet and are backed (i.e., next to the helmet shell) each by a cushion. The pads are then so arranged that one comes to lie against the forehead and one against each side of the head. In the specimens examined, the pad has been formed of calfskin so cut that the end which is attached to the sweat-band is the wider part; the opposite end divides into two lobes, each of which is pierced and threaded by a string which is so arranged that it draws together the free ends of all the tabs and forms an elastic carrier for the weight of the helmet. It should be noted that each tab bears an inner pocket which contains a small mattress filled with curled hair. This mattress is kept in position in the pocket by means of tapes which can be tied. The entire lining weighs 4 1/2 oz. It is so designed that it fits the head easily and allows free spaces (one on either side of the head and one at the back of the head) through which ventilation is secured and by means of which the weight of the helmet upon the head is carried on the three cushions described above. The scalp or the top of the head may thus still receive its supply of blood freely; for the vessels (and for that matter the nerves) which transmit the blood along the sides of the head upward or downward are not compressed by the constricting rim of the usual "hat-lining" of a helmet but have open passageway, thanks to the three spaces in the cushions. Another advantage of this type of lining is the way in which the wearer can adapt it comfortably to his head. Thus if he feels that the supporting cushions are too hard or too thick, he is quite at liberty to remove some of their stuffing to the desired degree; if on the other hand he finds that the helmet sits upon his head too loosely, he has merely to open the drawing strings of the enclosed pads and thrust behind each mattress the needed amount of stuffing, in the shape of a bit of burlap, a folded strip of handkerchief, a layer of cotton wool etc."

Although none of the U.S. experimental helmets was adopted, the most promising models all incorporated the three-pad lining, which as Dean (76) said, localized weight where best supported, cushioned the weight at points of support, and decreased pressure on the temples as well as provided abundant ventilation to the head between the cushions. While attention was being given to the helmet linings, security was a major consideration in addition to comfort. The center of gravity and balance were designed into the helmet to keep it stable on the head when the chin strap was secured.

Dean (76) indicated that great stress was laid on comfort but that comfort could not be achieved even under the best of conditions so he emphasized the requirement for discipline in enforcing helmet wear.

In 1934, a determination was made that none of the candidate designs for a new helmet was acceptable, and a decision was made to modify the M1917 helmet by the addition of an adjustable hair-filled pad. This helmet was designated the M1917A1 (274).

In November 1940 the Chief of Infantry complained that the M1917A1 helmet did not offer adequate protection to the sides and back of the head, was poorly balanced, and sat too high on the head. In January 1941 the Chief of Infantry recommended that Ordnance initiate a project to develop a better helmet. The Type TS3 was developed, found suitable after testing and standardized as the M1 Steel Helmet. The TS3 had a fiber liner, of the same shape as the helmet shell, which contained the Riddell-Type suspension system for the helmet. The suspension consisted of a spiderweb arrangement of lightweight webbing straps. Three straps were looped over a strong lace that formed a center ring below the crown and their ends were riveted at six points to the sides of the liner; another strap, which formed the periphery of the web, was attached to the liner at the same six points. The headband, which was attached to this peripheral strap of the suspension by snap fasteners, was a non-adjustable band made of fabric with a soft leather facing on the side against the head. The neckband was a short webbing strap, also non-adjustable, that stretched across the lower back part of the liner where it could rest just below the pole of the head and thus add to the suspension and stability of the liner. The leather chin strap, which was adjustable and removable, hung by triangular steel holders that looped over garter studs riveted into the sides of the liner; this strap could be worn on the chin or over the front brim of the liner. The Riddell suspension was modified to include an adjustable headband with self-locking clips. Later, an adjustable neckband was developed and incorporated into the liner (274, 53, 236, 238).

During the course of the North African Campaigns in 1943, the rigid hook fastener of the helmet chinstrap was found to be a source of potential danger by remaining intact under the impact of a blast wave of a nearby detonation and thereby jerking the head sharply with the production of fractures or dislocations of the cervical vertebrae. After testing a ball-and-clevis release was designed to release at a pull of 15 or more pounds. This device was standardized in 1944 (53, 160).

During World War II, troop acceptability was fairly high but a common complaint was the lack of stability of the helmet. The frontline combatant must be indoctrinated and impressed with the protective integrity and necessity of the helmet and equally with the ease and comfort with which it can be worn. Helmet design is one field of military design where correct tailoring should be obtained commensurate with the imposed limits of the protective ballistic materials (53).

Throughout World War II, efforts were made to develop new helmet models. Notable among these are the T21-24 series previously described in the history. Among this group, the N21 showed the most promise after test and evaluation. The 21E1 weighed five ounces less than the M1, and had an advantage in having four sizes. It utilized a liner which incorporated the M1 suspension system. This helmet was commented on favorably by Army Field Force Board No. 3 in a test in 1946 (319, 316) and recommended for continued development. Again in a 1952 helmet conference (217) the T21E2 (modified to increase neck coverage, which brought weight up to M1) was favorably commented upon, and questions were asked as to what had happened to this model. The Metropolitan Museum of Art representative attending the conference replied that "the reason for ditching the helmet -- the prime reason -- is that just about the time that it was under consideration, they transferred the activity of the development of body armor from Ordnance to the Quartermaster Corps... The recommendation of the Field Forces was that the helmet not be dropped, but their minor recommendations be met."

In any event, helmet (and liner) development continued, to include the E49 series, the E51 series, the T53, 54 and 55 series.

The E49 helmet, designed in two sizes, had a suspension system that was essentially a modification of the standard M1 system (241).

The EX51, designed in two sizes, also had essentially an M1 suspension system, but included a leather nape strap and a foam disk at the peak of the crown (86, 319, 165, 166, 167).

The T53-2 (144, 248, 86) had an experimental suspension system designed by Cornell Laboratories. The Doron helmets, Types I and II, have suspension systems similar to the M1 (159). This suspension incorporates an adjustable "geodetic" vertical support and an adjustable horizontal support. This system was designed to be entirely removable from the shell.

The T54 liner was also equipped with a modified M1 system. The headband, made in two sizes, regular and large, was lowered and clips redesigned to permit a better fit and adjustment. The cradle was equipped with a buckle adjustment and a floating nape strap added (144, 248).

The T55-2 Type 1 had a new suspension system attached to the liner. The system was 1/8 of an inch lower in front and 1 1/2 inches lower in back than the M1. The suspension system was composed of three web straps, one of which had a cradle loop through which the other two straps passed, eliminating the drawstring lace of the M1. A white name tab was installed on the cradle strap. The headband was attached to the suspension system by six alligator clips; two of these clips were toothed and held the front of the headband static; four of the clips were toothless and allowed the headband to move on the sweatband to allow adjustment to wearer's head contour. To complete the suspension, it had a floating nape strap with horizontal and vertical adjustment. The leather chin strap of the liner was eliminated. The suspension system of the T55-2 Type II was identical to the Type I except that it has an adjustable chin strap for parachutists (321, 44).

The T57-4 liner had the same suspension system as the T55-2 (152). In 1956 a contract was let to Egmont Arens for an "Analysis of Design." He reported that the suspension systems for new helmet designs should be based on refinements of the M1 suspension system. In 1957, a contract was awarded to Cornell Aeronautical Laboratory (CAL) to, in addition to other work, "develop fabricate and evaluate suspensions and suspension systems for the following specific helmets:

Liner, Helmet, Combat T53-2; Liner, Helmet, Steel M1; Helmet, CVC T54-3."

CAL concluded that "the suspension studies for the T53-2, M1 and T54-3 combat helmets have resulted in little improvement over the efforts of the previous contract (OG-998-D-1). It is recommended that no further studies be performed until field tests have been conducted of the systems so far presented" (86). Of the suspensions, the system incorporated into the T55-2 was ultimately adopted when the T55 was user tested in 1957, produced in 1959, and Type Classified as Standard A in 1960 (321, 341).

In 1967 NLABS awarded a contract to International Latex Corporation to develop a Removable Suspension System for the Lightweight Helmet. Three models were submitted, one was found unsatisfactory, and best design features of the other two incorporated into a new design. This last design was also found unsatisfactory because studs for attaching suspension broke when removed, but was later installed in the nylon helmet for Military Potential Test at Ft. Benning, Ga., in 1969. This test concluded that the removable suspension system is suitable for use with lightweight helmets and recommended that consideration be given to redesign of the chin strap to a football-type (350).

During this time period (1968-1969) work continued on improving the standard M-1 suspension per se by making it removable. Six studs replaced the rivets on the liner and clips were attached to suspension system in such a way as to correspond to the studs. The removable suspension was approved for type classification Standard A by ACSFOR in March 1970.

In the LINCLOE Program, two helmets were initially considered, a one-piece nylon with a removable suspension system (developed by International Latex), and a two-piece polycarbonate shell with present nylon liner. Later, the titanium helmets were added for consideration: Types I - III with removable nylon liner and IV, having a removable integrated suspension with no liner.

Burse and Cahill (36) reported on comfort and stability ratings of three prototype LINCLOE suspension designs installed in an M1 helmet liner in a polycarbonate shell.

(1) Pulley and ratchet suspension: flexible plastic headband with ratchet-type lock device adjusted through a cord and pulley arrangement by pulling or releasing the chin strap.

(2) Clamshell suspension: perforated plastic headband adjusted and retained by collar studs with rear nape band and front forehead band acting as a locking device.

(3) Hybrid suspension: perforated plastic headband retained and adjusted by collar studs with plastic nape band.

All three systems had crown pads and chin straps.

While the M1 helmet was rated inferior in comfort and stability, the M1 suspension system was generally rated superior to the experimental systems for comfort and stability.

The suspension system of the Hayes-Stewart helmet was distinctly different from other models as was the helmet itself. In the initial design (which included nine sizes), the so-called trial suspension consisted of five sponge pads permanently affixed to the inside of the helmet shell. After field tests in 1968 found that this suspension system offered improved stability and more comfort than the M1 system, Greaney recommended improvement in design (111). The modifications were made, and the suspension tested in 1969 was removable and consisted again of five flexible foam pads. Each pad is of a sandwich-type construction consisting of a backing of Velcro tape (loop portion), polyethylene foam and polyurethane foam. The pads are attached (inside the helmet shell) by pressing the Velcro tape backing of each pad to counterpoint hook

portions of Velcro tape that are cemented on the inside of the helmet. One pad (7" x 1") is located in the forehead area; two pads (3 1/2" x 1") are located 1 1/2 inches up from the rear bottom periphery and one inch left and right of the center line of the helmet. The suspension straps are made of leather and are designed to form a combination chin and nape strap assembly. They are attached to the temple area and back of the shell by removable fastening devices.

The 1969 test produced four conclusions:

(1) The Hayes-Stewart helmet is compatible with fatigue uniform, mask and hood. However, it is not compatible with the 12-ply nylon vest.

(2) The foam-pad system is not satisfactory since it permits change in fit and does not provide adequate absorption and dissipation of perspiration.

(3) Lighter weight is more comfortable.

(4) The Hayes-Stewart helmet is equal to the M1 with respect to stability, preference and effect on performance of activities on General Equipment Test Activity (USAGETA) Test Facility.

The 1969 report recommended that the suspension and retention be modified and that the armor vest or helmet be redesigned to prevent interaction between the two in the back neck area (157). Based on sizing studies at NLABS, Ft. Devens and Ft. Lee, NLABS developed molds for nine sizes to fit the active army population (341, 351).

A Product Improvement Test was conducted at Fort Benning, Ga., on the M-1 suspension system during the period December 1970 through March 1971 (326). Included in the test were three systems:

(1) A -- Standard suspension system with modified chin strap and plastic chin cup.

(2) B -- Adjustable polyurethane pads secured to nylon liner by velcro tape.

(3) C -- Welson-Davis: two-piece system which attaches in front, back and over the head with velcro tape, and a plastic attachment attached to studs on each side of the liner.

The test report concluded that System B (polyurethane pads) was not suitable for U. S. Army use. System A and System C received high acceptability from the test troops. The report recommended that Systems A and C be further developed and submitted for Engineering Design Test (EDT).

In September 1971 an EDT was initiated at Fort Benning, Ga., on M-1 suspension systems. Included in the test were the following:

(1) The Welson-Davis modified to reduce bulk and facilitate attachment by elimination of the plastic side attachments.

(2) A system identified as HEL (Human Engineering Laboratories) which consisted of the standard suspension with pads attached to the crown and the nape straps.

(3) A four-point retained chin strap fabricated of cotton webbing.

(4) A modified airborne chin strap incorporating the standard parachutist open chin cup.

(5) The standard A M-1 suspension system.

(6) The standard chin strap.

Test instructions required the testing of each suspension system with each chin strap.

The letter report of the suspension EDT indicated that the HEL suspension had high acceptability but suffered from the poor chemical resistance of the pads (crown and nape) used. The modified airborne chin strap had high acceptability. The four-point chin strap, the standard chin strap, the standard suspension system and the Welson-Davis suspension system all had low acceptability. It appeared the Welson-Davis was overcorrected, and the report recommended that further development of this system have for a starting point the original system submitted for PIT in December 1970.

A subsequent IPR on M-1 Suspension Systems and Chin Straps held in February 1972 recommended that the chin strap and suspension system be considered separate actions. It further recommended that the chin strap (modified airboene) be subjected to a two-phase PIT scheduled for first quarter FY 1973. The first phase will test a two-battalion unit and the second, conducted concurrently at Fort Benning, Ga., will test a unit of 100 men.

Also scheduled for first quarter FY 1973 is a Service Test of the HEL and Welson-Davis suspensions modified to correct the deficiencies noted in the EDT letter. During the period covered, numerous tests and evaluations were made of the various designs. In addition to those tests and descriptions already referenced, there were compatibility tests of the M1 with the T59-1 armor vest (247) and the M1 with cold-wet clothing and communications equipment (182).

The review of literature so far has treated the suspension and retention system collectively, and the literature has revealed that more attention has been directed to the suspension than to the retention. Objectively this is a correct approach, since one assumes a correctly fitting suspension system resting a helmet firmly and comfortably on the head, secured by a chin strap. Lewis (154) indicates that the chin strap completes the suspension system and says that in a properly designed system, there should be minimal tension on the chin strap. The chin strap can compensate for a small imbalance in the helmet on the head but cannot correct an improperly designed system. To be maximally effective, the plane of the chin strap should pass close to the center of gravity of the helmet and should be as close to the head as possible. The chin strap should rest on the point of the chin and have a method of adjustment.

Cold-weather headgear, when worn with a protective helmet, provides an additional problem for consideration. Cold-weather headgear normally worn without a helmet presents a compatibility problem when worn with the helmet unless there is an extensive size adjustment in the protective helmet suspension system. Even the area coverage and silhouette are changed, instability increases, and the design of the helmet is compromised. The Naval Medical Field Research Laboratory designed a cold-weather liner which was reported by Denich and Cole at the Quartermaster Research and Engineering (QMR&E) Armor Symposium, 1960 (351). The QMR&E Command developed a cold-weather head covering for wear with the M1 steel helmet and M1 helmet liner. This item, the T61-3 Cold-Weather Cap was tested by the U. S. Army Infantry Board and the U. S. Army Arctic Test Center, and it was recommended for approval and type classification as Standard A when certain deficiencies were corrected. The Helmet Liner Insulator was tested in 1963 and was found suitable for Army use, replacing four other cold-weather headgears (325).

In summary, two basic types of suspension systems have been utilized by the U.S. protective helmets. These are the multiple pad (variant of German) and the multiple webbing (Riddell type). When a single-size helmet is employed, the benefits of the Riddell type suspension are negated. The result is a variation in offset and increased instability. If the single-size helmet is to be continued, it would appear that a modification of the multiple-padding suspension would be preferable. Multiple-size helmets are required if maximum fit, comfort, stability and offset are to be achieved by the suspension system.

The present retention system appears inadequate in the areas of comfort and stability of the helmet on the head. It is improbable, however, that any chin strap can be designed which will be used consistently by infantry troops.

This survey of the design history of helmet suspension and retention suggests six recommendations:

1. Future design efforts should be limited to multiple-size helmets.
2. Removable and adjustable suspension systems are required through a range of sizes for each selected helmet size.
3. The modified Riddell system should be tested with multiple-size helmets.
4. Additional efforts are required in consideration of alternate methods and locations of attaching the chin strap to the helmet, to include multiple attachment and placement such as inside the helmet rather than on the rim.
5. To assure stability of the chin strap on the chin, and comfort in wearing, a chin cup or open chin strap should be employed.
6. Specific attention should be directed to efforts to design a retention system that does not require a chin strap for non-airborne employment.

ACOUSTIC CHARACTERISTICS

Tanenholtz, in his review of acoustical problems of the military (291), states that the limited development of blast and acoustic attenuating material and devices, as well as greater battlefield noise from more powerful weaponry and more mechanized equipment, increases auditory stress on the individual soldier. "If the sound properties of helmets are not taken into consideration," he says, "amplification of sound could result." Furthermore, not only has the compensation paid for hearing loss increased, but also nearly one-half of firing range personnel have been relieved of their normal duties because of incurred drastic hearing loss.

The early testing of the M1 steel helmet and liner combination revealed that sounds reverberated somewhat in the shell and caused a ringing sensation in the ears. The Bell Telephone Laboratories studied the disturbances and concluded the effect was minimal. They suggested the resonance could be reduced by using felt or foam rubber pads in the liner (rejected because of increased weight), or by perforating the liner and shell (rejected because of moisture in rainy weather). Nothing was done, with the conclusion that the soldiers would become accustomed to the resonance (207).

The M1 steel helmet and liner system is still being criticized for interference with hearing (330). Because of the shape of the M1 helmet there may be resonance effects or standing-wave formation which alter the acoustical characteristics of the helmet according to the size of the wearer (253). The M1 comes in one size with an unfilled volume area that varies with head size. If the individual soldier is wearing his helmet high, the vulnerable area around the ear and neck is left unprotected. When it is worn low, hearing is reportedly impaired (10). When the ear is partially protected, the ear canal is somewhat occluded and, in addition, the rim contour may reflect high-frequency sound toward the ear (253).

One of the disadvantages of the EX-51-1 aluminum helmet was the interference with hearing due to the lower side coverage. It impaired normal hearing to a greater extent than did the standard helmet and interfered with the use of communication equipment (319). The T53-2 design, also with lower side coverage, magnified sounds considerably and diminished hearing appreciably. The sound magnification was to the extent that it was feared it could lead to injuries from concussion (144). The Cornell one-piece shell and Arens Style No. 9 extended protective coverage to provide additional ear and cheekbone coverage, and with the "visor" in the up or forward position, the ear was exposed for improved ventilation, comfort and use of field communication equipment (10, 86).

Burse and Cahill (36) compared the M1 to an experimental LINCLOE polycarbonate helmet for interference with hearing and for helmet noise. The polycarbonate helmet was rated more favorably than the M1 both for interference with hearing and for helmet noise.

The Hayes-Stewart helmet exposes the ear canal and is designed to be close fitting, with multiple sizes. The unfilled volume is thus reduced and held more constant relative to the size of the wearers head (253). In his comparison of the form of the M1 and Hayes-Stewart on hearing, Randall found that the Hayes-Stewart helmet provides less high-frequency attenuation, and he suggested that the Hayes-Stewart may be preferable to the M1 for a sentry, all other factors being equal. However, he found only a 2-3 dB improvement in the Hayes-Stewart over the M1 (253).

The ear can be ballistically protected with a movable earpiece, hinged flap or movable neck piece with the resultant interference in hearing, or it can be protected with separate attenuating devices -- such as ear plugs, muffs or selective filters -- within acceptable designs. The design goal could be to provide radio communication to the infantry soldier at the same time providing acoustic protection and possible increased stability on the head by using communication head-sets (354, 39, 137, 375, 255, 190).

The conclusion is clear that, while many different designs and shapes of helmets have been proposed with a wide variety of ballistic materials, there is still a problem with acoustics in helmets. The increasing noise on the battlefield makes the problem more severe and research must evaluate the vulnerability of the ear e.g., advantages and disadvantages of protected, partially protected or unprotected hearing versus the requirement to hear in tactical situations. The research should include attention in design and materials to minimize amplification and reverberation.

Specifically, further research in helmet acoustics should pursue three objectives:

(1) To develop a helmet that would incorporate an ability on the part of the wearer to receive non-injurious sounds, particularly in the speech range, yet attenuate damaging noises.

(2) To determine the effect of the helmet form on hearing (sound localization, speech intelligibility).

TABLE 6
Acoustical Characteristics of Helmets

Helmet	Acoustics	Ear Protection	Attempted Solutions
M1917A1		Negative	
M1	Amplification resonance partial occlusion of ear canal	Partial, depending on head size	Pads, perforated shell/liner
EX 51-1	Impairment of normal hearing Vs. M1	Greater Vs. M1	Lower contour - 2 sizes
T53-2	Sound magnified possible concussion	Greater Vs. M1	Lower contour
LINCLOE Polycarbonate	Improved acoustics Vs. M1		Experimental suspensions
Hayes-Stewart	Improved acoustics Vs. M1	Less protection of ear canal Vs. M1	Ear cutout, multiple sizes, closer offset

(3) To assess the relative values of protection to the ear, as opposed to minimum impairment to hearing, in helmet design.

EYE PROTECTION AND VISUAL FIELD

As soon as the French Army had accepted the protective helmet, attempts were made to develop a face shield and eye guard. One, the Polack visor adapted to the helmet, came close to succeeding the Adrian helmet (76). The French-designed Dunand helmet, featuring a visor, was given serious consideration as a candidate helmet by the Americans, but the visor proved too fragile (76).

Ordnance Department Experimental Design No. 6 tried a tilting face dome, while Experimental Model No. 8 had a face visor with a narrow slit for vision that could be raised or lowered and could resist penetration of .45 caliber service ammunition of 800 foot seconds. Model No. 8 was carefully balanced and kept its position readily. Dean (76) says this model did not appear to be adequately tested.

The British continued work on a fragment visor in the 1930's (73), while the Americans, by 1944, were working on a visor for the Standard M1 Helmet (256).

In 1946 eye armor designed to fit the M1 Helmet was standardized (53). In research and development helmet studies by Cornell Laboratories, the Quartermaster asked for specific evaluation tests to determine the implications of design prototypes for interference with vision (86). The Arens report designs attempted to increase head coverage with movable visors or extended shell parts which affected visual field (10). Experimental Model No. 7's visor in the up position afforded excellent visibility, while in the extreme down position could result in a fine slit between the base shell and visor affording limited vision but extensive protection.

The size and shape of the visual field during wearing of any headgear was measured for the Quartermaster Handbook as was the size limit of the head and neck area (140). A device for measuring size and shape of the visual field was also developed by the Quartermaster (71). The effect of various helmets on field of vision is shown in Table 6 (186).

TABLE 7

Helmet Fields of Vision

Helmet	Field of Vision in Degrees			
	Horizontal		Vertical	
	Left	Right	Up	Down
USA M1	100	100	15	60
Denmark	45	45	20	N
France	90	90	45	50
Germany	N	N	45	N
Italy	N	N	60	N
UK	33	33	47	N

N = 90° or more

Most countries except the U. S. and Denmark report field of vision vertically up to 45° or more (186).

Work on the aircrewman's helmet in the 50's and 60's resulted in polycarbonate-resin visors that provided eye protection against small fragments (234, 148, 66). An eye shield using the polycarbonate lens was designed by the Navy to attach easily to the M1 helmet (122). It consists of a clear plastic visor mounted on an aluminum frame for raising and lowering. A polycarbonate cover shield protects the visor from being scratched in the "up" position (122). The shield was evaluated in Vietnam by the Navy. It did not reduce field of view and could be worn over prescription lenses. The ballistic limit of the shield is 630 feet per second for a .25 caliber T-37 fragment simulator, and 1050 feet per second for a two-grain steel sphere. The Navy recommended that its evaluation report should be used in any efforts to redesign the M1 helmet so as to incorporate the additional safety feature (122).

A reassessment of eye-protection devices for incorporation in future helmet designs should be made with the casualty-reduction analysis. The Navy visor design seems to incorporate the desired features of ballistic protection, vision, comfort, transmission of sound, ruggedness and compatibility with shoulder weapon.

The importance of vision to the soldier suggests at least three specific recommendations for eye-protection research:

(1) Casualty-reduction analyses of the effect of eye shields should be conducted to determine their value for inclusion in future helmet designs.

(2) Research into the helmet visual field as well as target acquisition and identification should be emphasized in both short and long-range programs of the Five-Year Personnel Armor System Technical Plan.

(3) The physiological and psychological impact on the wearer as a function of protection of the eyes and face should be researched.

ANTHROPOMETRICS AND MATHEMATICAL MODELS OF THE HEAD

The use of anthropometrics in designing and sizing helmets has been long recognized. The French World War I helmet was designed with great precision to fit the wearer as comfortably as possible. The shell came in three sizes: the first size, A, was for heads of size 6 7/8; size B was equivalent to 7 1/8; and size C to 7 3/8. For each of the three shell sizes, four different linings were available (76).

Recognizing the need for suspension and helmet offset, Lewis states that the best method for head protection is to fit the helmet as close as possible to the head (154). This reduces the missile-hit area on the helmet. Since the M1 is available in just one size and approximately 85 percent of them are a larger helmet than the wearers need, the possibility of receiving helmet hits is increased (354). The larger diameter requires more effort to turn the helmet and the excess surface area means more weight, more instability and more offset distance than required (354).

These problems were generally recognized and during World War II work continued to improve the M1. The T21 helmet shape was established through anthropometric studies of the head and provided curvature in all directions at all points on the body of the helmet, decreasing the size with no sacrifice in area coverage. It allowed a lower silhouette and closer fit than the M1 (53). In 1945, helmets of aluminum and nylon combinations were produced on the pattern of the T21.

The experimental EX 51-1 helmet was developed as a possible replacement for the M1 and was to be suitable for airborne and armored personnel as well. The 1946 military characteristics for the EX 51-1 prescribed "the helmet being in two sizes with the size break in the mid range. This results in the great majority of wearers with an 'average' sized head being able to wear either helmet, though both helmets are at the limits of their adjustment." The service test found that many men wear the larger heavier helmet unnecessarily and recommended the break in sizes be not in mid range but near the large size (319).

The assumption of helmet responsibility by the Quartermaster resulted in a review of anthropometric design requirements. The Cornell reports on combat-helmet development provided basic data for statistical average head shapes and sizes and the corresponding ranges. They recommended that two shell sizes (with a dividing point at size 7 1/8 for the larger size) would provide adequate sizing and still maintain a minimum number of shell sizes. The reports state that "in helmet design the first consideration should be given to the head rather than the helmet exterior, for in analysing each desirable or required feature it is the man which must function and be protected within the protective shell" (86).

In Arens' analysis of design it was stressed that by cutting down the size of the helmet to fit average and small heads, a favorable weight, fit and appearance would be gained "However," Arens continued, "after careful consideration by Quartermaster it was felt the two size system should be abandoned in favor of a one size helmet to fit the largest head." This one size was determined to have inside dimension of 9 1/2 inches long x 8 1/2 inches wide. Of primary consideration was the effort to keep Quartermaster inventory at a minimum (10).

The Hayes-Stewart helmet developed during the course of LINCLOE helmet program stresses anthropometry in design. Anthropometric data were established from measuring 500 Air Force heads in four dimensions, taking the mean vector and using the standard deviations for larger and smaller sizes. The resulting nine sizes fitted into the helmet-sizing algorithm within acceptable limits (109).

Attempts to design close-fitting or contoured helmets such as the Hayes-Stewart according to available anthropometric head measurements (length, breadth, height and circumference) emphasized the need for more anthropometric data describing the intervening points between the four basic measurements. Philip E. Durand, Project Engineer for the LINCLOE Helmet, compared this problem to that of a carpenter building a house according to a blueprint which shows only the length, height and perimeter of the house. It was the recognition of this problem and the insistence of Mr. Durand which established a work unit in the Five-Year Personnel Armor System Technical Plan to describe the human head mathematically by depicting all basic planes and coordinates necessary to achieve a close-fitting helmet.

Attempts to describe the upper human head mathematically and to take into account variations of the size and shape of the actual head have been currently assigned to the Vulnerability Laboratory of the Ballistic Research Laboratory (BRL) under the Five-Year Personnel Armor System Technical Plan. They are developing algorithms that can be used as an instrument for sizing prototype helmets and that will give solutions for one through any number of sizes. Using the Cinderella approach, efforts are being made to find heads to fit the algorithms. From measurements of 300 heads it has been found preliminarily that the relationship between head circumference and head height was not as expected. The BRL analysis indicates that an adequate representative anthropometric survey sample size would be 500 and that the number of head models could be limited to five or six sizes of heads (337).

The Suspension and Retention section in this report contains further information on the use of anthropometry in suspension design, as does Lewis' 1958 report (154). Suffice it to say here that the advantages of the Riddell-type suspension are negated by using the one size M1 helmet.

Table 8 summarizes the advantages and disadvantages of single-size and multiple-size helmets.

TABLE 8

Advantages and Disadvantages of One-Size Vs.
Multiple-Size Helmets

System	Advantages	Disadvantages
One Size	Cost Inventory Ease of manufacturing	Greater area More Weight Less stability, appearance
Multiple Sizes	Less weight Closer fit - more stability Less area, appearance	Cost Difficulty of manufacturing Less standoff

In his 1958 report, Lewis argued for multiple helmet sizes:

"The problem of a universal sized helmet versus a helmet available in several sizes should be considered as it has been in the sizing of clothing and other protective devices... Should an item supposedly worn continuously in combat take a subsidiary place in sizing...?" (154) The necessity for several helmet sizes has long been recognized by other nations and is now being recognized by the U. S.

Table 9 presents the sizing and suspension of helmets by various nations.

TABLE 9
Helmet Sizes and Suspensions

Country	Helmet Sizes	Suspensions
USA M1917A1	1	1 Adjustable
USA M1	1	1 Adjustable
USA T21	4	1 Adjustable
USA EX 51-1	2	1 Adjustable
USA 52-3	1	1 Adjustable
USA Hayes-Stewart	9	
Denmark	1	
France	1	
Germany	3	3 Headbands
Italy	1	
UK	1	7 Headbands
Poland	2	7 Liner Adjustments
Australia	1	1 Adjustable
Canada	1	1 Adjustable

Helmet sizing techniques are reported by Punton (234), Lewis (154), Zeigen and Churchill (380), Goulet and Sacco (109), and Allinikov (9).

Multiple sizes for infantry helmets are required because of the problems of fit with variance in head size and shape. There is a requirement for continuous anthropometrical survey to provide current sizing data to designers:

(1) Infantry helmets should be provided in multiple sizes up to five. Beyond five sizes it appears that the payoff in better fit does not equal the requirement for the increased inventory.

(2) A survey of a representative sample of new U.S. Army recruits should be established and updated periodically to maintain current anthropometric data.

WOUND BALLISTICS

Throughout history armed combatants have received injuries and wounds from the weapons of their enemies. The study of wounding, wound ballistics, has evolved from an initial casual observation of injuries to an in-depth analysis, employing the physical and life sciences as well as computer technology.

Blair (28) defines wound ballistics as "the study of the relationship between the physical and ballistic characteristics of kinetic energy missiles and blast, and the nature and severity of the wound produced by same in the human body."

Wounding data was recorded for both the Civil War and World War I. However, in World War II, Korea and Vietnam, efforts to collect field data, and to analyze the data collected, have been greatly increased.

In addition to the value of the medical data collected, when a systems-analysis approach is applied to the wound-ballistics data available, a great deal of additional, vital information may be retrieved and applied to other areas, such as weapons effectiveness studies, design of protective armor, and selection of armor materials.

The Biophysics Division of the Biomedical Laboratory at Edgewood Arsenal, Md., has been extensively involved in wound ballistics since early in the Korean War. Battlefield casualty studies prepared by the then Chemical Corps Medical Laboratory at Edgewood (57, 59, 60) have been extensively studied in relationship to both helmet and body-armor design. Wound ballistics studies have been continued since then in conjunction with the Ballistics Research Laboratories and later the Army Materiel Systems Analysis Agency at Aberdeen Proving Ground, Md., as well as with Watertown Arsenal and NLABS.

During the Vietnam War (1967-1969), the Wound Data and Munitions Effectiveness Team (WDMET) operated from the Research Laboratories at Edgewood and from AMSAA at Aberdeen (29). This team collected data on 7801 cases in Vietnam, drawn from 2734 engagements during its operation, for processing, analysis and evaluation at Edgewood and Aberdeen (284, 278). Two WDMET reports specifically address craniocerebral trauma (282) and head trauma (277). An analysis of data on munitions effectiveness and wounds (28) showed that of 11,206 hits on casualties, neck and face account for 6.5 percent of the body area but received 15.5 percent of the total hits, and those head, neck and face hits were the cause of death in 42 percent of the 456 deaths.

These data correlate with the analysis of Korean experience, where 16.4 percent of the wounds in 7773 casualties were head and neck wounds (53), and with data summarized by Beebe and DeBakey (24) in World War II. Additionally, the casualty studies conducted during the Vietnam War have also found that a major causative factor in wounding is fragmentation. N. A. Hitchman of (ORO) (125), in estimating the protective value of the helmet, has stated that although the head, face and neck mean projected area represent 12 percent of the body, this area took about 30 percent of the wounds received by infantrymen in World War II. He estimates an eight percent savings by helmets in total World War II battle casualties.

The extensive literature on wound ballistics serves to emphasize the vulnerability of the head to wounding. The incidence of head wounds is greater than would be expected from the relative size of this area. In addition to the higher-than-expected incidence of head wounds, wounds in the head area are more critical than in other areas, as reflected in the higher death rate.

In view of the higher relative incidence and the greater criticality of head wounds, the design and development of a new helmet should receive greater emphasis.

Although the goal of an ideal helmet would be to provide maximum area coverage to the head, this maximum coverage will reduce the visual field upward and laterally, and by covering the ear area will impair the hearing capability. An analysis of wound data should provide information about the relative incidence of ear-area and facial wounds. This information could then be used in an evaluation of helmet design to allow trade-offs e.g., do the number of wounds encountered in the facial area warrant an increase in protection at the cost of reduced vision, or, is increased vision more important, or, is a face visor an acceptable or desirable alternative.

Helmet offset is another critical aspect of helmet design as affects wounding. Specific medical guidance must be given to the designer at this critical point to allow the design of a helmet that will be fitted as close to the head as is possible. As offset increases, so does the area and weight of the helmet, with no increase in protection, and the helmet becomes a larger target.

Predictive models developed in laboratories can be compared to actual battlefield data, and vulnerability data can be developed from these same battlefield data. Robinson, Boyd and MacDowell (257) developed a method of estimating the medical workload from fragmentation weapons. Waldon, Kokinakis and Sperrazza (366) developed a predictive model for evaluating the protection offered by infantry helmets. Waldon, Dalton, Kokinakis and Johnson (367) present "A Parametric Analysis of Body Armor for Ground Troops" in ARDC TR No. 2. As determined at the Working Committee Meeting No. 3 in December 1971, ARDC TR No. 2 will be employed in the Standardized Casualty Reduction Analysis Reporting (377) for both materials and systems/components evaluation.

Lewis (154) has included a chapter on Medical Aspects (of head injury) and another on the Protective Value of the Helmet. Other reports on wound ballistics are contained in reports by Handford and Lewis (117), Gardner and Hitchman (96), and Dzemian, Light, Washburn and Coe (85).

The acquisition of wound-ballistic data has been greatly expanded over the period covered by this history. The use of a systems approach has greatly extended the application of these data in armor-design development and evaluation. The utilization of wound-ballistics data, vulnerability data, etc., in mathematical models has led to the development of casualty-reduction analysis techniques, which have greatly enhanced the developer's ability to determine design parameters and effect meaningful trade-offs in evaluation.

Continuing efforts should be made to expand the application of and to improve the casualty-reduction analysis techniques.

The developers should continue their efforts to obtain more specific offset requirements which can be incorporated into casualty-reduction analyses.

FUNDING

In a development program a prime consideration in planning and executing work, particularly as to scope and timeliness of work, is funding, not only for in-house development work but also for a contract program which insures supporting industrial expertise. The following tables showing contract programs and proposals indicate industry's interest and assistance in the helmet program.

TABLE 10

Contract Program

Helmet, Lightweight (LINCLOE) for Ground Troops

Fiscal Year	Contract and Scope
66	Mine Safety Appliances Co. No. 1060: To fabricate one mold and 110 lightweight helmets.
66 & 67	General Tire & Rubber Co. No. 1026: To produce a new mold and 250 Nylon Helmets.
67	Edgewood Arsenal, 67-103: To conduct Casualty Reduction Studies on three Helmet Approaches (Nylon, Titanium, Polycarbonate).
67	International Latex Co. No. 0212: To develop a Removable Suspension System for the Lightweight Helmet.
67	Mine Safety Appliances Co. No. 0191: To procure 300 Lightweight Polycarbonate Helmets for ET/ST.
67	Titanium Metals Corp. of America No. 0183: To fabricate 400 Titanium Alloy Helmet Shells.
67	General Tire & Rubber Co.: To investigate Feasibility of Producing a 1-1/2 lb. Combat Infantry Helmet.
68	I.L.C. Industries: To design and fabricate Integrated Helmets.
69	Ballistic Research Laboratories, Aberdeen, Md.: To evaluate helmets to determine casualty reduction criteria.

NOTE: Contracts include LINCLOE and Hayes-Stewart Helmet.

TABLE 11

Contract Program

Nylon Helmet Liner

(Including Improved Suspension System for the Standard Helmet)

Fiscal Year	Contractor and Scope
54 & 55	Victory Plastics: To develop armor materials for Helmet Liner, Steel.
55	Cornell Aeronautical Lab.: To develop helmet compatible with cold weather headgear.
55	Cornell: To develop helmet suspension.
57 & 58	Victory Plastics: To develop reinforced plastics with improved structural and durability characteristics for application to personnel armor.
59	Victory Plastics: To mold and color nylon helmet liner.
60	DeBell and Richardson, Inc.: To develop an integral finish molding system for helmet liners using a quick-cure cycle.

TABLE 12

Contract Program

Titanium Helmet for Ground Troops

Fiscal Year	Contractor and Scope
54	McCord Corp.: To investigate forming of commercially pure titanium alloy helmets.
55	McCord Corp.: To fabricate high-strength aluminum alloy helmets.
58	McCord Corp.: To fabricate titanium alloy helmets.
59	T.R.W., Inc.: To investigate hot-form titanium alloy helmets.
60	Ryan Aeronautical Co.: To investigate explosive forming of titanium alloy helmets.
65	Titanium Metals Corp. of America: To develop forming techniques and fabricate quantities of various-weight titanium alloy M-1 helmets.
67	Titanium Metals Corp. of America: To fabricate 400 24-ounce lightweight titanium helmets.
68	Whittaker Corp.: To develop a one-step mass-production process for forming titanium alloy helmets.

TABLE 13

Contract Program

M-1 Steel Helmet
(Product Improvement)

Fiscal Year	Contractor and Scope
67	Battelle Memorial Institute: To study various properties of M-1 steel helmets and correlate properties with ballistic protection.
67	McCord Corp.: To investigate hydro-forming of M-1 steel helmets to improve ballistic properties.
68	Battelle Memorial Institute: To strengthen the thickness vs. ballistic-limit correlation and develop a replacement inspection technique for ballistic testing.
69	Philco Ford Corp.: To investigate the use of dual-hardness steel in helmet application.

TABLE 14

Contract Program

Siege Helmet

Fiscal Year	Contractor and Scope
68	B.W. Welson and Co.: To develop a new suspension system for the helmet which will provide stability, proper fit and comfort.
68	Army Materials and Mechanics Research Center: To evaluate and determine the ballistic performance of advanced homogeneous and composite armor material against small-arms ammunition, fragment-simulating projectiles, cubes and flechettes.

TABLE 15

Personnel Armor Materials and Items

Industry Proposals to Natick Laboratories -- FY 69

Source	Description	Disposition
Avco Space Systems Lowell, Mass.	Non-destructive testing of ceramic armor.	Proposal not accepted; a concurrent approach was contained in a formal invitation for bid.
Titanium Metals Corp. of America	Helmets, lighter weight and increased protection	Proposal not accepted because of a lack of funds.
Greer Products, Inc. Los Angeles, Calif.	Titanium combat-helmet program	Proposal not accepted because of a lack of funds.
Titanium Metals Co. W. Caldwell, N. J.	Develop ballistic titanium alloy	Proposal not accepted because of a lack of funds.
Les Yogrem Monterey Park, Calif.	Bulletproof military helmet	Not accepted; concept was considered unfeasible.
Phillips Scientific Corp. Bartlesville, Okla.	Personnel armor material X-P for helmet	Not accepted; concept not considered within state of the art.
Hanes Hosiery Winston Salem, N. C.	Attaching armor plates to knitted fabrics	Not accepted; additional data and cost data not furnished when requested.
Illinois Institute Tech. Chicago, Ill.	Glass ceramic armor plate	Accepted.
Uniroyal Plastic Mishawaka, Ind.	Resin composites for steel helmet and liner	Accepted.

TABLE 16

Personnel Armor Materials and Items

Industry Proposals to Natick Laboratories — FY 70

Source	Description	Disposition
Philco Ford Corp. Newport Beach, Calif.	Body armor	Not accepted because of a lack of funds.
Greer Products, Inc. Los Angeles, Calif.	Titanium combat helmet	Not accepted because of a lack of funds.
Airesearch Mfg. Co. Los Angeles, Calif.	Infantry helmet suspension- system study	Not accepted; similar proposal was already in effect with B. Welson Co., Hartford, Conn.
Whittaker Corp. W. Concord, Mass.	Thermally formed titanium alloy helmet	Contract DAAG17-68-C-0203 awarded to Whittaker Corp.

Two additional documents were retrieved which are worthy of close review. The first is a helmet cost study by Finch and Schroder (92) which studies the cost of development and production of the Titanium Type I and III, LINCLOE Nylon and Hayes-Stewart, and compares them to the M1 Steel. The other document is a classified report by Tropf (296) in which he shows the relative economic breakeven points for infantry helmets of new design. Particular emphasis is placed on titanium.

The funds for the helmet-development programs covered by this historical review were adequate except for the years 1969-1970. In 1969 four industry proposals were not accepted because of lack of funds and in 1970 two industry proposals were not accepted because of lack of funds.

The establishment of the Five-Year Personnel Armor System Technical Plan, with the designation of a Program Manager, will provide for centralized management and greater flexibility in funding.

It appears that the funding has been carefully developed to support the five-year program and that the projected funds are adequate to support the proposed work program.

Inasmuch as the five-year program has been in effect for more than a year, a specific review should be made by the Work Unit Performing Organizations in the Scheduled Management Review to verify that the projected fund requirements are still sufficient to allow the full performance of the Work-Unit Requirements in accordance with the schedule.

DISCUSSION

A reviewer of all the documents that have been retrieved in the preparation of this document is inevitably impressed with the tremendous efforts that have been made to provide the U. S. soldier with the best head protection that can be achieved. There have been continuing improvements in all aspects of the helmet-developing program. Significant improvements have been made in the crucial areas of materials technology, wound ballistics, and test and evaluation methodology. The developer now has available to him a wide range of armor material, a valuable source of wound-ballistic data, additional anthropometric data, and more valid means of testing and evaluating both the helmet components and the helmet design. An additional significant improvement has been the increasing clarity in the military characteristics furnished by the requirements authority. These military characteristics provide the criteria by which the developer and the user testing agencies can evaluate the degree to which a candidate helmet meets the military requirement for protective headgear.

History reveals an interesting pattern in the U.S. helmet program. The M1917 helmet was adopted as an expedient from the British Mk 1. Since the U.S. had no protective helmet, an evaluation of the allies' helmets resulted in a choice of the Mk 1. This choice was made because the British could furnish the U.S. with helmets while the U.S. was tooling for its own production, because it offered the best ballistic protection, and because it was amenable to economic mass production. Research and development efforts toward an improved helmet resulted in numerous designs, all essentially "pot-shaped," which were rejected. In 1940, in response to a requirement from the Chief of Infantry for a new helmet, the pot-shaped TS-3 was designed, developed and standardized as the M1 Steel Helmet. This helmet gave increased area coverage and was determined to be economically mass producible. Additionally, it provided increased ballistic protection. Since 1940, all candidate model new helmets have had the pot shape, with the notable

recent exception of the Hayes-Stewart helmet, which has the look of a Roman Helmet and offers an increase in area coverage.

The point is that a resistance to change kept the M1917 and M1917A1 as standard for 23 years, even though the pot-shaped helmet offered demonstrable improvements. For the next 28 years, experimental helmet configuration was essentially that of the current standard M1, even though alternate designs were proposed in 1956 and 1957, until the Hayes-Stewart configuration was advanced in 1968. Helmet improvements have been evolutionary in nature, producing primarily an improvement to the suspension/retention system and an increase in ballistic protection by the substitution of a ballistic liner for the non-ballistic liner. Currently, improved suspension/retention systems, alternate armor material and the alternate design are being tested. The decision to consolidate the responsibility for development of all personnel armor in the Quartermaster in 1947, rather than to split responsibility between Ordnance and Quartermaster, was a distinct step forward for program management. The establishment of U.S. Army Materiel Command (AMC) as the logistical element of the Army was another step toward central management.

The latest advancement in helmet development was the decision to incorporate the helmet program into the Five-Year Armor Program. The result was the establishment of the AMC Five-Year Personnel Armor System Technical Plan, with Natick Laboratories (NLABS) as the lead laboratory with the program manager.

After due consideration of all aspects of helmet design and acceptability (both test and soldier acceptability), it has become quite apparent that the suspension (and retention) is the most critical aspect of design. Since the suspension system is the key to fit, balance, comfort, stability, hence decreased fatigue or physiological cost, and cumulatively, soldier acceptability or psychological acceptance, it must be realized that this aspect of helmet design must receive consideration comparable to ballistic protection.

The literature on battle casualties contains reports of non-wearing of the helmet for a variety of reasons, such as comfort, (too hot, too heavy, unstable, etc.), detectability (noise on patrol) and hearing deprivation.

Since it is improbable that a truly comfortable helmet can be developed which affords the desired protection, the question is raised as to whether it would not be better to have a ballistically inferior helmet which would be more acceptable to the soldier for essentially constant wear. At the same time, the developer cannot be held solely accountable for the soldier's failure to wear his helmets. The user must by training accustom the soldier to wearing the helmet and then through discipline enforce the wearing.

Suspension systems have been of essentially two types in U.S. helmets: the pad system and the cradle system. The M1 and all experimental helmets developed by the U.S. since World War II have had a variant of the cradle system, except the Hayes-Stewart helmet, which uses a five-pad system. In comparative tests, the trial and modified pad system compared very favorably with the standard M1 system, and it would appear that worthwhile effort could be devoted to overcoming the test shortcomings of the Hayes-Stewart by changing materials, changing the front slope and modifying the chin-nape strap, to accomplish a still better fit and more comfortable as recommended by the test organization.

Sizing of helmets has been contradictory throughout the development since World War II. Sizes have ranged from one size for all wearers, with the M1, to two, four, and nine sizes, as with the Hayes-Stewart helmet. The main argument in support of one size has been the reduction of inventory of helmet sizes. This argument seems to fail at first glance when offset, weight and area coverage are considered for the small, average or medium, and large wearer. It fails even further when stability is considered. Lastly, it would appear that for an item of equipment as valuable to the wearer as the helmet, "tailoring," i.e., a number of sizes, is required to offer improved fit, comfort, stability, proportioned weight and coverage, and proper offset. These factors will be a major contribution to making the helmet more acceptable to the soldier. The Hayes-Stewart Helmet, designed and fabricated in nine sizes, represents a step in this direction. In any event, multiple helmet sizes appear to be required. A multiple-sizing system improves stability, standardizes weight ratio per wearer/helmet, standardizes target-area size and standardizes offset.

During the period from World War II until now, advances in materials technology might well result in a superior ballistic material for a new helmet. Hopefully this material will weigh less per square inch and even more hopefully will be amenable to mass production at a reasonable cost. It would probably be desirable to re-evaluate some of the past most promising ballistic materials and some of the most promising designs, using the improved evaluation technique of casualty-reduction studies as well as applying improved techniques of fragment simulators. This re-evaluation should eliminate doubt, if doubt exists, as to why a given material or design failed.

Two candidate model helmets that were recommended for further development, yet not adopted, should be reconsidered: the T21E3, dropped when the Army changed from a two-helmet doctrine and returned to an all-purpose helmet in 1949; and the T53-E2, dropped when the Army selected the T55E3 nylon liner as a liner for the steel M1 shell after service tests in 1954-1955. Both of these helmets should be reconsidered to determine if they can be improved by material or design or if their good factors can be incorporated into other helmets. The T21E3 design in four sizes was established after anthropometric studies and was purported to offer increased strength and protection, decreased size at no decrease in protection, and less weight than the M1. The T53-2, also of aluminum and nylon, was designed in one size but offered a 10 percent increase in the protected area. This helmet was rejected when the T54-1 helmet liner (later the T55-3) was adopted after ballistic, logistical and acoustic considerations.

Historically, evaluation of a candidate armor material, and/or the evaluation of a candidate system/component, has been critical to the process of selection. From 1917-1918, when selection was essentially a relatively simple go, no-go process of simplified ballistic testing and determination of production feasibility, selection is now an evaluation of many variables far wider in scope and far more complex in application. The increased complexity reflects the great strides forward in materials technology, as well as the ability of managers to integrate the inputs from the physical and life sciences, using a system-analysis approach and taking advantage of computer technology.

The recent effort on the part of the program manager to effect standardization of terminology and methodology for characterization of personnel armor has led to the adoption of a standardized casualty-reduction analysis reporting, with criteria established for material evaluations and expanded criteria established for system/component evaluations. This approach should lead to common understanding among all personnel concerned with personnel armor development. In extension of the casualty-reduction analysis, there is a requirement to obtain more quantified data in the field of human factors for application in the mathematical models. The effects of weight, instability, fit, comfort, visual and acoustic characteristics and the part that they play in soldier acceptability of a new helmet are largely not quantified, but are subjective data obtained from observations, from wearer comments, and from responses to

questionnaires. The importance of objective data, subject to quantification, on soldier acceptability must be emphasized in the five-year plan by appropriate research. The acquisition of hard data will allow realistic trade-offs in helmet evaluations.

The entire problem of helmet design is currently being studied by the five-year plan team. Included in the design studies are studies to determine the requirement for offset. At present the Surgeon General requires an offset and efforts are being made to define the required minimum/maximum offset for helmet design. Helmet-design studies should also produce data indicating a minimum number of helmet sizes, based on defined basic head shapes and a defined number of sizes for each shape.

Throughout the course of U.S. helmet development there has been no reluctance on the part of the Ordnance Department or the Quartermaster Corps to solicit outside help in obtaining design assistance, primarily the Metropolitan Museum of Art in the case of the Ordnance Corps, and industry -- research and design corporations -- in the case of Quartermaster Corps. It might be said that the investment return was greater for the Ordnance Corps than it was for the Quartermaster Corps. Yet who can say as to whether it was a choice of contractor, guidance to the contractor by the government, or what proportion of both? However, even with work in progress, emphasis must be placed on a clearer statement of the problem so that design can be effected to accomplish all of the desired military aspects of a protective helmet. This statement should specifically include but not be limited to the definition of an acceptable weight; a definition of desired as well as required coverage; a specific definition of a minimum acceptable stand-off, minimum acceptable acoustical characteristics and minimum acceptable visual field; a statement as to the requirement for visual protection; a definition as to the minimum and maximum number of sizes that are acceptable; a statement as to priority of requirements for compatibility with various other pieces of the infantryman's equipment (compatibility with a shoulder-fired weapon is the number one priority, but which is more important, compatibility with binoculars, with communications equipment, armor vest or with protective mask? These and other questions must be answered so a material choice can be made, a design established, laboratory tests planned and evaluated, and finally, field evaluations conducted.

In summary, decisions have to be made to resolve the following apparent conflicts in requirements:

- (1) Ballistic protection requirement vs. helmet weight.
- (2) Material vs. cost.
- (3) One size vs. multiple sizes.
- (4) One-piece helmet vs. two-piece helmet.
- (5) Infantry helmet vs. all-purpose helmet.
- (6) Hearing and vision vs. protection.
- (7) Pad-type suspension vs. multiple-web suspension.
- (8) Protection only vs. ancillary benefits.

In the past, decisions have been made on the basis of subjective opinion, and, with primary weight being given to one aspect of a proposed helmet, as in the case of the Model No. 5 rejection on the grounds that it resembled the German helmet too closely. Such was also the case of the T53-2, which if it had been adopted would have obsoleted the U.S. helmet inventory, or of the decision to develop one size to fit the large man to reduce the inventory. The establishment of a central program manager, with control over all the supporting laboratories, should definitely facilitate the decision-making process, and the program manager can take the necessary steps to acquire the data necessary to systematic decision making.

One conflict which is not so simply listed in tabular form is very important. That is the requirement that the helmet be compatible with all the wearer's clothing and equipment. Ear protection may lead to difficulty in using communications equipment and back of the neck protection may lead to weapon-firing problems in the prone position. Resolution of the conflicts will not be easy since they are so closely inter-related; therefore, the requirements to be satisfied should be weighed, and of particular importance should be the assignment of weights to those factors that have significant importance in influencing soldier acceptability. In the last analysis, the U.S. soldier will not wear the best helmet in the world if he does not want to wear it.

CONCLUSIONS

Selection of an improved armor material for the helmet still ranks as a number one problem even though there has been an aggressive and comprehensive pursuit of new materials and combinations of materials for protective helmets. Even with all the research, testing and evaluation of armor materials that has been accomplished, an acceptable substitute for the Hadfield steel used in the M1 helmet has not been developed. There are, however, candidate materials under current consideration which may be applicable. The technology of evaluating ballistic protection has greatly expanded, and while an acceptable substitute for the current standard M1 helmet has not been developed, techniques for more realistic evaluation have been developed, particularly since World War II and most recently with the acceptance of a standardized casualty-reduction analysis reporting procedure. This procedure should facilitate the development of an improved helmet.

There are two basic types of suspension systems that have been utilized by the U.S. for protective helmets. These are the multiple pad (variant of German), and the multiple webbing (Riddell type). When a single-size helmet is employed, the benefits of the Riddell-type suspension are negated. The result is a variation in offset and increased instability. If the single-size helmet is to be continued, it would appear that a modification of the multiple-padding type would be preferable.

Multiple-size helmets are required if maximum fit, comfort, stability and offset are to be achieved by the suspension system. The present retention system appears inadequate in the areas of comfort and stability of the helmet on the head.

While many different designs and shapes of helmets have been proposed with a wide variety of ballistic materials, there is still the problem of acoustics in helmets. The increasing noise on the battlefield makes the problem more severe, and research must be accomplished to evaluate the vulnerability of the ear, e.g., advantages and disadvantages of protected, partially protected or unprotected hearing vs. the requirement to hear in tactical situations. The research should include attention in design and materials to minimize amplification and reverberation.

A reassessment of eye-protection devices for incorporation in future helmet designs should be made with the casualty-reduction analysis.

Multiple sizes for infantry helmets are required because of the problem of fit with variance in head size and shape. Anthropometrical surveys to provide current sizing data to designers should be continued.

The acquisition of wound-ballistic data has been greatly expanded over the period covered by this history. The use of a systems approach has greatly extended the application of these data in armor design, development and evaluation. The utilization of wound-ballistics data, vulnerability data, etc., in mathematical models has led to the development of casualty-reduction analysis techniques, which have greatly enhanced the developers' ability to determine design parameters and effect meaningful trade-offs in evaluations.

The funding for the helmet-development programs covered by this historical documentation appeared to be adequate and the projected funds for the proposed work plan in the Five-Year Personnel Armor Systems Technical Plan appear to be adequate.

REFERENCES

1. Abbott, & Papetti. Comparative ballistic behavior of personnel armor materials (U). AMMRC TR 71-39, Army Materiel & Mechanics Research Center, September 1971.
2. Aberdeen Proving Ground. Armor protection against fragments from HE ammunition, VT fuzed. Report AD-1101, Aberdeen Proving Ground, Md., 21 November 1946.
3. Adjutant General's Office. Operational report for period ending 31 July 1968 (U). Lessons Learned, Headquarters, 1st Infantry Division, Department of the Army, Washington, D. C., July 1968. (Confidential report)
4. Adjutant General's Office. Lessons learned. Headquarters, 11th Aviation Battalion (Combat) (U). Department of the Army, Washington, D. C., May 1970 (Confidential report)
5. Agen, H. E. The effect of shot peening on the ballistic characteristics of the M-1 helmet. Technical Report ME-1, Quartermaster Research & Engineering Command, Natick, Mass., July 1962.

A study was conducted to determine if shot peening the outer surface of the M-1 helmet shell would have any effect on its ballistic characteristics. While increasing the protective capability was the main objective, there would also be residual benefit of surface preparation before the final finishing of the helmet shell. However, the increase in ballistic resistance of the peened helmets evidenced by this experiment was not significant enough to warrant further consideration of this process.

6. Alesi, A. L., & Landsberg, M. Two unique plastic helmets. Quartermaster Research & Engineering Center, Natick, Mass., February 1960.
7. Alexander, M., & Hertzberg, H. T. E. A comfort evaluation of a form-fitting high altitude helmet. Aerospace Medical Research Laboratories, Wright-Patterson AFB, Ohio, February 1957.
8. Allen, C. H. Earmuff cushion prototype: Friction-spring design: Final report 1 July 1967-31 January 1968. Report Number BBN-1597, Bolt, Beranek & Newman, Inc.: Cambridge, Mass., August 1968.

This report summarizes the development and performance of prototype earphone cushions designed to provide improved, low-frequency noise isolation when used with a protective, hard helmet. The cushions are soft and seal well for a low-static clamping force against the head, but are stiff and provide a relatively rigid support for the earphone enclosure against oscillating forces induced by an external sound field. This report also describes a new mounting system for earphone enclosures in a protective helmet that provides excellent vibration isolation and utility.

9. Allinikov, S., Ziegenhagen, J. A., & Morton, W. H. Foam-in-place form fitting helmet liners. Technical Report June 1968 - November 1969, Number AFML-TR-70-21, Air Force Materials Laboratory, Wright-Patterson AFB, Ohio, April 1970.

The feasibility of a foamed-in-place, form fitting foam helmet liner for Air Force crash or flying helmets was proven. Polyurethane foam helmet liners may be foamed-in-place directly on the flying crew member's head, producing a perfectly fitting helmet liner with a minimum of time, labor, and inconvenience. A suitable polyurethane foam formulation was tailored to the specific requirements for the foam-in-place helmet liners. Design and fabrication of a suitable mold in which the helmet liner is foamed and which would be worn by the individual being fitted for a custom helmet liner during the foaming process, was accomplished.

10. Arens, E. U. S. Army protective headgear analysis of design. Contract Number DA 44 109 QM 1821, Egmont Arens Industrial Design, New York, N. Y., March 1956.
11. Army Materiel & Mechanics Research Center. Advanced armor materials research program (U). 9 January 1962.
12. Army Materiel & Mechanics Research Center. Program on the development of improved test methodology for evaluating armor materials versus fragmenting munitions. 26 February 1970.
13. Army Materiel & Mechanics Research Center. Annex A to the USAMC five-year personnel armor system technical plan — directed plan for personnel armor materials research and development (U). 27 November 1970.
14. Army Materiel & Mechanics Research Center. Materials for personnel armor first status report to the senior steering committee. 16 September 1971.
15. Army Materiel & Mechanics Research Center. Materials for personnel armor — second quarterly report first quarter FY 72 summary. 20 October 1971.
16. Army Materiel & Mechanics Research Center, & Ballistics Research Laboratory. Lightweight armor program FY72 progress briefing for the Honorable Robert L. Johnson, Assistant Secretary of the Army, R&D. 27 December 1971.
17. Army Materiel & Mechanics Research Center. Materials for personnel armor (U). First semi-annual progress report FY72. Report SP72-3.
18. Army Materiel & Mechanics Research Center. Development of improved test methodology for evaluating armor materials versus fragmenting munitions. AMMRC SP72-7, March 1972.
19. Army Work Study Group. Infantry team (U). Report Number Memo. 2/65, Army Work Study Group, Warminster, England. (Confidential report)
20. Atkinson, R. V. Letter report (JRATA 2K 452.0) Evaluation of the nylon helmet liner: Final report November 1963 - October 1964. Report Number CDTC V VIII, Joint Research and Test Activity, San Francisco, Calif., October 1964.

Combat evaluation of the US Army nylon ballistic helmet liner, soldier's steel helmet, type II, DSA Vietnam armed forces (Rangers, Special Forces, Marines, Airborne) in combat and training, report recommends immediate issue of the liner to US advisory personnel and priority issue of the liner to Vietnamese units.

21. Ballistic Research Laboratories. Report of the first meeting of the committee to establish standard procedures for measuring behind armor damage after perforation by KE projectiles. Technical Note Number 903, Aberdeen Proving Ground, Md., May 1954.
22. Ballistic Research Laboratories. A double spark shadowgraph technique for the measurements of velocities over short paths. Memorandum Report Number 20/1085, Project Number TB3-0112, Aberdeen Proving Ground, Md., July 1957.
23. Ballistic Research Laboratories. Velocity losses of cylindrical steel projectiles perforating mild steel plates. Report Number 1019, Aberdeen Proving Ground, Md., July 1957.
24. Beebe, G. W., & De Bakey, M. E. Battle casualties. Springfield, Ill.: Charles C. Thomas, 1952.
25. Beyer, R. J., & Smith, D. R. Confirmatory (Type II) test of squad radio consisting of AN/PRT-4 transmitter and AN/PRR-9 receiver under Arctic winter conditions: Final report 13 October 1967 - April 1968. Army Arctic Test Center, Ft. Greely, Alaska, April 1968.

A confirmatory (Type I) test of the squad radio consisting of the transmitter, AN/PRT-4, and receiver, AN/PRR-9, was conducted by the US Army Arctic Test Center, Ft. Greely, Alaska. The confirmatory test evaluated the harness, electrical equipment, ST-153U/PRR-9, fabricated at the request of USATECOM as a result of the previous arctic service test of the squad radio. The purpose of the test was to determine if the squad radio was suitable for US Army use under arctic winter conditions, and to determine if deficiencies reported from the previous arctic service test had been corrected. Testing was conducted in temperatures of 0 F to -50 F by soldiers representative of those who would operate the radio in the field.
26. Bjorksten Research Foundation. Development of improved flight helmet liner. WADC TR 59-435, Contract AF33 600 34149, ARDC, USAF, Wright-Patterson AFB, Ohio, October 1959.
27. Bjorksten Research Laboratories, Inc. First quarterly report entitled "Information regarding the energy absorbing characteristics of materials for utilization in armor." 20 June 1957.
28. Blair, J. R., Analyzing data on munitions effectiveness and wounds. US Army Management Views, Book I, Vol. XV, pp. 124-142, Ft. Belvoir, Va., March 1970.

29. Blair, J. R., & Sperrazza, J. Wound data and munitions effectiveness as based upon battlefield surveys in Vietnam (U). Ballistic Research Laboratories, Aberdeen Proving Ground, Md., 1969. (Confidential report)

Under the auspices of the Army, the Navy, the Marine Corps and the Joint Technical Coordination Group for Munition Effectiveness, two wound data and munition effectiveness survey teams were fielded in Vietnam. One was an Army team, in theater from June 1967 through June 1969, with headquarters at Ton Son Nhut and data collection teams at An Khe (1st Air Cavalry), Pleiku (4th Infantry Division), Lai Khe (1st Infantry Division), and Cu Chi (25th Infantry Division). The other was a Marine Corps/Navy Team, operational in Corps from May 1968 to May 1969 and attached to the 1st Marine Division of the 3rd Maf. the effort was divided into three phases: (1) Data collection, (2) Data analysis, and (3) Data evaluation. The first phase was conducted in Vietnam and the last two by the Research Laboratories (EA), the Ballistic Research Laboratories and the Army Materiel Systems Analysis Agency (APG). This paper presents a resume of the results and, in particular, on how well the following five objectives were met: (1) Enhance lethality of present/future weapons; (2) Confirm/modify criteria for estimating weapons requirements; (3) Confirm/modify wound ballistic criteria; (4) Evaluate/improve (U).

30. Bohan, & Garnis. Development and evaluation of a low modulus, low density glass fiber reinforcement for composite armor (U). Picatinny Arsenal, Dover, NJ, February 1972.
31. Brown, R. E. Study of transfer of momentum to monkey's head from impact of ceramic-composite armor (U). Technical Report Number 4128, Edgewood Arsenal, Md., October 1967. (Confidential report)
32. Browning, R. W. Product improvement test of suspension system for M1 helmet: Final report. USAIB Project Number 3327, U. S. Army Infantry Board, Ft. Benning, Ga., March 1971.
33. Bureau of Aeronautics. Development of eye, head or face protective devices. Control Number a(S)-59-6124C, Department of the Navy, Washington, D. C., November 1959.
34. Bureau of Ordnance. Armor fragment-resistant. Bureau of Ordnance Specification NAVORD OS3563, Department of the Navy, Washington, D. C., 10 October 1944.
35. Burse, R. L. USAF size extra-large flight helmet: Comparison of dimension specifications with anthropometric data. Natick Laboratories, Natick, Mass., January 1965.

36. Burse, R. L., & Cahill, W. D. Comfort and stability ratings for LINCLOE helmet and suspension systems compared to those for standard items. Research Study Report Number EPR-15, Pioneering Research Laboratory, Natick Laboratories, Mass., July 1968.

A sample of sixteen test subjects awarded comfort and stability ratings to the standard US army M-1 steel helmet and suspension system, one experimental LINCLOE polycarbonate helmet and three experimental LINCLOE helmet suspension systems. All occurrences of subjects' touching or readjusting the helmet system were recorded, as were subjective ratings for ease of adjustment of the suspension system, overall comfort, helmet warmth, location of chinstrap, pressure produced by the suspension system, annoyance produced by the suspension system, interference with hearing, noise produced by the helmet/suspension combination and stability when running, jumping, throwing, crawling, digging and crawling under a wire obstacle, the standard M-1 steel helmet was generally rated inferior to the experimental polycarbonate helmet for comfort and stability. While the standard M-1 suspension system was generally rated superior to all experimental suspension systems for comfort and stability, of the performance tasks utilized in the study, grenade throwing and low crawling appeared to best identify suspension systems which were unstable enough to tip over the forehead and produce visual restriction.

37. Burse, R. L., Cahill, W. D., & Summers, E. P. Comfort and stability ratings for prototype LINCLOE titanium helmet system. Research Study Report Number EPR-16, Pioneering Research Laboratory, Army Natick Laboratories, Mass., August 1968.

Six test subjects awarded comfort and stability ratings for the standard 3.16 pound M-1 Steel Helmet System and an experimental 1.53 pound LINCLOE one-piece titanium helmet system. The suspension system of the experimental helmet was attached directly to the titanium ballistic shell, obviating the need for a helmet liner. Subjective ratings were recorded for: ease of adjustment of the suspension system comfort, helmet warmth, location of chin strap, interference with hearing, noise produced by the helmet, interference with aiming the carbine and stability when running, jumping, grenade throwing and crawling under a wire obstacle. After scaling differences between the ratings for the experimental and the standard systems underwent T-Testing for significance.

38. Byer, H. H., & Lund, D. J. Evaluation of visor helmet, flying type, HGU-2 A/p, experimental laser protector. Project Number DA-1-T-06110, Frankford Arsenal, Philadelphia, Pa., June 1969.

39. Camp, R. T., & Keiser, R. L. Sound attenuation characteristics of the Army APH-5 helmet. USAARU Report Nr. 67-6, U. S. Army Aeromedical Research Unit, Ft. Rucker, Ala., February 1967.
40. Camp, R. T., & Keiser, R. L. Sound attenuation characteristics of the Navy SPH-3 (modified) (LS) helmet. U. S. Army Aeromedical Research Unit, Ft. Rucker, Ala., May 1967.
41. Carroll, J. F. Ballistic evaluation of nylon helmet liners with and without M1 steel helmet shells (U). Report Nr. DPS 622, Aberdeen Proving Ground, Md., August 1962. (Confidential report)
42. Chaffin, J. M., & Youngling, E. W. Human factors evaluation of clothing and personal equipment in Thailand and the Republic of Viet Nam. Army Natick Laboratories, Mass., August 1963.

This report summarizes work done in Southeast Asia related to human factors requirements in the design of clothing and personal equipment for the Royal Thai Army and for the Republic of Viet Nam Armed Forces. The findings reported are based on controlled observations and structured interviews made in the respective countries, specific recommendations are made concerning human factors considerations for each clothing and equipment item observed.

43. Churchill, E., & Daniels, G. S. Nomographs of head measurements. WADC TR 53-14, Contract Number AF18 600 30, WADC, Wright-Patterson AFB, Ohio, May 1953.
44. Clark (David) Company. Development of headware for removable suspension system for "liner, soldier's steel helmet T55-2" and "helmet, combat vehicles crewman T56-6." Report Number 1, David Clark Company, Worcester, Mass., 6 September 1961.
45. Clark (David) Company, Inc. Integration of personal equipment. Contract Number AF33 616 6444, David Clark Company, Inc., Worcester, Mass., October 1961.

This report describes the various efforts, methods of approach and solutions to some problems of integrating items of air crew personal equipment. The major problems of integration is the combining of the various individual items, which have specific functions with each other, without complicating these combinations beyond their effectiveness limits. Practical solutions were achieved in some areas but additional work is required in others.

46. Clarke, D. P. J. Acoustic properties of headgear: XXIII. The Anticooustic Co. Nosonic Mk IX earmuff with earphones and liquid-filled ear seals; and General Textile Mills Co. helmet with modified sound valve and liquid-filled ear seals (U). Technical Memo Report Nr DRML-TM-643, Defence Research Medical Laboratories, Toronto (Ontario), August 1966. (Confidential report)
47. Clarke, D. P. J. Acoustic properties of headgear: XXIV. The ML Aviation Co. LTD. noise excluding helmet type NG(T) and the Roanwell Corp. headset-microphone type P/N 10900 (U). Technical Memo Report Nr DRML-TM-654, Defence Research Medical Laboratories, Toronto (Ontario), November 1966. (Confidential report)

48. Clarke, D. P. J., & Lederman, S. J. Acoustic properties of headgear: XXVI. The Gentex Corp. helmet model DF41-2 hearing protector with three sizes of earcups (U). Technical Memo Report Nr DRET-TM-678, Defence Research Establishment, Toronto Downsview (Ontario), September 1967. (Confidential report)
49. Clarke, D. P. J., Forshaw, S. E., & Neely, K. K. Acoustic properties of headgear: XXI. Safety Supply Co. Type 290 'sound barrier' C/W liquid-and foam-filled ear seals; General Textile Mills Co. helmet C/W sound valve and liquid-filled ear seals; and Mine Safety Appliances Co. 'noisefoe' Mk II ear protector C/W foam-filled ear seals(U). Technical Memo Report Nr DRML-TM-617, Defence Research Medical Laboratories, Toronto (Ontario), October 1965. (Confidential report)
50. Clark, J. B., & George, T. W. NRL Report January 1949 (U). Naval Research Laboratory, Washington, D. C., p. 19. (Confidential report)
51. Clark, J. B., & George, T. W. NRL Report April 1949 (U). Naval Research Laboratory, Washington, D. C., p. 26. (Confidential report)
52. Clifford, J. M. Head ventilation. RAF Institute of Aviation Medicine, Farnborough, England, April 1965.
53. Coates, J. B., & Beyer, J. C. Wound ballistics. Office of the Surgeon General, Washington, D. C., 1962.
54. Coe, G. B., MacNamee, J. K., & Herget, C. M. Steel armor protection of the animal head against a non-penetrating missile. Report Nr 98, Chemical Corps Medical Laboratory, Army Chemical Center, Md., January 1952.
55. Coe, G. B. Wound ballistics; KIA, Korea 20 March-23 April 1952. Research Report Nr 116, Chemical Corps Medical Laboratory, Army Chemical Center, Md., June 1952.
56. Coe, G. B. Relationship of casualties to tactics in a given situation, Korea 26-30 July 1951. Research Report Nr 141, Chemical Corps Medical Laboratory, Army Chemical Center, Md.
57. Coe, G. B. Wound ballistics; KIA Korea 24 April-12 July 1952. Research Report Nr 144, Vol. II, Chemical Corps Medical Laboratory, Army Chemical Center, Md., October 1952.
58. Coe, G. B. Battlefield performance of the M1 steel helmet. Research Report Nr 248, Chemical Corps Medical Laboratory, Army Chemical Center, Md., February 1954.
59. Coe, G. B. Wound ballistics; KIA Korea 6 August-19 August 1953. Research Report Nr 257, Chemical Corps Medical Laboratory, Army Chemical Center, Md., March 1954.
60. Coe, G. B., Stoughton, R. B., & Debiec, R. P. Wound ballistics; KIA Korea 15 November 1952-1 March 1953. Research Report Nr 221, Vol. III, Chemical Corps Medical Laboratory, Army Chemical Center, Md., October 1953.
61. Coe, G. B., MacNamee, J. K., & Herget, C. M. Steel armor protection of the animal head against a non-penetrating missile. Report Nr 98, Chemical Corps Medical Laboratory, Army Chemical Center, Md., January 1952.

62. Coe, G. B., Michalski, J. V., Light, F. W., & Herget, C. M. Effectiveness of protection from wounding by Doron and spot-bonded nylon body armor. Research Report Nr 103, Chemical Corps Medical Laboratory, Army Chemical Center, Md., March 1952.
63. Cohen, A. Sound transmission through the combat vehicle crewman's helmet when the seal of the earpads is broken. QREC-PB-39, Quartermaster Research & Engineering Center, Natick, Mass.
64. Cohen, A. Temporary hearing loss for protected and unprotected ears as a function of exposure time to continuous and impulse noise. Technical Report Nr EP-151, Quartermaster Research & Engineering Center, Natick, Mass.
65. Cohen, A. The psychoacoustic and comfort properties of helmet communications gear. Quartermaster Research & Engineering Field Evaluation Agency, Ft. Lee, Va.
66. Coleman, R. A., Sherr, A. E., & Tucker, R. J. Development of experimental absorptive and reflective lenses for goggles and helmet visors. Technical Report Nr A5D-TR-68-67, Wright-Patterson AFB, Ohio, April 1969.
67. Cornell Aeronautical Laboratory. Interim report covering instrumentation development for helmet deformation investigation (U). CAL Report OG-900-D-1; WAL Report 710/1043, Buffalo, N. Y., 15 October 1954. (Confidential report)
68. Cornell Aeronautical Laboratory, Inc. Transient deformation and residual energy characteristics of M1 and EX51-1 helmets at 0°, 45°, 60° angles of obliquity (U). CAL Report No. OG-900-D-2; WAL Report Nr 710-1043-1, Buffalo, N. Y., 1 March 1955. (Confidential report)
69. Cornell Aeronautical Laboratory. Transient deformation and residual energy characteristics of M1 and EX 51-1 helmets at 0°, 45° 60° angles of obliquity. CAL Report OG-900-D-2; WAL Report 710/1043-1, Buffalo, N. Y., June 1955.
70. Cornell Aeronautical Laboratory. Combat helmet suspension studies. Contract DA 19-129-OM-218, Project Nr 7-80-05-001, Buffalo, N. Y.
71. Crist, B. A device for measuring the size and shape of the visual field during the wearing of army headgear. Technical Report Nr EP-152, Quartermaster Research & Engineering Command, Natick, Mass., June 1962.

A modified perimeter devised for measuring restrictions in the size and shape of the available visual field due to wearing army headgear is described. The device is similar to the conventional perimeter, but it is much larger and allows automatic readout and direct control of the visual target by both subject and experimenter. Construction and operating details are furnished.

72. Crowell, B. America's munitions, 1917-1918. Report of Benedict Crowell, the Assistant Secretary of War, Director of Munitions, Government Printing Office, Washington, D. C., 1919.
73. Cruise, R. R. A visor for the prevention of war blindness. British Medical Journal, 4141, 19 May 1940.

74. Davis, D. W. Head armor module for aircrewmembers protection (U). Technical Report on Phase 2. Report Nr PA-TR-3906, Project Nr DA-1-M-643303-D-547, Picatinny Arsenal, N. J., February 1970. (Confidential report)
75. Davis, D. W. Development of composite armor and aircrewmembers head protection (First Phase) (U). Technical Report Nr PA-TR-3865, Project Nr DA-1-M-624101-D-504, Picatinny Arsenal, N. J., January 1970. (Confidential report)
76. Dean, B. S. Helmets and body armor in modern warfare. Yale University Press, 1920.
77. DeBell & Richardson, Inc. Development of an integral finish helmet liner: Final report 29 June 1960. Contract Nr DA 19-129-qm-1138, Hazardville, Conn.
78. DeBell & Richardson, Inc. Development of rapid production systems for laminated nylon helmet liners. Contract Nr DA 19-129-qm-328, Hazardville, Conn., 11 August 1960.
79. Department of the Army. Armor, fragment-resistant; plate or sheet; general specification. U. S. Army specification AXS-1346 (Rev. 1) Washington, D. C., 18 April 1945.
80. Desert Warfare Board. Liners, helmet M1. Report Nr 36, 22 June 1942.
81. Dohnal, F., & Cook, C. R. Deep drawing of titanium alloy helmet shell - 6 AL-4V. Contract Nr DA 19-129-qm-1430, Thompson Ramo Woolridge, Inc., Los Angeles, Calif., May 1960.
82. Dorfman, D., Stein, S. D., & Salzman, R. S. Terminal effects of flechettes (U). Ammunition Engineering Directorate, Picatinny Arsenal, Dover, N. J., April 1964. (Secret report)
83. Dunlap, J. W., & Affinito, F. J. Development of methodology for measuring effects of personal clothing and equipment on combat effectiveness of individual soldiers: Final report of Phase III. U. S. Army General Equipment Test Activity, Ft. Lee, Va., December 1967.
84. Dyer, E. G. Individual combat clothing and equipment: Status report 1 June-30 November 1970. Marine Corps Development & Education Command, Quantico, Va., November 1970.

This report covers the period 1 June-30 November 1970 and presents the current status of items of individual combat clothing and equipment considered to offer potential improvement over existing Marine Corps items.
85. Dziemian, A. J., Light, F. W., Washburn, M. L., & Coe, G. B. Chemical Corps Medical Laboratory Research Report Nr 219. Army Chemical Center, Md., October 1953. (Confidential report)
86. Egly, J. M. Combat helmet development (suspension studies). Report OG-998-D-2, Cornell Aeronautical Laboratories, Buffalo, N. Y., January 1957.

87. Electro-Optical Systems, Inc. Night vision goggles (U): quarterly report no. 1, 30 September-31 December 1966. Report Nr EOS-7145-Q-1, Pasadena, Calif., April 1967. (Confidential report)

The purpose of this program is to design, develop, construct, test and deliver engineering design models of night vision goggles (NVG). The goggles are required to meet the detailed requirements set out in the purchase description. Emphasis is to be placed on performance. Reliability, durability, minimum weight and size, maintenance, and compatibility with gas mask and other head or helmet mounted equipment. A total of 18 goggles are to be delivered over a period of 20 months. This report describes the work performed during the first three months of the program. During this period the main effort has been expended in objective lens design, the preliminary design of the monocular, and problems, involved in tube integration. A Human Factors study, was instituted with primary emphasis on the design of a mask for mounting the goggle to the wearer's head. Designs for special purpose test fixtures have been started and some parts procured. The design and fabrication of anticondensation discs is also proceeding. An appendix to the report contains a detailed technical description for the NVG prepared in purchase description form. The appendix also contains descriptions of the test equipment and test procedures (U).

88. Ewing, H. O., Jr., & Furgeson, W. J. NRL Report October 1952 (U). Naval Research Laboratory, Washington, D. C. (Confidential report)
89. Fassler, G. D. Individual combat clothing and equipment: Status report 1 July - 31 December 1968. Marine Corps Development & Education Command, Quantico, Va., January 1969.

Monitoring of development progress on combat clothing and equipment comprised the major effort. Specific items discussed, to include the status thereof, are as follows: (1) armored vehicle crewman's uniform; (2) woodsman's Pal 681 survival axe; (3) joint operational requirement for body armor; (4) lightweight intrenching tool; (5) LINCLOE lightweight nylon helmet; (6) overhead cover for foxholes; (7) nomex material in the utility uniform; and (8) high fragment protection body armor.

90. Fassler, G. D. Individual combat clothing and equipment: Status report 1 January - 30 June 1969. Marine Corps Development & Education Command, Quantico, Va., July 1969.

Monitoring of developmental progress on combat clothing and equipment comprised the major effort during the reporting period. Specific items discussed are as follows: Armored vehicle crewman's summer uniform: Machete: Lightweight (JOR) body armor: Lightweight intrenching tool: Lightweight (LINCLOE) helmet: Overhead cover for foxholes: High fragment protection body armor: Winter uniform for armored vehicle crewmen: Camouflaged jungle hat: Temperate zone combat uniform: Flame resistant utility uniform: Zipper lacing for DMS tropical combat boot: Bivouac shoe: Combat life jacket flotation cell.

91. Fassler, G. D. Individual combat clothing and equipment: Status report 1 July - 31 December 1969. Marine Corps Development & Education Command, Quantico, Va., January 1970.

The report presents the current status of items of individual combat clothing and equipment considered to offer potential improvement over existing Marine Corps items. Monitoring developmental progress on the items of interest constituted the major effort during the reporting period. Specific items covered in this report are: Machetes, lightweight (JOR) body armor, rainsuits, wading coverall, small arms/fragment body armor, lightweight helmet, LINCLOE load carrying equipment, life preserver, overhead cover for foxholes, armored vehicle, crewmen uniform, temperate zone combat uniform, zipper lacing for combat boot, bivouac shoe.

92. Finch, G. A., & Schroeder, F. C. Helmet cost study. Systems and Cost Analysis Division, Army Materiel Command, Washington, D. C., December 1968.

The study provides life cycle cost data on these US Army infantry-type helmets: (1) titanium type I; (2) titanium type III; (3) LINCLOE nylon; and (4) Hayes-Stewart. These data include research and development production, and operating costs. A 95 percent learning (experience) curve gradient is appropriate for helmet production.

93. Forshaw, S. E., Clarke, D. P. J., & Neely, K. K. Acoustic properties of headgear: XX. The Safety Supply Co. Type 358 earmuff C/W high-impedance earphone conversion; and the Welsh Mfg. Co. styles 4501 and 4502 'sound-off' ear protectors (U). Technical Memo Report Nr DRML-TM-593, Defence Research Medical Laboratories, Toronto (Ontario), September 1965. (Confidential report)
94. Furgeson, W. J., & Ewing, H. NRL Report December 1951 (U). Pp. 28-29. Naval Research Laboratory, Washington, D. C. (Confidential report)
95. Furgeson, W. J., & Seibert, E. R. Evaluation of glass reinforced plastic helmets (U). Memorandum Report Nr NRL-F04-02, Naval Research Laboratory, Washington, D. C., June 1968. (Confidential report)
96. Gardner, J. H., Hitchman, N. A., & Best, R. J. Protection of the soldier in warfare. Report ORO-R-5, Operations Research Office, Johns Hopkins University, Chevy Chase, Md., January 1952.
97. General Textile Mills, Inc. Development of tropical helmet. Contract Nr W44-109-qm-1295.
98. General Tire & Rubber Company. Liner (nylon) helmet, soldiers' steel, T57-4: Final report. Contract Nr DA-19-129-qm-1219, Wabash, Ind.
99. General Tire & Rubber Company. Alternate armor materials for helmet liners: Progress report No. 1 November/January 57. Contract Nr DA-19-129-qm-768, Wabash, Ind.

100. George, T. W., & Clark, J. B. NRL Report November 48 (U). P. 29. Naval Research Laboratory, Washington, D. C. (Confidential report)
101. George, T. W., & LaTome. NRL Report December 1948 (U). P. 28. Naval Research Laboratory, Washington, D. C. (Confidential report)
102. George, T. W., Clark, J. B., & Sullivan, S. F. NRL Report May 1950 (U). P. 29. Naval Research Laboratory, Washington, D. C. (Confidential report)
103. George, T. W., & Furgeson, W. NRL Report October 1950 (U). P. 26. Naval Research Laboratory, Washington, D. C. (Confidential report)
104. George, T. W., Furgeson, W., & Bernstein, H. NRL Report December 1950 (U). Pp. 44-46. Naval Research Laboratory, Washington, D. C. (Confidential report)
105. George, T. W., Furgeson, W., & Ewing, H. NRL Report January 1951 (U). Naval Research Laboratory, Washington, D. C. (Confidential report)
106. George, T. W. NRL Report June 1952 (U). P. 32. Naval Research Laboratory, Washington, D. C. (Confidential report)
107. Gilson, R. A., & Quaid, T. B. An integrated circuit helmet radio receiver. Published in IEEE International Convention Record PT6 P106-17, Army Electronics Command, Ft. Monmouth, N. J., 1967.

The design and development of an integrated circuit FM receiver is described, with emphasis on the unique aspects of integrated circuit design. Seven silicon monolithic linear integrated circuits of five different types are used in the VHF receiver, and each of these is described individually. Also discussed is the degree of realization of the overall design goals, namely optimum performance, low cost, low power drain, and high reliability.

108. Glidden Company. Army helmet research. Contract Nr DA 44-109-qm-346.
109. Goulet, D. V., & Sacco, W. Algorithms for sizing helmets. National Research Council Committee on Helmets, 13-14 September 1971, Washington, D. C.
110. Gransucci, J. S., & Kasson, H. D. Operational test and evaluation of AN/PRC-87 pararescue radio. MAC-OT/E-6-1-68, Military Airlift Command, Scott Air Force Base, Ill., April 1971.
111. Greaney, A. L. Engineer design test of special design infantry helmet (compatibility phase): Final report. U. S. Army Infantry Board, Ft. Benning, Ga., September 1968.
112. Green, A. A literature study of sound as related to the combat vehicle crewman helmet. Quartermaster Research & Engineering Center, Natick, Mass., January 1958.
113. Gregg, A. J. Project supporting paper relating to helmets and body armor 1917 - August 1945. Quartermaster Research & Development Laboratory, Ordnance Department (Army), Washington, D. C., 1945.

114. Gruber, A., Dunlap, J. W., & DeNittis, G. Development of a methodology for measuring effects of personal clothing and equipment on combat effectiveness of the individual field soldier. Contract Nr DA 19-129-qm-2068, Dunlap & Associates, February 1964.
115. Gruber, A., Dunlap, J. W., & DeNittis, G. Development of methodology for measuring effects of personal clothing and equipment on combat effectiveness of individual soldiers: Final report of Phase II, December 1964. Development of a methodology for measuring infantry performance in rifle firing and reloading, June 1965. Development of a methodology for measuring infantry performance in maneuverability, June 1965. U. S. Army General Equipment Test Activity, Ft. Lee, Va.
116. Haley, J. R., & Turnbow, J. W. Impact test methods and retention harness criteria for US Army aircrewman protective headgear. Project Nr DA-44-177-AMC-254-T, Aviation Safety Engineering & Research, Phoenix, Arizona, March 1966.
117. Handford, S. W., & Lewis, F. J. Protective and armored garments with related pertinent mechanisms of wounding: The physiologic and pathologic effects of implanted body armor materials. Vol. III, Naval Medical Field Research Laboratory, Camp Lejeune, N. C., July 1951.
118. Hardaway, B. F. Evaluation of the nylon helmet liner. Letter Report (JRATA 2K 452.0), ARPA Research & Development Field Unit - Vietnam, Office of the Secretary of Defense, APO 143, San Francisco, Calif., 1 November 1964.
119. Hardigg, W. B., & Eddy, G. G. Test of steel helmets submitted by the US Armor Corporation. APG-OP-4889-6, Aberdeen Proving Ground, Md., January 1941.
120. Hardigg, W. B., & Eddy, G. G. Test of steel helmets, helmets submitted by the McCord Radiator and Mfg Co. APG-OP-4889-7, Aberdeen Proving Ground, Md., January 1941.
121. Hardigg, W. B. Test of steel helmets: Report No. 1, June 6, 1941. Ordnance Program Nr 4889, Report Numbers 6, 7, 8, 9 and 10. Aberdeen Proving Ground, Md.
122. Hassett, R. J., Hanlein, S. L., & Goeller, J. E. Protective eye shield against small fragments. Final report Nr NOLTR-70-202, Naval Ordnance Laboratory, White Oak, Md., June 1970.

Casualty reports from southeast Asia indicate a need for a small fragment protective eye shield which will not interfere with the normal duties of the user. Commercially available eye goggles which are in accordance with Federal Specification FSN 4240-052-3776 were evaluated and found to provide inadequate ballistic protection. A polycarbonate eye shield which can be easily attached to the M-1 steel helmet was designed and found acceptable in evaluation reports from Vietnam. Ballistic data on the shield and construction details are given in this report.

123. Hawkins, C. E., Stewart, G. M., Williams, R. L., & London, J. C., Jr. Resistance of body armor to projectiles. Part V. Body armor materials and quartermaster end items versus steel flechettes (U). CRDL Report Nr 3212, Chemical Research & Development Laboratories, Edgewood Arsenal, Md., April 1964. (Secret report)

124. Hirsh, I. J., & Pollack, I. Size of earphones to be used under the M-1 helmet. Harvard University, Psycho-Acoustic Laboratory, Cambridge, Mass.
125. Hitchman, N. A. Keep your head....keep your helmet. Army, September 1957.
126. Holbourn, A. H. S. Mechanics of head injuries. The Lancet, 1943, 438-441. (London, England)
127. Holding, D. H., & Dennis, J. Hearing in the combat cap. Report Nr CEPRE 37, Clothing & Stores Experimental Establishment, Great Britain, June 1954.
128. Hurlich, A., & Sullivan, J. F. Metallurgical and ballistic comparison of German, Japanese and American (M1) helmets. WAL 710/776, Watertown Arsenal, Mass., 21 September 1945.
129. Johns Hopkins University. A comparison of various materials in their resistance to perforation by steel fragments: Empirical relationships (U). Report Nr 25, Contract DA-36-034-ORD-1678, Baltimore, Md., July 1965. (Confidential report)
130. Johnson, W. P., Collins, L. I., & Kindred, F. A. A mathematical model for predicted residual velocities of fragments after perforating helmets and body armor (U). Technical Note Nr BRL-TN-1705, Project Nr RDT/E-1-T-062110-A-027, Ballistic Research Laboratories, Aberdeen Proving Ground, Md., October 1968: (Confidential report)

Experimental ballistic data acquired from the Biophysics Laboratory, Edgewood Arsenal, has been generalized in order to predict the residual velocity of various fragments after striking different types of protective material. The predictions are a function of the initial striking velocity of the fragment and the A/M ratio of the fragment, where A represents the average cross-sectional area of the missile along its trajectory and M represents the weight of the fragment striking the protective material. Generalizations have been made from observations of the behavior of cubes with initial weights ranging from 1 to 225 gr. Data are presented for independent assessments of the 0 and 45 degree obliquity angles (U).

131. Johnson, W. P., Collins, L. I., & Taylor, T. M. Expected residual velocities of cubes perforating armor material as a function of projectile size and obliquity angle (U). Memorandum Report Nr BRL-MR-2011, Ballistic Research Laboratories, Aberdeen Proving Ground, Md., September 1969. (Confidential report)

Experimental residual velocity data, acquired from the Body Armor Branch, Edgewood Arsenal, Maryland, have been generalized for several types of armor materials. These data consisted of firings at both the 0 and 45 degree angles of obliquity with cubes ranging in weight from 1 to 225 grains. A mathematical model is presented which can be used to determine the expected residual velocity of cubes, within the range of the experimental data, that perforate specific armor materials as a function of their size and obliquity angle (U).

132. Kane, R. L., & Smith, R. S. A forming technique for soldiers titanium helmets. Final Technical report, Titanium Metals Corporation of America, West Caldwell, N. J., July 1968.

The report discusses the use of both alloy and commercially pure titanium metal for fabrication of infantry helmets. The use of titanium metal allows a weight reduction without impairing the ballistic protection of the helmet.

133. Kane, R. L., & Smith, R. S. A forming technique for soldiers titanium helmets. Technical Report Nr 69-32-GP, Army Natick Laboratories, Natick, Mass., July 1968.
134. Kastenbein, E. L., McLaren, M. G., & Matolka, R. W. Investigation of low density and reinforced ceramic structures for application in helmet and body armor (U): Final report. Contract DA 19-129-qm-1974, Project Nr 7 80 05 001, Rutgers - The State University, School of Ceramics, New Brunswick, N. J., September 1963. (Confidential report)
135. Kauffman, J. W., & George, T. W. NRL Report May 1949 (U). P. 45. Naval Research Laboratory, Washington, D. C. (Confidential report)
136. Kauffman, J. W., & George, T. W. NRL Report August 1949 (U). Pp. 30-31. Naval Research Laboratory, Washington, D. C. (Confidential report)
137. Keith, N. A., & Jeltema, D. J. Service test of headset-microphone kit MK-1039/G for combat vehicle crewmans helmet, T56-6. Army Armor & Engineering Board, Ft. Knox, Ky., February 1968.
138. Keithley, S. M., & Fry, D. Product improvement test of infantry helmets, special array test: Final report 12 June-15 December 1968 (U). Report Nr APG-MT-3076, Materiel Test Directorate, Aberdeen Proving Ground, Md., March 1969. (Secret report)
139. Kleiman, F. G. A field test of cap, pile T56-3 and liner, helmet, soldiers, steel, T55-2A. FEA 56036, Quartermaster Research & Development Field Evaluation Agency, April 1957.
140. Kobrick, L., & Crist, B. Quartermaster human engineering handbook series: VII. The size and shape of the available visual field during the wearing of army headgear. Technical Report Nr EP-133, Quartermaster Research & Engineering Center, Natick, Mass., May 1960.
141. Kobrick, J. L. Quartermaster human engineering handbook series: VI. Size limits of the head and neck area of the soldier wearing QM gear. Technical Report Nr EP-107, Quartermaster Research & Engineering Center, Natick, Mass., March 1959.
142. Kokinakis, W., & Sperrazza, J. Criteria for incapacitating soldiers with fragments and flechettes (U). Report Nr BRL-1269, Ballistic Research Laboratories, Aberdeen Proving Ground, Md., January 1965. (Secret report)

143. Land Vehicle Board. Test of liner and helmet, T19E1. Project 49, Ft. Ord, Calif., 7 August 1945.
144. Landsberg, M. I., & Lewis, J. L. Final development and engineering test report of liner, helmet, soldier's, steel, T54-1 and helmet and liner, combat, T53-2. Technical Nr CP-2, Project Nr 7-80-05-001, Quartermaster Research & Development Center, Natick, Mass., November 1955. (Confidential report)
145. Lastnick, A. Thermal protective characteristics of standard and experimental combat helmet and body armor materials subjected to intense thermal radiation. Technical Report Nr CP-6, Quartermaster Research & Engineering Center, Natick, Mass., August 1957.
146. Lastnick, A. L. Molding helmet liners for nylon cloth made from 1050 denier type 700 nylon yarns. Quartermaster Research & Engineering Center, Natick, Mass., July 1962.
147. Lastnick, A. L. Factors influencing the impact energy attenuation capabilities of the US Army flyer's protective helmet (AFH-1). Project Nr DA-1-M-64330, Army Natick Laboratories, Natick, Mass., July 1968.
148. Lastnick, A. L. Advances in the development of head protection for aircraft crewmen. Technical Report Nr 67 53 CM, U. S. Army Natick Laboratories, Natick, Mass., February 1967.
149. Lastnick, A. Development and fabrication of polycarbonate eyeshield for USA flyer helmet. Technical Report Nr 71 3 CE, Army Natick Laboratories, Natick, Mass., June 1970.
150. LaTorre, R. R., & George, T. W. NRL Report February 1949 (U). P. 27. Naval Research Laboratory, Washington, D. C. (Confidential report)
151. LaTorre, R. R., & George, T. W. NRL Report May 1949 (U). P. 44. Naval Research Laboratory, Washington, D. C. (Confidential report)
152. Lepore, R. R. Alternate armor materials for helmet liners. Contract Nr DA 19-129-qm-768, General Tire & Rubber Company, Wabash, Ind., December 1960.
153. Lewis, F. J. Note on a method for producing experimental helmet models in plastic. Naval Medical Field Research Laboratory, Camp Lejeune, N. C., June 1950.

In the design and development of helmets for various applications, it is often necessary to fabricate several experimental models. Various changes and modifications are incorporated in each successive model, with the final model representing the optimum compromise between natural anthropometric factors and military requirements. This report describes a rapid, economical and flexible method for the production of these experimental models.

154. Lewis, F. J., Sr., Cole, F. A., Jordon, R. D., Denick, L. G., Quinlam, J. F., & Inskeep, M. D. Military helmet design report NM 81-01-09, Naval Medical Field Research Laboratory, Camp Lejeune, N. C., June 1958.

155. Link, M. M., & Coleman, H. A. Medical support of the Army Air Force in WW II. Office of the Surgeon General, U. S. Air Force, Washington, D. C., 1955.
156. Long, J. L. Service test of functional uniform for armored vehicle crewman under arctic winter conditions: Partial report. Army Arctic Test Center, Ft. Greely, Alaska, April 1969.
157. Mangum, E. W. Engineer design test of Hayes-Stewart helmet (non-ballistic version): Final report. U. S. Army General Equipment Test Activity, Ft. Lee, Va., December 1969.
158. Margosiak, S. A. Development of rapid production systems for laminated nylon helmets liner. Contract DA 19-129-qm-828, DeBell & Richardson, Inc., Hazardville, Conn., August 1960.
159. Marine Corps Equipment Board. Helmets, plastic, test of. Project Nr 411, Marine Corps Equipment Board, Quantico, Va., 15 June 1945.
160. Marine Corps Equipment Board. Modification, certain equipment, (helmet, steel). Test Report Project Nr 454, Marine Corps Equipment Board, Quantico, Va., 18 September 1945.
161. Marine Corps Landing Force Development Center. Cold weather helmet system service test: Report of (U). Marine Corps Landing Force Development Center, Quantico, Va., June 1961. (Confidential report)
162. Marine Corps Development & Education Command. Status report of USMC Project Nr 42-68-02, individual combat clothing and equipment (as of July 1968). Marine Corps Development & Education Command, Quantico, Va., July 1968.

A requirement exists for improved items of lightweight clothing and equipment to lighten the load of the infantryman. In this respect, acceptance of reduced service life will permit the utilization of new designs and lighter weight materials which will contribute significantly to reducing the weight of clothing and individual equipment. The modifications made to the Marine Corps M-1967 Load Carrying System to permit attachment of the lightweight intrenching tool (FSN 521-878-5932) and carrier will increase the overall versatility of the M-1967 Load Carrying System. The exploratory development of a prototype lightweight helmet (GRP) by the Marine Corps will provide extensive support to the product improvement efforts addressed in the Army QMR for LINCLOE.

163. Mascianica, F. S. Personnel armor-ballistic evaluation of laminated nylon helmet liners - Model EX 49-3 (U). Report Nr WAL 710/998, Watertown Arsenal Laboratories, Watertown, Mass., January 1952. (Confidential report)
164. Mascianica, F. S. Personnel armor; ballistic evaluation of aluminum alloy helmet shells and laminated nylon liners, Models EX 49-3. Report Nr WAL 710/999, Watertown Arsenal Laboratories, Watertown, Mass., February 1952.

165. Mascianica, F. S. Personnel armor, ballistic evaluation of M1 and experimental EX 51-1 helmets (U). Report Nr WAL 710/1013, Watertown Arsenal Laboratories, Watertown, Mass., 21 August 1953. (Confidential report)
166. Mascianica, F. S. Ballistic and metallurgical evaluation of Soviet infantry helmets and comparison with American helmets. Report Nr WAL 710/1015, Watertown Arsenal Laboratories, Watertown, Mass., 3 January 1954.
167. Mascianica, F. S. Ballistic evaluation of experimental nylon helmet liners, T54-1 with and without M1 steel helmet shells (U). Report Nr WAL-TR-710/1048, Watertown Arsenal Laboratories, Watertown, Mass., 11 October 1954. (Confidential report)
168. Mascianica, F. S. Ballistic and metallurgical evaluation of a Danish helmet (U). Report Nr WAL-TR-710/1050, Watertown Arsenal Laboratories, Watertown, Mass., 23 November 1954. (Confidential report)
169. Mascianica, F. S. Ballistic and metallurgical evaluation of a Canadian Army helmet (U). Report Nr WAL-710/1051, Watertown Arsenal Laboratories, Watertown, Mass., 19 September 1955. (Confidential report)
170. Mascianica, F. S. Ballistic evaluation of experimental helmet and liner, combat T53-2 (U). Report Nr WAL-TR-710-1061C, Watertown Arsenal Laboratories, Watertown, Mass., October 1955. (Confidential report)
171. Mascianica, F. S. Ballistic and metallurgical evaluation of a Swedish helmet (U). Report Nr WAL-TR-710/1063, Watertown Arsenal Laboratories, Watertown, Mass., 16 August 1956. (Confidential report)
172. Mascianica, F. S. Ballistic and metallurgical evaluation of a Norwegian helmet (U). Report Nr WAL 710/1064C, Watertown Arsenal Laboratories, Watertown, Mass., November 1956. (Confidential report)
173. Mascianica, F. S. Ballistic evaluation of an experimental Canadian helmet (U). Report Nr WAL 710/1072C, Watertown Arsenal Laboratories, Watertown, Mass., January 1957. (Confidential report)
174. Mascianica, F. S. Ballistic concepts employed in testing lightweight armor: Monograph series. Report Nr WAL-MS-12, Watertown Arsenal Laboratories, Watertown, Mass., October 1959.

The ballistic testing techniques which are described have been developed by various research establishments with a view toward improving ballistic testing techniques, especially with regard to determining ballistic limits with minimum number of rounds and developing a simple and reproducible test. Much thought has been given to developing and standardizing a ballistic test for use in rating, comparing, and testing fragment-resistant armor. The ballistic test that is currently in use by the Ordnance Corps for specification acceptance of lightweight armor materials is the one employing fragment-simulating projectiles. It is considered to be the simplest, most reproducible, and most meaningful of any test developed to date.

175. Mascianica, F. S. Ballistic performance of nylon helmet liners (U). Report Nr AMRA-ABI-46, Army Materials Research Agency, Watertown, Mass., July 1966. (Confidential report)
176. Mascianica, F. S. Ballistic technology of lightweight armor (U). AMMRC TR71-21, Army Materiel & Mechanics Research Center, July 1971.
177. Matthews, J. M. An engineering test of armor, body, fragmentation protective, 3/4 collar, T59-1. Technical Report Nr T-156, FEA 59052, Quartermaster Field Evaluation Agency, U. S. Army, Quartermaster Research & Engineering Command, Ft. Lee, Va., May 1960.
178. McArthur, L. F., Feldmann, F. W., & Hill, R. S. Integrated helmet for thermalibrium ensemble. Progress Report Nr 67-69, Contract Nr DAAG17-67-C-0220, ILC Industries, Inc., Dover, N. J., May 1969.

A program was conducted to design and fabricate an integrated helmet for the thermalibrium ensemble, a universal protective clothing system. Using the government furnished integrated helmet as a guide, the design goals included increasing the stability of the present ballistic helmet assembly and reducing the outer shell area. The helmet designed and fabricated consists of a laminated ballistic nylon outer shell and a polycarbonate inner shell. The head is completely encapsulated by the helmet, a retractable polycarbonate face shield and an airtight neck-shroud helmet seal. The inner shell contains the head suspension, filtered air inlet connector, communications and the emergency filter.

179. McCord Corporation. Aluminum talker helmet: Progress report. Contract Report Nr 19-129-qm-673, Detroit, Mich.
180. McCord Corporation. .134" aluminum helmet, 24st alloy: Final report. Contract Report Nr DA 44-109-qm-1798, Detroit, Mich., 18 January 1955.
181. McCord Corporation. Helmet shell aluminum 24st (large and small): Final report. Contract Report Nr DA 44-109-qm-149, Detroit, Mich., 29 June 1951.
182. McGinnis, J., & Rosinger, G. Human factors study of the compatibility of the QMC equipped soldier with field communications equipment under cold wet conditions. Research Study Report Nr PB-38, Project Nr 7x95-01-001, Quartermaster Research & Engineering Center, Natick, Mass., July 1960.
183. McKenzie, D. M. A human engineering evaluation of the combat vehicle crewmans helmet T56-6. Technical Memorandum 10-69, Human Engineering Laboratories, U. S. Army Aberdeen Research & Development Center, Aberdeen Proving Ground, Md., August 1969.
184. McLean, E. A., & George, T. W. NRL Report July 1949 (U). P. 21. Naval Research Laboratory, Washington, D. C. (Confidential report)
185. McLean, E. A., & George, T. W. NRL Report September 1949 (U). P. 34. Naval Research Laboratory, Washington, D. C. (Confidential report)
186. McManus, L. Problems of the M1 helmet and an analysis of foreign helmets, 13-14 September 1971. National Research Council Committee on Helmets, Washington, D. C.
187. Metals and Alloys. Fabricating and finishing the new M-1 soldier's helmet: A pictorial description. Vol. 19, 1137-1140 (1940).

188. Midwest Research Institute. A method of predicting the performance of light armor. Final report on Contract W-23-072-ORD-2123 WAL 710/858-11 (Part I); 15 November 1948.
189. Miller, J. F., Ashman, W. P., & Jameson, J. W. Ballistic limits of skulls against steel cubes (U): technical report November 67-October 1968. Report Nr EA-TR-4373, Project Nr DA-1-T-062110-A-027, Edgewood Arsenal, Md., April 1970. (Confidential report)
190. Milner, P., & DiMattia, A. L. Development of microphones for high ambient noise operation. ECOM-0661-F, CBS Laboratories, Stamford, Conn., January 1970.
191. Modern Plastics. The army helmet liner. Pp. 35-38, May 1942.
192. Modern Plastics. Triumph in a helmet. Vol. 20, pp. 53-55, November 1942.
193. Modern Plastics. Wind up of the helmet. Vol. 20, pp. 49-52, April 1943.
194. Morrissey, P. J., & Sullivan, J. T. Evaluation of vests (US Army M1952-3A US Marine M1955, titanium composite T61-5, and experimental nylon felt) and M1 helmet and nylon liner vs. M-26 grenade (U): Technical memo February-July 1965. Report Nr CRDL-TM-2-22, Chemical Research & Development Laboratories, Edgewood Arsenal, Md., September 1965. (Confidential report)
195. Motsinger, A. V. Development of E10R27 helmet-mounted field protective mask. Report Nr CRDL-SP 3-12, Chemical Research & Development Laboratories, Edgewood Arsenal, Md., October 1963.

The objective of this work was to develop a field protective mask that could be donned quickly, without removal of the helmet, either from an alert position while attached to the helmet or from a carrier on the cartridge belt. The E10R27 Field Protective Mask can be carried either on the helmet with the facepiece in a folded alert position, from which it can be fitted on the face in about 2 seconds, or it can be inserted in a carrier attached to a cartridge belt, from which it can be donned in about 6 seconds. By adjustment of straps to fit the head, the mask can be used independent of the helmet. Using the E10 mask without removal of the helmet eliminates the battlefield hazard of exposing the head, and shortens the time necessary to mask.

196. National Academy of Sciences - National Research Council Advisory Board on Military Personnel Supplies Meeting, Committee on Helmets, 13-14 September 1971, Washington, D. C.
197. National Bureau of Standards. Development of body armor, helmets and armored clothing, 1 July to 30 September 1953. Washington, D. C., September 1963.
198. Naval Proving Ground. Ballistic test of 5/8" titanium armor. NPG Report Nr 584, Dahlgren, Va., 17 July 1950.
199. Naval Proving Ground. Fragment-resistant light armor (U). Reports Nrs 474(C) and 617(C), Dahlgren, Va., 17 January 1950 and 17 August 1950. (Confidential reports)
200. Naval Proving Ground. Metallurgical examination of 5/8" plate of commercial titanium. NPG Report Nr 859, Dahlgren, Va., 17 October 1951.
201. Neely, K. K. Acoustic properties of headgear: II. Helmets LTD. headgear assembly. Report Nr 100-3, Defence Research Medical Laboratories, Toronto (Ontario), April 1954.

202. Neely, K. K., & Thrasher, G. D. Acoustic properties of headgear: IX. The effect of various helmet suspensions (U). Report Nr TM100-10, Defence Research Medical Laboratories, Toronto (Ontario), August 1960. (Confidential report)
203. Neely, K. K., & Thrasher, G. D. Acoustic properties of headgear: XI. Two suspensions and two ear seal combinations (U). Report Nr TM100-12, Defence Research Medical Laboratories, Toronto (Ontario), August 1960. (Confidential report)
204. Newman, R. W. Anthropometric analysis of liner, helmet T55-2A, etc. Research Study Report Nr PA-9, Project Nr 7-83-01-004, August 1956.
205. Office of Chief of Ordnance. Helmets and body armor. Department of the Army, Washington, D. C., 1 June 1945.
206. Office of Naval Research. Titanium, report of symposium, 16 December 1948. Department of the Navy, Washington, D. C., March 1949.
207. Office of the Quartermaster General. History of development of Quartermaster supplies No. 21, plastics helmet liners. Historical Staff Military Planning Division, Department of the Army, Washington, D. C., 30 January 1947.
208. Office of the Quartermaster General. Quarterly technical progress report of Quartermaster research and development. Department of the Army, Washington, D. C., 30 September 1948.
209. Office of the Quartermaster General. Technical progress report, 1 July - 31 August 1949. Military Planning Division, Department of the Army, Washington, D. C., 31 August 1949.
210. Office of the Quartermaster General. Quarterly technical progress report of Quartermaster research and development, 2nd quarter, FY 1949. Military Planning Division, R&D Branch, Department of the Army, Washington, D. C.
211. Office of the Quartermaster General. Quarterly technical progress report of Quartermaster research and development, 3rd quarter, FY 1949. Military Planning Division, R&D Branch, Washington, D. C.
212. Office of the Quartermaster General. Technical progress report, 4th quarter, FY 1949. Military Planning Division, R&D Branch, Washington, D. C.
213. Office of the Quartermaster General. Technical progress report, 1 January - 30 June 1950. Military Planning Division, R&D Branch, Washington, D. C.
214. Office of the Quartermaster General. Technical progress report, 1 July - 31 December 1950. Military Planning Division, R&D Branch, Department of the Army, Washington, D. C.
215. Office of the Quartermaster General. Technical progress report, 1 January - 31 December 1951. Military Planning Division, R&D Branch, Department of the Army, Washington, D. C.
216. Office of the Quartermaster General. Technical progress report, 1 January - 31 December 1952. Military Planning Division, R&D Branch, Department of the Army, Washington, D. C.

217. Office of the Quartermaster General. Army helmet conference, 9-10 December 1952, Department of the Army, Washington, D. C.
218. Office of the Quartermaster General. Headgear conference held in Research and Development Division. Department of the Army, Washington, D. C., 2 July 1953.
219. Office of the Quartermaster General. Technical progress report, 1 January - 31 December 1953. Military Planning Division, R&D Branch, Department of the Army, Washington, D. C.
220. Office of the Quartermaster General. Classified supplement to technical progress report, 1 January - 31 December 1953. Military Planning Division, R&D Branch, Department of the Army, Washington, D. C.
221. Office of Scientific Research & Development. Metallurgical examination of German canteen and messkit; and Japanese canteens and helmets. OSRD Nr 5265, 22 June 1945.
222. Office of Technical Services. Selected bibliography on titanium. SB-20, Washington, D. C., September 1949.
223. Olin Matheson Chemical Corporation. Feasibility study for the production of a transparent plastic laminate: Final report 30 September 1959. Contract Nr DA 19-129-qm-1187.
224. Olivier, A. G., Brown, B. J., & Merkler, J. M. Wound ballistics of the 0.85-grain steel disk (U). Report Nr 2372, Army Chemical Warfare Laboratories, Army Chemical Center, Md., May 1950. (Secret report)
225. O'Neal, J. W. OT&E of custom fitted helmets and modified HGU-17/P comparison, Phase B. TAC-TR-68-202, Tactical Fighter Weapons Center, Nellis AFB, Nev., August 1969.
226. Operations Research Office. Semi-annual report, Vol. IV, Nr 2, 31 December 1951 (U). Johns Hopkins University, Chevy Chase, Md. (Confidential report)
227. Ormeller, F. J. Test and evaluation of universal full face helmet assembly: Final report Nr ST35 39R63. Naval Air Test Center, Patuxent River, Md., August 1963.
228. Pittsburgh University. Development of radio receiver, AN/PRR-9, and radio transmitter, AN/PRT-4: Interim report. Pittsburgh, Pa., September 1964.

This report describes a versatile, compact, squad radio set that consists of two different but related components. One component is the AN/PRR-9 radio receiver that is normally attached to the helmet of its user, the other is the handcarried AN/PRT-4 radio transmitter. The set is intended to help the leader of a small unit maintain control in future warfare operations (present doctrine calls for wide dispersion of small units), outposts, observation posts, and crew-served weapons leaders can issue orders through the set without the necessity of shouting or leaving covered positions.

229. Pittsburgh University. Development of head-contact, microphone, M-123 ()/U. Contract DA 49 186-AMC-214D, Pittsburgh, Pa., February 1965.

The M-123 ()/U head-contact microphone is being developed for use with the latest types of radio equipment and protective headgear used by ground or air personnel of the Army, such as infantrymen, armored vehicle crews, and aircraft crews. One experimental model, a velocity-sensitive transducer, uses a modified magnetic phonograph pickup cartridge that is coupled to the skin by a contact disk that picks up aural sounds conducted by the bone structure of the head and converts them into electrical impulses. This model is held against the forehead by an elastic strap. Another experimental model makes use of a miniature inertial transducer with low mechanical impedance. In this unit, the transducer is a small crystal compliantly mounted to an outer case with four small springs and the assembly is attached to the head with a flexible strap.

230. Pittsburgh University. Personnel armor for ground troops and aircrews (U): Interim report. Contract Nr DA 49-186-AMC-214(D), Research Staff, Washington, D. C., January 1968. (Secret report)

Although body armor and helmets developed in WW II saved the lives of many ground troops and fliers, they were effective only in defeating shell fragments. Since then, new materials and better designs have permitted the fabrication of lighter, more comfortable armor that gives protection against caliber .30 and 7.62-MM ammunition. Modern armor is articulated so that it responds to bodily movements and does not hamper the wearer's activities. Designers of body armor have as their objective the defeat of caliber .50 bullets without an increase in the weight of the armor or a lessening of its flexibility. Noteworthy developments of recent years are armored seats for pilots and copilots for protection in the back, the sides, and the front, and from below, and small arms protective armor for aircrewmembers (U).

231. Pleskun, W. G. A/P 22S-2 lightweight helmet. Project Nr 6336, Contract Nr AF 33 600 41559, David Clark Company, Inc., Worcester, Mass., April 1965.
232. Plumb, R., & Urban, J. J. Porous laminated protective head shield. Report Nr TR 6211, Walter Reed Army Medical Center, Army Medical Biomechanical Research Laboratory, Washington, D. C., May 1962.
233. Popper, P., & Hoffman, D. Protective efficiency of the polyamid helmet. Report Nr FSTC-381-T65-513, Army Foreign Science & Technology Center, Washington, D. C., November 1965.

Translation of Italian report on the protective efficiency of polyamide plastic helmets.

234. Punton, C. W. Development of integrated crash helmet and helmet sizing techniques. Progress Report Nr 2, Contract NOAS-53-420C, Mine Safety Appliances Company, Pittsburgh, Pa., August 1953.

Development of integrated crash helmet and helmet sizing techniques.

235. Punton, C. W. Development of integrated crash helmet and helmet sizing techniques (NOFORN). Mine Safety Appliances Company, Pittsburgh, Pa., November 1953.

236. Quartermaster Board. Test of clips for linear, helmet, M1. Project Nr T-20, Department of the Army, Camp Lee, Va.
237. Quartermaster Board. Final report of test clips for liner, helmet, M1. Project Nr T-20 (supplement). Department of the Army, Ft. Lee, Va., 16 March 1943.
238. Quartermaster Board. Final report of test of sheepskin headbands, M1. Project Nr T-106, Department of the Army, Ft. Lee, Va., 17 April 1943.
239. Quartermaster Board. Markings, rank, for helmets and helmet liners. Project Nr QMBT 401, Department of the Army, Camp Lee, Va., 13 December 1944.
240. Quartermaster Board. Report of test of neckband for liner, helmet, M1. Project Nr T-385, Report Nr T-1483, Department of the Army, Ft. Lee, Va., 29 December 1944.
241. Quartermaster Board. Test of helmet, EX 49-1. Report Nr QMBT 806, Department of the Army, Camp Lee, Va., 31 October 1949.
242. Quartermaster Corps. Consolidated research and development annual project report. Reports Control Symbol CSCRD-1, Vol. 1, 1 January - 31 December 1956. Department of the Army, Washington, D. C.
243. Quartermaster Corps. Consolidated research and development annual project report. Reports Control Symbol CSCRD-1, Vol. 1, 1 January - 31 December 1959. Department of the Army, Washington, D. C.
244. Quartermaster Research & Development Command. Technical progress report 1 January - 31 December 1954. Natick, Mass.
245. Quartermaster Research & Development Command. Classified supplement to technical progress report 1 January - 31 December 1954. Natick, Mass.
246. Quartermaster Research & Development Command. Classified supplement to technical progress report 1 January - 31 December 1955. Natick, Mass.
247. Quartermaster Research & Development Field Evaluation Agency. Armor, torso: Helmet, combat. FEA 54039, Ft. Lee, Va., 18 August 1954.
248. Quartermaster Research & Development Field Evaluation Agency. Liner helmet steel T-54-1, helmet combat T-54-1, combat vehicle crewmans T-54-3. FEA 55045, Ft. Lee, Va., 28 February 1956.
249. Quartermaster Research & Development Laboratory. All-purpose helmet, Project Nr 2107, Ft. Benning, Ga., 7 March 1948.
250. Quartermaster Section. India-Burma theater enemy equipment intelligence service, Japanese helmets. Report Nr 32, Department of the Army, Washington, D. C., 13 May 1945.

251. Ramsey, R. C. Status report Nr 8, 15 November - 15 December 1964. Electro-Voice Inc., Buchanan, Mich., December 1964.
252. Randall, F. E., Damon, A., Benton, R. S., & Patt, D. I. Human body size in military aircraft and personal equipment. AAF Technical Report Nr 5501, AAF Air Material Command, Dayton, Ohio, 10 June 1946.
253. Randall, R. B. The effect of the helmet form on vision and hearing. National Research Council, Committee on Helmets, 13-14 September 1971, Washington, D. C.
254. Reid, A. M., & Elwood, M. A. A comparative physiological trial of a new issue helmet liner of the British steel helmet Mk IV. Clothing and Stores Experimental Establishment, Great Britain, August 1956.
255. Reneau, M. B., & West, R. E. Service test of headset-microphone kit Mk-1039/G for combat vehicle crewman's helmet, T56-6: Final report. Project USATECOM 1-5, Army Arctic Test Center, Ft. Greely, Alaska, April 1968.
256. Restarski, J. S., & Schelenyak, M. C. A visor for the standard M-1 helmet to prevent injuries to the face. Project Nr X227, Report Nr 1, Naval Medical Research Institute, Bethesda, Md., 19 June 1944.
257. Robinson, R. C., Jr., Boyd, D. M., & McDowell, E. C. Medical workloads from fragmentation munitions, 1969-1974 Vol. I (U). Final Report Nr RAC-R-65-VOL-1, Research Analysis Corporation, McLean, Va., October 1969. (Secret report)
258. Robinson, R. C., Jr., & McDowell, E. C. Medical workloads from fragmentation munitions, 1969-1974, Vol. II. The Pharac(F) user manual. Report Nr RAC-R-65-VOL-2, Contract Nr DA 44-188-ARO-1, DAHC19-69-C-0017, Research Analysis Corporation, McLean, Va., July 1969.

Report RAC-R-65 describes the research undertaken in the development of a simulation, and its use in estimating medical workloads resulting from attacks with fragmentation munitions, including opfrag. The workloads are obtained in terms of the number of outpatients and the number of hospitalized patients, and the time-phasing of the need for hospitalization (until recovery or death). The number killed in action and the number of noncasualties are also determined. Estimates of initial surgical treatment requirements in hours, are provided. The model developed, named the Pharac(F) Simulation, can be run on both the IBM 7040/44 and IBM 7090/94 computer systems to provide estimates from fragmentation attacks in scenarios for which input data can be adequately specified. Mathematically it is a four-dimensional space model that considers the interaction of individual fragments with air, vegetation, helmets, armor and body tissues. It is a stochastic simulation, and statistical analyses are automatically provided.

259. Rudnick, A., Beatty, G. H., & Maringer, R. E. Development of a new acceptance criterion for M1 helmets. Phase I. Analysis of data and development of inspection plan. Technical Report 8 May - 18 October 1968, Battelle Memorial Institute, Columbus Laboratories, Columbus, Ohio.

A strong, linear relationship between the ballistic limit (the current inspection parameter) and thickness was found. This relationship serves as the justification for the recommended change in inspection procedure. An inspection by attributes plan is recommended for use with the thickness inspection.

260. Sahagian, S., & Turner, E. Ballistic performance of combinations of armor for helmets (U). Victory Plastics Company, Hudson, Mass., October 1955. (Confidential report)
261. Scherrer, V. E., & George, T. W. NRL Report October 1948 (U). P. 25, Naval Research Laboratory, Washington, D. C. (Confidential report)
262. Schladermundt (Peter) Associates. Design, develop and produce functional production models of head-wound protector mask. New York, N. Y.
263. Skvaril, W. J. ERDL patterned camouflaged lightweight utilities and ERDL patterned camouflaged helmet covers: Final report. Marine Corps Landing Force Development Center, Quantico, Va., February 1967.

An immediate requirement exists for a camouflaged utility uniform with matching helmet cover for marines in RVN. The ERDL patterned camouflaged tropical utilities and helmet cover in the configuration of the latest test items are suitable for Marine Corps use in RVN with certain minor modifications. A requirement exists for a distinctive field utility uniform. To include a matching helmet cover for Marine Corps use world-wide, the ERDL pattern is the best and most suitable camouflage presently available. Further field testing of the ERDL patterned tropical utility uniform and helmet cover is not considered to be warranted or necessary in view of the minor modifications recommended for incorporation in the latest test item. Camouflaged patterned field uniforms offer an added degree of concealment over the solid state OG-107, making enemy target acquisition more difficult. The camouflaged uniform is a troop prestige item and would do much to enhance esprit-de-corps.

264. Smith, M. D. Transient deformation and residual energy characteristics of M-1 and EX 51-1 helmets at 0 degrees, 45 degrees, 60 degrees angles of obliquity (U). Report Nr 710 1043 1TR710 1043 10G 900 D 2, Water Pollution Research Board, Watford, England, June 1955. (Confidential report)
265. Smith, M. D. Instrumentation development for helmet deformation investigation (U). Report Nr 710 1043 OG 900 D 1, Water Pollution Research Board, Watford, England, October 1954. (Confidential report)
266. Sperrazza, J. Probabilities of incapacitation of helmeted troops by a heavy steel fragment (U). Technical Note, Report Nr BRL-TN-1235, Project Nr DA 5803-04-010, Ballistic Research Laboratories, Aberdeen Proving Ground, Md., December 1958. (Confidential report)
267. Steel. New combat helmets. Vol. III, No. 14, pp. 122-123, 1942.
268. Steele, W. M. Helmet, T21E1: Test report. Project Nr 503, Marine Corps Equipment Board, Quantico, Va., 31 May 1946.
269. Sterne, T. E. The probability of incapacitation by a steel sphere or by darts when portions of the body are rendered invulnerable (U). Memorandum Report Nr BRL-MR-960, Project Nr DA 5803-04-002, Ballistic Research Laboratories, Aberdeen Proving Ground, Md., February 1956. (Confidential report)
270. Sterne, T. E. Probabilities of incapacitation of helmeted troops by a steel sphere (U). Memorandum Report Nr BRL-MR-1010, Project Nr DA 5803-04-002, Ballistic Research Laboratories, Aberdeen Proving Ground, Md., June 1956. (Confidential report)

271. Stewart, G. M., & Deutsch, E. L. Determination of transient deformation and secondary missile characteristics of nylon liner T54-1 and combat vehicle crewman helmet T56-5 (U). Report Nr 2181, Army Chemical Warfare Laboratories, Army Chemical Center, Md., September 1957. (Confidential report)
272. Stone, J. T. O&TE of dual visor assembly TAC-TR-70A-123F, July 1971: Final report. Tactical Fighter Weapons Center (TAC), Nellis AFB, Nev.
273. Stuart, W. A. US Army protective headgear analysis of design. Contract Nr DA 44-109-qm-1821, Arens (EGMONT) Industrial Design, N. Y., March 1956.
274. Studler, R. R. The new combat helmet. Development of a superior head armor for the US soldier. Army Ordnance, 1942, Vol. 22.
275. Sturdivan, L. M., Bruchey, W., Jr., & Whitmire, R. A preliminary frequency analysis of WDMET Data-I (U). Memorandum Report Nr BRL-MR-1992, Project Nr RDT/E-1-T-062110-A-027, Ballistic Research Laboratories, Aberdeen Proving Ground, Md., July 1969. (Confidential report)

A method is presented for handling data from the Wound Data and Munitions Effectiveness Team (Vietnam). The method, which is applied to the first 930 cases covered by WDMET, consists of compiling by high-speed digital computer, the rate of occurrence of the factors contained in the data collection format as well as two- and three-way correlates of these factors (U).

276. Sullivan, J. F. Comparative resistance of various components of experimental helmet T21E1. Report Nr WAL 710/788, Watertown Arsenal Laboratory, Watertown, Mass., 29 November 1945.
277. Sunshine I., Campana, H. A., & Smith, H. T., Jr. Head trauma: Analysis of 120 casualties in Vietnam from July 1967 to January 1968. Technical Report Nr EA-TR-4359, Edgewood Arsenal, Md., March 1970.

To assist in the development of models for the study of head injury, 120 consecutive case histories of men who sustained head wounds were selected for analysis from the files of the Wound Data and Munitions Effectiveness Team (WDMET) at Edgewood Arsenal. The sample consists of 60 men who died and 60 who survived. These casualties were incurred by combat units of the US Army in Vietnam during the period of July 1967 to January 1968. It was concluded that when the brain is penetrated by a missile in combat, the prognosis is poor. Only 31% of our sample with penetrating injuries (32 cases) survived this type of injury. The prognosis of multiple lobe injuries is very poor. In our sample of fatalities, 21 of 60 men (35%) sustained this type of injury. This was the largest category of injuries to the central nervous system in the fatalities. Frontal lobe damage was observed in 50% of the survivors with open head wounds. This corresponds with reports in the literature regarding the relatively less severe prognosis of frontal lobe injury. Conversely, injuries of the parietal area accounted for the largest number of deaths in single lobe injuries. The data suggest that the helmet offers more protection against fragments than against bullets and may retard a bullet sufficiently to convert a potentially perforating wound into a penetrating one.

278. Sunshine, I., Campana, H. P., & Smith, H. T., Jr. Analysis of 210 US Army deaths in Vietnam from July-September 1967. Edgewood Arsenal Technical Report Nr 4357, WDMET, Edgewood Arsenal, Md., March 1970.
279. Sunshine, I. Missile wounds of the abdomen: Analysis of 135 US Army casualties in Vietnam. Edgewood Arsenal Technical Report Nr 4374, WDMET, Edgewood Arsenal, Md., March 1970.
280. Sunshine, I. Thoracic trauma: Analysis of 140 US Army casualties in Vietnam July-September 1967. Edgewood Arsenal Technical Report Nr 4358, WDMET, Edgewood Arsenal, Md., March 1970.
281. Sunshine, I. Injuries of extremities in 369 US Army and Marine Corps casualties in Vietnam. Edgewood Arsenal Technical Report Nr 4402, WDMET, Edgewood Arsenal, Md., April 1970.
282. Sunshine, I. Craniocerebral trauma in Vietnam. Edgewood Arsenal Technical Report Nr 4412, WDMET, Edgewood Arsenal, Md., July 1970.
283. Sunshine, I. Intrathoracic combat wounds. Edgewood Arsenal Technical Report Nr 4422, EDMET, Edgewood Arsenal, Md., August 1970.
284. Sunshine, I. Analysis of 500 US Army combat fatalities in Vietnam, July 1967 - November 1963. Edgewood Arsenal Technical Report Nr 4432, WDMET, Edgewood Arsenal, Md., September 1970.
285. Sunshine, I. Combat wounds of abdominal organs. Edgewood Arsenal Technical Report Nr 4447, WDMET, Edgewood Arsenal, Md., September 1970.
286. Sydenham, H. G. Steel helmets. Report Nr 1186. Infantry Board, Ft. Benning, Ga., January 29, 1941.
287. Sydenham, H. G. TS-3 helmet: Report of tests. Report Nr 1211, Infantry Board, Ft. Benning, Ga., April 29, 1941.
288. Sydenham, H. G. Improved steel helmet TS-3 and liners. Report Nr 1221, Infantry Board, Ft. Benning, Ga., June 3, 1941.
289. Tactical Fighter Weapons Center. OT/E of custom-fit liners and modified HGU-17/P liners. Nellis AFB, Nev., April 1968.
290. Tactical Air Warfare Center. Exploratory test, polycarbonate visor. TAWC-Test-69-2B, Elgin AFB, Fla., December 1969.

291. Tannenholtz, S. D. Research on acoustical problems of the military: A review and future aspect. Technical Report, Army Natick Laboratories, Pioneering Research Laboratory, Natick, Mass., October 1968.

A review has been made of the literature in the area of acoustics, vibration, shock, and blast phenomena related to effects on the physiological system and attenuation effects of materials and devices. In addition, information from sources other than the literature pertinent to an evaluation of the significance of acoustic hazards in the military environment, is also presented. Damage-risk and standards criteria are presented, and further studies are suggested to advance the state-of-the-art in acoustic hazards protection as well as to exploit the potentials of acoustic phenomena for the investigation of material properties.

292. Thompson, Ramo-Woolridge, Inc. Deep drawing of titanium alloy helmet shell 6A1-4U. Contract Nr DA 19-129-qm-1430, Project Nr 7-80-05-001.
293. Thrasher, G. D., & Neely, K. K. Acoustic properties of headgear (U): VI (R). Report Nr 100 7, Defence Research Medical Laboratories, Toronto, Ontario, August 1959. (Confidential report)
294. Thrasher, G. D., & Neely, K. K. Acoustic properties of headgear: X. RCAF prototype helmet-earmuff devices (U). Report Nr TM100 11, Defence Research Medical Laboratories, Toronto, Ontario, August 1960. (Confidential report)
295. Tolson, J. A note concerning impact tests carried out on a fibre glass helmet. Report Nr TM10, Clothing and Stores Experimental Establishment, Great Britain, November 1952.
296. Tropf, W. J., Jr. An analysis of the relative economic breakeven points for infantry helmets of new design (U). Technical Report Nr TR-69-18, Army Materiel Command, Systems and Cost Analysis Division, Washington, D. C., May 1969. (Confidential report)

This report provides a breakeven analysis in terms of costs and benefits of helmets of new design. For the purposes of this analysis these helmets are of two categories. On one hand, those helmets which provide improvements to physiological factors through a decrease in weight and an improvement in configuration, and on the other, the helmets which provide increased protection. The report will address the cost and benefits of the new helmet designs, the resulting breakeven points, and the conclusions derived (U).

297. Uminski, E. A. Thermolibrium headgear assembly. Phase I. Conceptual design study and fabrication of a representative mockup. Phase II. Design study and fabrication of functional and non-functional prototypes. Contract Nr DA 19-129-qm-2045, Mine Safety Appliances Company, Research & Engineering Division, Pittsburgh, Pa., January 1965.
298. Underwood, E. K. Acoustic properties of headgear: XVIII. Safety Supply Company, Fibre glass safety helmet type 291000; leather earmuff helmet; and earmuff type 258 C/W EM7/8(MOD). headframe assembly (U). Report Nr TM551, Defence Research Medical Laboratories, Toronto, Ontario, April 1964. (Confidential report)
299. Underwood, E. K., & Demmery, W. W. Acoustic properties of headgear: XVI. Safety Supply Company, Types 255 and 258 earmuffs, David Clark Company, Straightway type SPHS ear protector helmet, and the Ambco Electronics auraldome headset (U). Project Nr PCC D50 89 01 01, Defence Research Medical Laboratories, Toronto, Ontario, April 1963. (Confidential report)

300. Underwood, E. K., De La Riviere, W. D., & Neely, K. K. Acoustic properties of headgear: XIX. General Textile Mills Type APH-6A helmet; American Optical 'hear-guard' types 1200 and 1275 hearing protectors; Parmalee Ltd. 'straightway' Model X-5516 ear protector; and Safety Supply Company type 258 earmuff C/W EM-9(SF) foam-filled ear seals (U). Technical Memo Report Nr TM-DRML-592, Defence Research Medical Laboratories, Toronto, Ontario, May 1965. (Confidential report)
301. Underwood, E. K., & Neely, K. K. Acoustic properties of headgear: XVII. Sharpe Instruments Company Type ED/ROF earmuffs; Safety Supply Company Type 255 earmuff with EM-9 ear seals; Cold Lake groundcrew protective helmet; and Roanwell Corporation headset models H-157/AC and R-425 (U). Report Nr TM526, Project Nr D50-89-01-01, Defence Research Medical Laboratories, Toronto, Ontario, March 1964. (Confidential report)
302. U. S. Army Aberdeen Proving Ground. Test of steel helmets. Helmets submitted by the McCord Radiator and Manufacturing Company. APG-OP-4889-9, Aberdeen Proving Ground, Md., May 1941.
303. U. S. Army Aberdeen Proving Ground. First report on plastic helmets manufactured by Mr. Geoffrey Gwyther and Mr. W. S. McDuffee. Aberdeen Proving Ground, Md., 10 February 1941.
304. U. S. Army Aberdeen Proving Ground. Test of steel helmets, hinged chin strap loops for steel helmet, M1. APG-OP-4889-10, Aberdeen Proving Ground, Md., October 1943.
305. U. S. Army Armor Board. Test of RCA quiet ear kit for combat vehicle crewman helmet, T56-6. Headquarters, U. S. Army Continental Army Command, Ft. Monroe, Va., May 1959.
306. U. S. Army Chemical Warfare Board. Test of crash liner for M1 helmet. Project Nr 687, Edgewood Arsenal, Md., 8 June 1945.
307. U. S. Army Chemical Warfare Laboratories. Symposium on wound ballistics of body armor (U). Conducted by U. S. Army Chemical Warfare Laboratories, 19 and 20 August 1958 (U). Report Nr SP2-26, Army Chemical Center, Md., February 1960. (Confidential report)
308. U. S. Army Chemical Warfare Laboratories. Wound ballistics annual progress report January-June 1958 (U). Chemical Warfare Technical Report Nr 2289, Army Chemical Center, Md., July 1959. (Secret report)
309. U. S. Army Combat Developments Command. Trip report - 25th Infantry Division, 3 and 9 (U). Army Combat Developments Command, San Francisco, Calif., February 1968. (Confidential report)

A visit was made to the 25th Infantry Division and 12th Evacuation Hospital to gather information concerning steel helmets, 81mm mortars, beehive ammunition, tank and APC resistance to damage and possible danger from nylon boots in vehicular fires (U).

310. U. S. Army Combat Developments Command. Trip report - 4th Infantry Division 10-12 February 1968 (U). Army Combat Developments Command, Liaison Detachment, San Francisco, Calif. (Confidential report)

311. U. S. Army Combat Developments Command. Trip report - 9th Infantry Division (U). Army Combat Developments Command, Liaison Detachment, San Francisco, Calif., February 1968. (Confidential report)

On 14 February 1968 the 9th Infantry Division was visited to discuss light weight helmets, damage to tanks and M113's by mines and RPG rounds, and use of beehive ammunition in the jungle (U).

312. U. S. Army Combat Developments Command. Trip report - 1st Infantry Division 18 February 1968 (U). Army Combat Developments Command, Liaison Detachment, San Francisco, Calif. (Confidential report)

Elements of the 1st Infantry Division were visited to discuss troop acceptance of a new helmet. The damage inflicted on tanks and APC's exposed to RPG's and mines, and their ability to continue the flight, use of flechette rounds, and 81mm mortar rounds (U).

313. U. S. Army Combat Developments Command. Operational report - lessons learned (U). Quarterly report, Army Combat Developments Command, Ft. Belvoir, Va., May 1969. (Confidential report)

314. U. S. Army Continental Command. Service test of covers, helmet, camouflage, Continental Army Command Board 3, Ft. Benning, Ga., 5 August 1955.

315. U. S. Army Engineering Research & Development Laboratories. Symposium on materials and design for light-weight construction. The titanium seminar, 6 August 1952, Ft. Belvoir, Va.

316. U. S. Army Field Forces Board No. 3. Minutes of conference on body armor. Ft. Benning, Ga., 1 July 1948.

317. U. S. Army Field Forces Board No. 3. Liner, helmet, M1 (textured coating) and lined helmet M1 (jungle camouflaged). Report Nr 1469, Ft. Benning, Ga., 8 April 1943.

318. U. S. Army Field Forces Board No. 3. Evaluation of helmet assembly, EX 49-3. Report Nr 2294, Ft. Benning, Ga., April 1950.

319. U. S. Army Field Forces Board No. 3. Service test of helmet EX 51-1. Project Nr 2428, Ft. Benning, Ga., 3 October 1952.

320. U. S. Army Field Forces Board No. 3. Service test of covers, helmet camouflage. Project Nr 2687, Ft. Benning, Ga., August 1955.

321. U. S. Army Field Forces Board No. 3. Service test of liner, helmet, soldiers, steel T55-2. Report Nr 2740, Ft. Benning, Ga., 25 March 1958.

322. U. S. Army Field Forces Board No. 3. Service test of cover, helmet, camouflage. Report Nr 2815, Ft. Benning, Ga., December 1959.

323. U. S. Army Foreign Science & Technology Center. Steel helmet for airborne troops. Report Nr FSTC381T64, Army Foreign Science & Technology Center, Washington, D. C., December 1964.

Translation of instructions for the manufacture of the steel helmet with interior fittings for airborne troops.

324. U. S. Army Human Engineering Laboratories. USAMC five-year personnel armor system technical plan working committee meeting no. 3, 15-16 December. Aberdeen Proving Ground, Md.
325. U. S. Army Infantry Board. Final report of confirmatory test (Type II) of helmet liner insulation. USAID Project Nr 3027, Ft. Benning, Ga., 21 May 1964.
326. U. S. Army Infantry Board. Product improvement test of suspension system for M1 helmet. USAIB Project Nr 3327, final report by Major Robert W. Browning, Ft. Benning, Ga., March 1971.
327. U. S. Army Materiel Command. Helmet conference, minutes of, 16 May 1968 (U). Washington, D. C. (Confidential report)
328. U. S. Army Materiel Command. Technical information report 33.1.2.2 (U). Prepared by University of Pittsburgh, Research Staff, Washington, D. C., January 1968. (Secret report)
329. U. S. Army Materiel Command. Subject index of technical information reports published August 1967-January 1968. University of Pittsburgh, Research Staff, Washington, D. C., February 1968. (NOFORN)
330. U. S. Army Materiel Command. Five-Year personnel armor system technical plan. Washington, D. C., November 1970.
331. U. S. Army Materiel Command. First year summary of progress and up-dated milestone schedule, USAMC five year personnel armor system technical plan. Washington, D. C., November 1971.
332. U. S. Army Materiel Command. Summary report no. 1 for the AMC senior steering committee on body armor and helmets, Washington, D. C.
333. U. S. Army Materiel Command. Minutes of 1st AMC working committee meeting, Washington, D. C., 21 April 1971.
334. U. S. Army Materiel Command. Minutes of 2nd AMC working committee meeting. Washington, D. C., 3, 4 August 1971.
335. U. S. Army Materiel Command. Minutes of meeting of AMC senior steering committee on body armor and helmets. Washington, D. C., 17 September 1971.
336. U. S. Army Materiel Command. Minutes of fourth meeting of AMC working committee. Washington, D. C., 8, 9, 10 February 1972.

337. U. S. Army Materiel Command. Minutes of working committee meeting No. 3. Washington, D. C., 15, 16 December 1971.
338. U. S. Army Materiel Command. Materials for personnel armor second quarterly report first quarter FY 72. Summary prepared by Army Materials & Mechanics Research Center. Washington, D. C., 20 October 1971.
339. U. S. Army Medical Research Laboratory. Study of head protection for tank crews. Ft. Knox, Ky., 13 June 1945.
340. U. S. Army Medical Research Laboratory. Attenuation characteristics of four ear protective devices. Report Nr 322, Ft. Knox, Ky., January 1958.
341. U. S. Army Natick Laboratories. Body armor and helmet program. (Letter) Natick, Mass., 3 September 1970.
342. U. S. Army Natick Laboratories. NLABS report on armor materials research (U). Natick, Mass., April 1964. (Confidential report)
343. U. S. Army Natick Laboratories. RDT&E annual project report. RCS CSCRD-1 (R-3), Vol. VII, Part B, Section 1. Natick, Mass., 1 January 1964.
344. U. S. Army Natick Laboratories. RDT&E annual project report. RCS CSCRD-1 (R-3), Vol. VII, Part B, Section 2. Natick, Mass., 1 January 1964.
345. U. S. Army Natick Laboratories. RDT&E annual project report. RCS CSCRD-1 (R-3), Vol. VII, Part B, Section 3. Natick, Mass., 1 January 1964.
346. U. S. Army Natick Laboratories. RDT&E engineering development program quarterly status reports. FY 65. Natick, Mass.
347. U. S. Army Natick Laboratories. RDT&E engineering development program quarterly status reports. FY 66. Natick, Mass.
348. U. S. Army Natick Laboratories. RDT&E engineering development program quarterly status reports. (RCS-XREC-8-P), Vol. II, FY 67. Natick, Mass.
349. U. S. Army Natick Laboratories. RDT&E engineering development program quarterly status reports. (RCS-XREC-8-P), Vol. II, FY 68. Natick, Mass.
350. U. S. Army Natick Laboratories. RDT&E engineering development program quarterly status reports. (RCS-XREC-8-P), Vol. II, FY 69. Natick, Mass.
351. U. S. Army Natick Laboratories. RDT&E engineering development program quarterly status reports. (RCS-XREC-8-P), Vol. II, FY 70. Natick, Mass.
352. U. S. Army Natick Laboratories. Fibrous materials for personnel armor (U). Natick, Mass., March 1972.
353. U. S. Army Quartermaster Research & Engineering Command. Summary of Army personnel armor conference, 8-10 October 1958. Natick, Mass., January 1959.

354. U. S. Army Quartermaster Research & Engineering Command. Personnel armor symposium first annual meeting held 7-9 June 1960 (U). Natick, Mass., December 1960. (Confidential report)
355. U. S. Army Quartermaster Research & Engineering Command. The effect of shot peening on the ballistic characteristics of the M1 helmet. Tech Rpt Nr ME-1, Natick, Mass., July 1962.
356. U. S. Army Test & Evaluation Command. Arctic environmental test of body armor and helmets. Final report on materiel test procedure No. MTP-10-4-009, Aberdeen Proving Ground, Md., November 1969.

The report describes test methods and techniques for evaluating the performance and characteristics of body armor and helmets under arctic winter environmental conditions, relative to the requirements expressed in qualitative materiel requirements, small development requirements, or other applicable documentation containing design requirements. The end objective of testing is to ascertain whether the test item is suitable for military service use under arctic winter environmental conditions.

357. U. S. Army Test & Evaluation Command. Helmets, combat vehicle crewmans. MTP-10-3-206, Aberdeen Proving Ground, Md., May 1970.
358. U. S. Naval Air Engineering Center. SPH-2 helmet, ventilation investigation. NAEC-ACEL-521, Philadelphia, Pa., September 1964.
359. Victory Plastics Company. Ballistic performance of combinations of armor for helmets. Contract DA 19-020-ORD-2422, WAL No. 710/1055-10, Project TB4-10, Hudson, Mass.
360. Victory Plastics Company. Development of improved ballistic materials for various armor structures and helmets. Final report. Contract DA 19-129-QM-540, Hudson, Mass., September 1957. (Confidential report)
361. Victory Plastics Company. Ballistic performance of 6 percent AL - 4 percent V titanium alloy in combination with bonded nylon (U). Report No. TR 710-1025-14, Contract DA 29-020-ORD-3638, Hudson, Mass., August 1958. (Confidential report)
362. Victory Plastics Company. Development of reinforced plastics and structures, development of body armor, helmet and armored clothing. Hudson, Mass., May 1959.
363. Victory Plastics Company. Development of improved reinforced plastics and structures. Contract DA 19-129-QM-849, Hudson, Mass., September 1960.
364. Victory Plastics Company. Development of plastic materials and personnel armor structures. Report No. 6, Contract DA 19-129-QM-1482, Project 7-80-05-001; 7-93-30-001, Hudson, Mass.
365. Victory Plastics Company. Development of improved reinforced plastics and structures. Development of plastic materials and personnel armor structures. Final report, Project Nos. 7-93-30-001, 7-80-05-001, Contract No. DA-19-129-QM-1482, Headquarters, R&E Command, QM R&E Center, U. S. Army Natick Laboratories, Natick, Mass.

366. Waldon, D. J., Kokinakis, W., & Sperazza, J. On the protection offered by infantry helmets. Technical Report No. AMSAA-TR-1, Army Materiel Systems Analysis Agency, Aberdeen Proving Ground, Md., July 1968.
367. Waldon, D. J., Dalton, R. E., Kokinakis, W., & Johnson, W. P. A parametric analysis of body armor for ground troops. ARDC TR 2, Aberdeen Proving Ground, Md., September 1969. (Secret report)
368. Ward, G. B. Personnel fragmentation equipment. Technical Information Division, Library of Congress, Washington, D. C., July 1955.
369. Watertown Arsenal. Development of projectiles for testing body armor to simulate flak and 20mm HE fragments. Report WAL 762/247, Watertown, N. Y., 17 December 1943.
370. Watertown Arsenal. Development of projectiles to be used in testing body armor to simulate fragments of a 20mm HE projectile. Report WAL 762/247, Watertown, N. Y., 7 January 1944.
371. Watertown Arsenal. Resume of progress of development of body armor undertaken at Watertown Arsenal during World War II. Report WAL 710/747, Watertown, N. Y., 30 October 1945.
372. Watertown Arsenal. Criteria for the design of canister ammunition (U). Report WAL 763/887(C), Watertown, N. Y., July 1955. (Confidential report)
373. Watertown Arsenal. Evaluation of fragment-resistant armor materials (U). Report WAL 710/930(C), 23 December 1955; WAL 710/930-7A(C) - Addendum 1, Fragment resistant characteristics of 6A1-4V titanium alloy armor and comparison with other fragment-resistant armor materials, 3 May 1956. Watertown, N. Y.
374. Werkowski, S. J., & Smith, R. S. The application of the poisson distribution in the simulation of attack by fragmentation munitions on infantry helmets. Technical Report USA-NLABS-TR-70-66-OA/EO, Contract M00027-69-C-0139, Natick, Mass., June 1970.

This report concerns the application of the poisson distribution as a mathematical model in the simulation of fragment perforation of infantry helmets to assess the effectiveness of these helmets which were fabricated from different materials. The basic data were developed through sequential firings of fragmentation munitions to obtain fragment density and perforation data on several types of infantry helmets. Live munitions were utilized to simulate actual fragmentation attacks under combat conditions. The poisson mathematical model was employed to predict the probability of helmet failure. A comparison between the actual and the estimated results verified that the testing conducted was reliable.

375. Wilcox, C. S. Engineering test of headset-microphone kit MK-1039/G for combat vehicle crewman's (CVC) helmet T56-6. Final report, Army Electronics Proving Ground, Ft. Huachuca, Ariz., March 1968.
376. Williams, R. B., & Lilly, C. Retardation of the 225-grain steel cube by clothing and goat tissue (U). Report No. 398P40 S 60, Army Chemical Warfare Laboratories, Army Chemical Center, Edgewood, Md., May 1960. (Secret report)
377. Wright, W. C. Recommendations to establish standardized casualty reduction analyses reporting (U). Natick, Mass., December 1971. (Confidential report)

378. Yustein, S. E., & Winans, R. R. Report of investigation of ventilation holes in protective hats. Final report 4526-18-FR, New York Naval Shipyard, Brooklyn Materiel Laboratory, N. Y., October 1951.

On the basis of the various data obtained in the course of the reported investigation, it appears that on the whole, the samples of protective hats tested as reported were not seriously affected by ventilation holes drilled in the samples as described. The following instructions that might be issued to field activities regarding the proper location of ventilation holes are recommended. Ventilation holes may be drilled in a protective hat or cap if desired, under the supervision of a shop supervisor of tools. These holes shall not, under any circumstances exceed a total of 8 in number. Four (4) spaced 2 inches apart in a horizontal row on each side of the hat and uniformly centered. These holes shall not be more than $\frac{1}{4}$ inch in diameter. In the case of the brimless cap, the horizontal row shall be 2 inches above the edge; in the case of the full brim hat, the horizontal row shall be 2 inches above the inner edge of the brim.

379. Zampieri, R. P. Tropic service test of radio set AN/PRT-4 and AN/PRR-9. Final report, June 1966 - June 1967. Army Tropic Test Center, Fort Clayton, Canal Zone, January 1968.
380. Zeigen, R. S., Alexander, M., & Churchill, E. A head circumference sizing system for helmet design, including three-dimensional presentations of anthropometric data. WADC Technical Report No. 60-631, Contract AF33-616-6792, Antioch College, Yellow Springs, Ohio, December 1960.

A system for the sizing and design of rigid and semi-rigid helmets based on a single key dimension. Head circumference is described. Anthropometric data largely obtained in the 1950 survey of Air Force flying personnel were analyzed. This report includes an account of the historical development of sizing systems, programs, and resultant headforms in the Air Force: A detailed statement concerning the design rationale and statistical concepts used: Comprehensive tables needed by the designer for all sizing programs discussed: A statement as to sculpturing techniques and problems: and a comment on preliminary validation results and on the over-all design materiel-sizing concept. Appendices include a glossary of significant terms, descriptions of selected head and face dimensions. A detailed discussion of statistical concepts and formulae referred to in the report and tables of comparative four and six-size programs based on the key dimensions head length, head breadth.

DISTRIBUTION LIST

HQ DA (DARD-ARB)
Wash DC 20310

HQ DA (DACS-ZC-W-TIS)
Wash DC 20310

HQ DA (DAPE-HRS)
Wash DC 20310

Commander
U. S. Army Materiel Command
ATTN: AMCDL (Ofc of Deputy for Labs)
Washington, DC 20315

Commander
U. S. Army Materiel Command
ATTN: AMCRD-G
Washington, DC 20315

Commander
U. S. Army Materiel Command
ATTN: AMCRD (Air Def & Msl Ofc)
Washington, DC 20315

Commander
U. S. Army Materiel Command
ATTN: AMCRD (Air Mobility Ofc)
Washington, DC 20315

Commander
U. S. Army Materiel Command
ATTN: AMCRD (Comm-Elec Ofc)
Washington, DC 20315

Commander
U. S. Army Materiel Command
ATTN: AMCRD (Weapons Ofc)
Washington, DC 20315

Commander
U. S. Army Materiel Command
ATTN: AMCRD (Dr. Kaufman)
Washington, DC 20315

Commander
U. S. Army Materiel Command
ATTN: AMCRD (Mr. Crellin)
Washington, DC 20315

Headquarters
USA Medical R&D Command
ATTN: Behavior Sciences Rsch Br.
Main Navy Building
Washington, DC 20315

Commander
Harry Diamond Labs.
ATTN: AMXDO-EDC (B. I. Green, Br. 720)
Adelphi, MD 20783

Director
Walter Reed Army Institute of Research
Walter Reed Army Medical Center
ATTN: Neuropsychiatry Division
Washington, DC 20012

Army Audiology & Speech Center
Forest Glen Section
Walter Reed General Hospital
Washington, DC 20012

OAD/E&LS
ODDR&E, Pentagon, Rm 3D129
ATTN: MAJ Henry L. Taylor
Wash DC 20301

Commander (4)
US Army Institute for Behavior &
Social Sciences
1300 Wilson Blvd.
Arlington, VA 22209

Commander
US Army Combat Developments Command
ATTN: CDCCD-C
Fort Belvoir, VA 22060

Commander
US Army Combat Developments Command
ATTN: CDCMR
Fort Belvoir, VA 22060

Commander
US Army Combat Developments Command
ATTN: CDCRE
Fort Belvoir, VA 22060

Commander
US Army Combat Developments Command
ATTN: CDCCS-DS-Q
Fort Belvoir, VA 22060

Commander
US Army Mobility Equipment Research &
Development Center
ATTN: Human Factors Engr.
Fort Belvoir, VA 22060

Commander
Engr. Topographic Labs.
ATTN: Mr. Sidney Presser
Fort Belvoir, VA 22060

Commander
USCONARC
Fort Monroe, VA 23351

Commander
USCONARC
ATTN: ATIT-RD-RD
Fort Monroe, VA 23351

President
US Army Infantry Board
Fort Benning, GA 31905

Commander
US Army Materiel Command Infantry
Rsch & Dev Liaison Office
Fort Benning, GA 31905

U. S. Army Infantry School Library
Infantry Hall
Fort Benning, GA 31905

Commander
US Army Missile Command
ATTN: AMSMI-RBLD
Redstone Arsenal, AL 35809

Commander
US Army Missile Command
ATTN: AMSMI-RLH (Mr. Chaikin)
Redstone Arsenal, AL 35809

US Army Board for Aviation Accident
Research Laboratory
ATTN: Gail Bankston
Bldg. 5504
Fort Rucker, AL 36360

Director of Research
US Army Aviation HRU
ATTN: Librarian
P. O. Box 428
Fort Rucker, AL 36362

US Army Natick Laboratories
ATTN: Tech Library (AMXRE-STL)
Natick, MA 01760

US Army Natick Laboratories
Behavioral Sciences Division
ATTN: AMXRE-PRB
Natick, MA 01760

US Army Natick Laboratories
Behavioral Sciences Division
ATTN: AMXRE-PRBE
Natick, MA 01760

US Army Natick Laboratories
Behavioral Sciences Division
ATTN: AMXRE-PRBN
Natick, MA 01760

Headquarters
USA Rsch Inst. of Environmental Medicine
ATTN: MEDRI-CL (Dr. J. Kobrick)
Natick, MA 01762

Commander
US Army Electronics Command
ATTN: AMSEL-RD-GDA
Fort Monmouth, NJ 07703

Commander
US Army Electronics Command
ATTN: AMSEL-VL-E
Fort Monmouth, NJ 07703

Commander
Picatinny Arsenal
ATTN: SMUPA-VC1 (Mr. J. Carlock)
Dover, NJ 07801

Director
Military Psychology & Leadership
United States Military Academy
West Point, NY 10996

Commander
US Army Medical Equipment R&D Lab.
Fort Totten, Flushing, LI, NY 11359

Commander
Watervliet Arsenal
ATTN: SWEWV-RDT
Watervliet, NY 12189

Commander
Frankford Arsenal
ATTN: Library (C2500, Bldg 51-2)
Philadelphia, PA 19137

Commander
Frankford Arsenal
ATTN: SMUFA-N; 6400; 202-4 (HF)
Philadelphia, PA 19137

President
US Army Maintenance Board
ATTN: Adjutant
Fort Knox, KY 40121

Commander
US Army Medical Research Lab.
Fort Knox, KY 40121

US Army Armor Human Research Unit
ATTN: Library
Fort Knox, KY 40121

Commander
US Army Tank-Automotive Command
ATTN: AMSTA-RKAE
Warren, MI 48090

Commander (2)
US Army Tank-Automotive Command
ATTN: AMSTA-RHFL, Rsch Library
Warren, MI 48090

Commander
US Army Tank-Automotive Command
ATTN: AMSTA-R
Warren, MI 48090

Commander (2)
US Army Weapons Command
ATTN: SWERI-RDD-PD
Rock Island Arsenal, IL 61201

Commander
US Army Weapons Command
ATTN: AMSWE-RDT
Rock Island Arsenal, IL 61201

Commander
US Army Weapons Command
ATTN: AMSWE-SMM-P
Rock Island Arsenal, IL 61201

Director of Graduate Studies & Research
ATTN: Behavioral Sciences Representative
US Army Command & General Staff College
Fort Leavenworth, KS 66027

Commandant
US Army Artillery & Missile School
ATTN: USAAMS Tech Library
Fort Sill, OK 73503

Director of Research
HumRRO Div. No. 5 (Air Def)
P. O. Box 6021
Fort Bliss, TX 79916

Commander
Yuma Proving Ground
ATTN: Tech Library
Yuma, AZ 85364

Commander
Ft. Huachuca Spt Comd, US Army
ATTN: Tech References Div.
Fort Huachuca, AZ 85613

Commander
US Army Electronics Proving Ground
ATTN: Mr. J. Abraham, Test Dir.
Fort Huachuca, AZ 85613

Commander
ATTN: Tech Library
White Sands Missile Range, NM 88002

Commander
White Sands Missile Range
ATTN: STEWS-TE-Q (Mr. Courtney)
White Sands Missile Range, NM 88002

Human Factors Division
G-2/3, USACDCEC
Fort Ord, CA 93941

USACDC Experimentation Command
ATTN: Tech Library, Box 22
Fort Ord, CA 93941

Commander
USACDC Air Defense Agency
Fort Bliss, TX 79916

Commander
USACDC Armor Agency
Fort Knox, KY 40121

Commander
USACDC Artillery Agency
Fort Sill, OK 73503

Commander
USACDC Aviation Agency
Fort Rucker, AL 36360

Commander
USACDC CBR Agency
Fort McClellan, AL 36201

Commander
USACDC Combat Systems Group
Fort Leavenworth, KS 66027

Commander
USACDC Comm-Elec Agency
Fort Monmouth, NJ 07703

Commander
USACDC Engineer Agency
Fort Belvoir, VA 22060

Commander
USACDC Infantry Agency
ATTN: Central Files
Fort Benning, GA 31905

Commander
USACDC Inst. of Strategic & Stability
Operations
Fort Bragg, NC 28307

Commander
USACDC Intelligence & Control Sys Gp.
Fort Belvoir, VA 22060

Commander
USACDC Medical Service Agency
Fort Sam Houston, TX 78234

Commander
USACDC Personnel & Logistics Group
Fort Lee, VA 23801

Commander
USACDC Military Police Agency
Fort Gordon, GA 30905

Commander
USACDC Supply Agency
Fort Lee, VA 23801

Commander
US Army Arctic Test Center
ATTN: STEAC-IT
APO Seattle, WA 98733

Commander (2)
US Army Tropic Test Center
ATTN: Behavioral Scientist
P. O. Drawer 942
Fort Clayton, Canal Zone

USA Standardization Group, UK
ATTN: Rsch/Gen Materiel Rep.
Box 65
FPO New York 09510

Director
Biomedical Lab., APG-EA
ATTN: HF Gp. (SMUEA-BL-H)

Director
Biomedical Lab., APG-EA
ATTN: Psychology Sec. (SMUEA-BL-REP)

USAEHA, APG-EA
ATTN: Librarian, Bldg 2100 (2)

Director
Biomedical Lab., Clinical Investigation
APG-EA, Bldg 3101
ATTN: CPT Peterson

Technical Library, Bldg 305, APG-AA

CO, USACDCMA, Bldg 305, APG-AA

USATECOM, Bldg 314, APG-AA

USACDC Ln Ofc, Bldg 314, APG-AA

USMC Ln Ofc, Bldg 314, APG-AA

USN Submarine Medical Center
ATTN: Library
Box 600, USN Submarine Base, New London
Groton, CT 06340

Code 455
Office of Naval Research
Washington, DC 20360

Commander
USANLABS
Natick, MA 01760
AMXRE-CCE (Mr. W. Wright) 20

Dr. Burton G. Andreas
Department of Psychology
Suny at Brockport
Brockport, NY 14420

Dr. Alexis M. Anikeeff
Department of Psychology
University of Akron
Akron, OH 44304

Mr. A. J. Arnold
HF Engineer, Safety Group
GM Design Staff, GM Tech Center
Warren, MI 48090

Dr. Lloyd A. Avant
Dept. of Psychology
Iowa State University
Ames, IA 50010

Dr. Herbert J. Bauer
GM Rsch Labs., GM Tech Center
Warren, MI 48090

Dr. Corwin A. Bennett
Ind. Eng. Dept.
Kansas State University
Manhattan, KS 66502

Mr. Richard K. Brome
Govt Pub Sec., JFK Memorial Library
Calif. State College at Los Angeles
5151 State College Drive
Los Angeles, CA 90032

Dr. Bill R. Brown
Perf. Rsch. Lab.
University of Louisville
Louisville, KY 40208

Dr. Edwin Cohen
Link Group
General Precision Systems Inc.
Binghamton, NY 13902

Dr. Vicki Cohen
Dept. of Psychology
California State at Hayward
Hayward, CA 94542

Dr. Renwick E. Curry
Dept. of Aeronautics & Astronautics
School of Engineering, MIT
Cambridge, MA 02139

Dr. Anthony Debons
IDIS, University of Pittsburg
Pittsburgh, PA 15213

Mr. John A. Dinan
Raytheon Company
Missile Systems Division
S4-4
Hartwell Road
Bedford, MA 01730

Prof. Richard C. Dubes
Computer Science Dept.
Michigan State University
East Lansing, MI 48823

Mr. John H. Duddy
Dept. 62-40, Bldg. 151
Lockheed Missiles & Space Co.
P. O. Box 504
Sunnyvale, CA 94088

Dr. Richard A. Dudek, Dir.
Ctr. of Biotechnology & Human Perf.
Texas Tech University
Lubbock, TX 79409

Dr. Selby H. Evans
Inst. for the Study of Cognitive Sys.
Texas Christian University
Fort Worth, TX 76129

Dr. John L. Fletcher
Dept. of Psychology
Memphis State University
Memphis, TN 38111

Mr. Gerald J. Fox
Chief, Life Sciences
Grumman Aerospace Corp.
Bethpage, NY 11714

Mr. Henry E. Guttman
Tech Div 1642, Sandia Corp.
Albuquerque, NM 87115

Dr. Ralph Norman Haber
Ctr. for Visual Science
University of Rochester
Rochester, NY 14627

Dr. Robert J. Hall
Spec Proj Div, EG&G Inc.
P. O. Box 15110
Las Vegas, NV 89114

Dr. William Harris
Human Factors Rsch., Inc.
6780 Cortona Drive
Goleta, CA 93017

Dr. Sheldon F. Hendricks
Department of Psychology
University of Nebraska at Omaha
Omaha, NB 68102

Dr. Donald Henderson
Dept. of Otolaryngology
Upstate Medical Center
Adams Street
Syracuse, NY 13210

Dr. Arthur S. Kamlet
Bell Telephone Labs (1B-125)
Whippany Road
Whippany, NJ 07981

Dr. P. Robert Knaff
Rsch Ctr, Nat Highway Safety Inst.
US Dept. of Transportation
Washington, DC 20591

Dr. M. I. Kurke
Human Sciences Rsch Inc.
7710 Old Springhouse Road
McLean, VA 22101

Mr. Robert H. Lambert
EG&G Inc., Special Proj. Div.
P. O. Box 15110
Las Vegas, NV 89114

Dr. Michael Loeb
Department of Psychology
University of Louisville
Louisville, KY 40208

Dr. Robert R. Mackie
Human Factors Rsch Inc.
Santa Barbara Rsch Park
6780 Cortona Dr.
Goleta, CA 93017

Dr. Andrew A. Monjan
Johns Hopkins Univ.
Sch. of Hygiene & Public Health
Dept. of Epidemiology
615 N. Wolfe St.
Baltimore, MD 21205

Mr. James Moreland
Westinghouse Electric Corp.
R&D Center
Churchill Boro
Pittsburgh, PA 15235

Dr. Ben B. Morgan
Perf Rsch Lab.
University of Louisville
Louisville, KY 40208

Dr. Thomas I. Myers
Inst. for Rsch in Psychobiology
American Institutes for Research
8555 Sixteenth Street
Silver Spring, MD 20910

Mr. Edwin F. Neff
OCD Staff College, Federal Bldg.
Battle Creek, MI 49016

Dr. Robert Pachella
Human Performance Center
330 Packard Road
Ann Arbor, MI 48104

Dr. Richard G. Pearson
Dept. of Ind. Eng., Box 5518
North Carolina State University
Raleigh, NC 27607

Dr. Lawrence C. Perlmuter
Psychology Department
Virginia Polytechnic Institute & State U.
Blacksburg, VA 24061

Dr. Irwin Pollack
Mental Health Rsch Inst.
University of Michigan
Ann Arbor, MI 48104

Mr. C. E. Righter
Airesearch Mfg. Co.
Life Sciences Dept.
9851 Sepulved Blvd.
Los Angeles, CA 90009

Dr. Marshall J. Farr
Assoc Dir, Pers & Tng Programs
Code 458
Office of Naval Research
Washington, DC 20360

Director
Naval Research Laboratory
ATTN: Code 5143A
Washington, DC 20390

Commander & Director
Naval Training Device Center
ATTN: Technical Library
Orlando, FL 32813

US Navy Electronics Laboratory
ATTN: Chief, HF Div.
San Diego, CA 92152

Mr. Wardell B. Welch
US Navy Electronics Laboratory
Code 3400
San Diego, CA 92152

HQ ESD (ESTI)
L. G. Hanscom Field
Bedford, MA 01730

6570 AMRL (MRHE) (2)
Wright-Patterson AFB, OH 45433

6570 AMRL (MRHER/Mr. C. Bates, Jr.)
Wright-Patterson AFB, OH 45433

6570 AMRL (MRHE, Dr. M. J. Warrick)
Wright-Patterson AFB, OH 45433

AF Flight Dynamics Laboratory
ATTN: FDCR (CDIC)
Wright-Patterson AFB, OH 45433

HQ, 4442d Cmbt Crew Tng Wing (TAC)
Little Rock AFB
Jacksonville, AR 72076

AFHRL (DOJZ)
Brooks AFB, TX 78235

AMD (AMRH)
Brooks AFB, TX 78235

Defense Documentation Center (12)
Cameron Station
Alexandria, VA 22313

Department of Transportation Library
Reference & Research Branch, TAD-494.6
800 Independence Avenue, SW
Washington, DC 20591

US Postal Service Laboratory
ATTN: Mr. D. Y. Cornog
Chief, HF Group
11711 Parklawn Drive
Rockville, MD 20852

Dr. Edgar M. Johnson
US Army Inst. for Behavior & Soc Sciences
Room 239, The Commonwealth Bldg.
1320 Wilson Blvd.
Arlington, VA 22209

Civil Aeromedical Institute
Federal Aviation Agency Aeronautical Ctr.
P. O. Box 25082
Oklahoma City, OK 73125

Human Resources Rsch Organization
300 North Washington St.
Alexandria, VA 22313

Prof. James K. Arima
Department of Operations Analysis
Naval Postgraduate School
Monterey, CA 93940

Commander
USAVSCOM
ATTN: AMSAV-R-F (Mr. S. Moreland)
P. O. Box 209
St. Louis, MO 63166

Institute for Defense Analysis
ATTN: Dr. J. Orlansky
400 Army-Navy Drive
Arlington, VA 22202

Dr. Arthur Rubin
U. S. Dept. of Commerce
Bldg 226, Room A317
National Bureau of Standards
Washington, DC 20234

Mr. R. W. Young
Behavioral Sciences Department
Armed Forces Radiobiology Rsch Inst.
Bethesda, MD 20014

American Institutes for Research Library
710 Chatham Ctr Ofc Bldg.
Pittsburgh, PA 15219

American Institutes for Research/Kensington
ATTN: ISB
10605 Concord St.
Kensington, MD 20795

American Institutes for Research
ATTN: Library
8555 16th St.
Silver Spring, MD 20910

American Institutes for Research
ATTN: Library
P. O. Box 1113
Palo Alto, CA 94302

The Franklin Institute Rsch Labs.
ATTN: Tech Report Library
20th & Benjamin Franklin Parkway
Philadelphia, PA 19103

Manager, Behavioral Sciences
Litton Scientific Support Lab.
P. O. Box 379
Fort Ord, CA 93941

Purdue University
Serials Unit
Lafayette, IN 47907

Documents Librarian
Wilson Library
University of Minnesota
Minneapolis, MN 55455

The University of Wyoming
ATTN: Documents Library
University Station, Box 3334
Laramie, WY 82070

Psychology Abstracts
1200 17th Street, NW
Washington, DC 20036

AC Electronics Div., GMC
Tech Library, Dept. 32-55 2A
Milwaukee, WI 53201

BioTechnology, Inc.
ATTN: Librarian
3027 Rosemary Lane
Falls Church, VA 22042

The Boeing Company
Vertol Div., Boeing Center
ATTN: Mr. W. Jablonski
P. O. Box 16858
Philadelphia, PA 19142

Librarian
Chrysler Defense Engineering
P. O. Box 1316
Detroit, MI 48231

Grumman Aircraft Eng. Corp.
ATTN: Mr. L. Bricker, Life Scientist
Plant 5
Bethpage, LI, NY 11714

Hughes Aircraft Company
ATTN: Co. Tech Doc Ctr, E-110
Centinela at Teale Street
Culver City, CA 90230

Research Analysis Corp.
ATTN: Document Library
McLean, VA 22101

Ritchie, Inc.
630 Brubaker Drive
Dayton, OH 45429

Sprint Human Factors MP 537
Martin Company
Orlando, FL 32805

Dr. Charles Abrams
Human Factors Research
Santa Barbara Research Park
Goleta, CA 93017

Dr. Earl Alluisi
VP for Planning & Inst. Rsch.
University of Louisville
Louisville, KY 40208

Dr. Nancy Anderson
Department of Psychology
University of Maryland
College Park, MD 20742

Mr. Jack W. Ruby
Dept. 2601, Eng & Rsch Staff
Ford Motor Co.
P. O. Box 2053
Dearborn, MI 48126

Dr. S. Seidenstein
Org. 55-60, Bldg. 151
Lockheed, P. O. Box 504
Sunnyvale, CA 94088

Mr. John Senders
Senders Associates, Inc.
195 West Street
Waltham, MA 02154

Dr. John B. Siegfried
Dept. of Psychology
University of Houston
Houston, TX 77004

Dr. Arnold M. Small
Inst. of Aerospace Safety & Mgmt.
University of Southern Calif.
Los Angeles, CA 90007

Dr. F. Loren Smith (2)
Department of Psychology
University of Delaware
Newark, DE 19711

Dr. Howard W. Stoudt
Harvard University
School of Public Health
655 Huntington Ave.
Boston, MA 02115

Dr. Harvey A. Taub
Rsch Sec., Psych Svc.
Veterans Administration Hospital
Irving Ave. & University Place
Syracuse, NY 13210

Dr. Leonard Uhr
Computer Sciences Dept.
University of Wisconsin
1210 Dayton St.
Madison, WI 53706

Mr. Wesley E. Woodson
MAN Factors Inc.
4433 Convoy St., Suite D
San Diego, CA 92111

Dr. Richard A. Wunderlich
Psychology Dept.
Catholic University
Washington, DC 20017

Dr. Albert Zavala
Cornell Aeronautical Laboratory, Inc.
P. O. Box 235
Buffalo, NY 14221

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Human Factors Group Biomedical Laboratory Edgewood Arsenal, Maryland 21010		2a. REPORT SECURITY CLASSIFICATION Unclassified	
		2b. GROUP	
3. REPORT TITLE HISTORICAL DOCUMENTATION OF THE INFANTRY HELMET RESEARCH AND DEVELOPMENT (USAMC Five-Year Personnel Armor System Technical Plan)			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (First name, middle initial, last name) Charles W. Houff Joseph P. Delaney			
6. REPORT DATE February 1973		7a. TOTAL NO. OF PAGES 108	7b. NO. OF REFS 380
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S) Technical Memorandum	
b. PROJECT NO. 1J664713DL40		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) AMCMS Code 564M.55.L40	
c.			
d.			
10. DISTRIBUTION STATEMENT Distributed limited to U. S. Government agencies only; test and evaluation; February 1973. Other requests for this document must be referred to Director, U. S. Army Human Engineering Laboratory, Aberdeen Proving Ground, Maryland 21005.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY U. S. Army Human Engineering Laboratory Aberdeen Proving Ground, Maryland 21005	
13. ABSTRACT <p>This report documents the history of U. S. infantry helmets from 1917 to 1971. Major topics are presented in separate sections: Ballistic Protection, Materials Technology, Suspension and Retention, Acoustic Characteristics, Eye Protection and Visual Field, Anthropometrics and Mathematical Models of the Head, Wound Ballistics, and Funding. Discussion of helmet design includes one-piece versus two-piece (shell and liner), one size versus multiple sizes, pad versus multiple-web suspension, and area coverage. The current evaluation procedure, Casualty Reduction Analysis, is also discussed.</p> <p>The report concludes that the helmet program contained in the USAMC Five-Year Personnel Armor System Technical Plan adequately addresses the major problem areas established by this documentation. It concludes further that the systems approach is appropriate for problems of incompatibility and for optimizing the total ballistic protection for the combat soldier.</p>			

KEY WORDS

LINK A

LINK B

LINK C

ROLE

WT

ROLE

WT

ROLE

WT

Infantry Helmets
Ballistic Protection
Materials Technology
Suspension and Retention
Acoustic Characteristics
Eye Protection
Visual Field
Anthropometrics
Mathematical Models of the Head
Wound Ballistics
Funding
Human Factors Engineering

